

TACC INTERNATIONAL CORP. -- NEOPRENE RUBBER ADHESIVE -- 8040-00-273-8717

=====
Product Identification
=====

Product ID:NEOPRENE RUBBER ADHESIVE

MSDS Date:03/17/1994

FSC:8040

NIIN:00-273-8717

MSDS Number: CHKGR

=== Responsible Party ===

Company Name:TACC INTERNATIONAL CORP.

Address:AIR STATION INDUSTRIAL PARK

Box:390

City:ROCKLAND

State:MA

ZIP:02370

Country:US

Info Phone Num:617-878-7015

Emergency

Phone Num:617-878-7015

CAGE:0HZU1

=== Contractor Identification ===

Company Name:TACC INTERNATIONAL CORP

Address:AIR STATION INDUSTRIAL PARK

Box:City:ROCKLAND

State:MA

ZIP:02370

Country:US

Phone:781-878-7015

CAGE:0HZU1

=====
Composition/Information on Ingredients
=====

Ingred Name:HEXANE (SARA 313) (CERCLA) VP 0

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: 20-50%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:50 PPM

ACGIH TLV:50 PPM

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Na

me:TOLUENE (SARA 313) (CERCLA) VP = 22 @ 68F CEILING LIMIT 300
PPM, PEAK 500 PPM
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 5-20%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM/STEL 150
ACGIH TLV:50 PPM/STEL 150
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL ALCOHOL (ETHANOL) (SARA 313) VP = 40 @ 68F
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM/STEL 250
ACGIH TLV:1000 PPM/STEL 250

=====
Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: REMOVAL OF
SKIN OILS, IRRITATION, DERMATITIS, SENSITIZATION W/LONG
OVER-EXPOSURE. INHAL: HEADACHE, DIZZY, NAUSEA, UPPER RESPIRATORY
DRYNESS, IRRITATION, DROSY, MENTAL DEPRESSIO N, NARCOSIS, BREATHING
DIFFICULTY.
Effects of Overexposure:CHRONIC: EFFECTS OF OVER-EXPOSURE TO SOLVE
NT
VAPORS COULD LEAD TO PERMANENT EFFECTS OF NS, BRAIN, BODY ORGANS.
USE W/ADEQUATE VENTILATION.
Medical Cond Aggravated by Exposure:NONE

=====
First Aid Measures =====

First Aid:EYES: FLUSH W/WATER 15 MINUTES. SKIN: WASH W/MILD SOAP &
WATER. APPLY MILD CREAM. INHAL: GET FRESH AIR, GET MED AID. INGEST:
CALL POISON CONTROL CENTER IMMED.

=====
Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:

0F,-18C

Lower Limits:1.1

Upper Limits:12.3

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR FOG.

Fire Fighting Procedures:AVOID BREATHING SMOKE. USE AIR SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED AREA. WATER TENDS TO SPREAD BURNING LIQUID IF LARGE AMOUNTS USED.

Unusual Fire/Explosion Hazard:VAPORS IGNIT EXPLOSIVELY, CAUSE FLASH FIRES. ELIMINATE IGNITS. USE ADEQUATE CROSS VENT SUFFICIENT TO REMOVE VAPORS. ELECTRICALLY GROUND CONTAINER DURING TRANS

=====

===== Accidental Release Measures =====

Spill Release Procedures:SM SP: ABSORB W/APPROPRIATE ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CNTNR CLSD WHEN NOT IN USE. STORE @60-90F OUT OF THE SUN. ADEQUATE VENT TO AVOID BREATHING WHEN COVER IS REMOVED. GROUND EQUIPMENT WHEN TRANSPORT

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VAPORS EXCEED TLV,
USE NIOSH APPROVED
SELF-CONTAINED ORGANIC MASK.

Ventilation:SUFFICIENT TO KEEP WORK ROOM CONCENTRATION BELOW TLV.

Protective Gloves:CHEMICAL RESISTANT

Eye Protection:SAFETY GLASSES/FACE SHIELD.

Other Protective Equipment:BARRIER CREAM FOR SENSITIVE SKIN.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:133 TO 231F

Melt/Freeze Pt:M.P/F.P Text:NA

Decomp Temp:Decomp Text:NA

Vapor Pres:NA

Vapor Density:>AIR

Spec Gravit

y:0.81393

pH:NA

Evaporation Rate & Reference:FASTER THAN (BUAC)

Solubility in Water:NA

Appearance and Odor:AMBER LIQUID, KETONE ODOR.

Percent Volatiles by Volume:84.1

Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG ACIDS AND BASES.

Stability Condition to Avoid:FIRE, SPARKS, STATIC ELECTRICITY

Hazardous Decomposition Products:OXIDES OF CARBON.

===== Disposal Cons

iderations =====

Waste Disposal Methods:IN ACCORDANCE W/FEDERAL, STATE AND LOCAL
REGULATIONS. DRIED ADHESIVE MAY BE DISPOSED OF AS ORDINARY WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person uti

lizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.