

ENGLEHARD CORP. SPECIALTY METALS DIV. -- SILVALOY 15 SILVER-COPPER-PHOSPHORUS
BRAZING ALLOY -- 3439-00-204-2555

=====
Product Identification
=====

Product ID:SILVALOY 15 SILVER-COPPER-PHOSPHORUS BRAZING ALLOY

MSDS Date:11/13/1997

FSC:3439

NIIN:00-204-2555

MSDS Number: CHKWV

=== Responsible Party ===

Company Name:ENGLEHARD CORP. SPECIALTY METALS DIV.

Address:235 KILVERT ST

City:WARWICK

State:RI

ZIP

:02886

Country:US

Info Phone Num:401-739-9550

Emergency Phone Num:800-424-9300(CHEMTREC)

CAGE:86337

=== Contractor Identification ===

Company Name:ENGELHARD CORP

Address:235 KILVERT ST

Box:City:WARWICK

State:RI

ZIP:02886

Country:US

Phone:401-739-9550

CAGE:86337

Company Name:ENGELHARD CORP SPECIALTY CHEM DIV RESEARCH DEPT

Address:MENLO PARK

Box:City:EDISON

State:NJ

ZIP:08817

Country:US

Phone:908-205-5000

CAGE:9A166

=====
Composition/Information on Ingredients
=====

Ingred Name

:COPPER (SARA 313) (CERCLA)

CAS:7440-50-8

RTECS #:GL5325000

Fraction by Wt: 74-94%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.1MG/M3 FUME/1 DUST

ACGIH TLV:0.2 MG/M3 FUME; 9596

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:SILVER (SARA 313) (CERCLA)

CAS:7440-22-4

RTECS #:VW3500000

Fraction by Wt: 0.5-19%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.01 MG/M3

ACGIH TLV:0.1 MG/M3; 9596

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:PHOSPHOROUS (YELLOW) (SARA 302/313) (CERCLA)

CAS:7723-14-

0

RTECS #:TH3500000

Fraction by Wt: 2-8%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.1 MG/M3

ACGIH TLV:0.02 PPM; 9596

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE/SKIN:IRRIT.INHAL:IRRIT RESP

TRACT.SHORTTERM OVEREXPO MAY CAUSE FLU-LIKE ILL

NESS(METAL FUME

FEVER).TYPICALLY METAL FUME FEVER BEGINS 4-12HRS AFT SUFFICIENT

EXPO TO FRESHLY FORMED FUMES.SYNDROME RUN S ITS COURSE IN

24-48HRS.INGEST:HARMFUL.MAY CAUSE ABDOMINAL

PAIN,NAU,VOMIT,DIARR.COPPER POIS CAN RESULT IN (SUPPLEMENTA)

Explanation of Carcinogenicity:PER

MSDS:CARCINOGENICITY:NPT/IARC/OSHA:NO.

Effects of Overexposure:OVEREXPO MAY CAUE KIDNEY/LIVER DMG,BLOOD

DISORDERS.MAY CAUSE RESP TRACT IRRIT.OVEREXPO TO FRESHLY FORMED

FUMES MAY CAUSE FLU-LIKE I

ILLNESS CALLED METAL FUME FEVER.HARMFUL IF
LARGE AMOUNTS SWALLOWED.MAY CAUSE GI IRRITATION,NAUSEA,VOMITING,DIARRHEA.MAY CAUSE
EYE/SKIN IRRITATION.

Medical Condition Aggravated by Exposure:MAY ADVERSELY AFFECT EXISTING MEDICAL
CONDITIONS SUCH AS EYE,SKIN,RESPIRATORY,BLOOD,LIVER, &/OR KIDNEY
AILMENTS.INDIVIDUALS WITH WILSON'S DISEASE @INCREASED RISK OF COPPER POISONING.

===== First Aid Measures =====

First Aid:EYE:FLUSH WITH PLENTY OF WATER.IRRITATION DEVELOPS CALL DOCTOR.SKIN:IMMEDIATE
WASH WITH SOAP/PLENTY
OF WATER.IRRITATION PERSISTS CALL DOCTOR.INHALATION:EXPOSURE TO
EXCESSIVE LEVELS OF METAL FUMES REMOVE TO FRESH AIR.SEEK MEDICAL
ATTENTION.INGESTION:PROCEDURES NORMALLY NOT NEEDED.IF LARGE QUANTITIES
INGESTED SEEK MEDICAL ADVICE.

===== Fire Fighting Measures =====

Autoignition Temp:Autoignition Temp Text:NA

Lower Limits:NOT APPLICABLE

Upper Limits:NOT APPLICABLE

Extinguishing Media:USE CO2,CHEMICAL FOAM,DRY CHEMICAL.USE ANY MEANS FOR
EXTINGUISHING SURROUNDING FIRE.DON'T USE WATER ON METAL
FIRES.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED POSITIVE-PRESSURE
SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING AS
SPECIFIED IN 29CFR1910.156.

Unusual Fire/Explosion Hazard:NOT FIRE/EXPLOSION HAZARD IN SOLID FORM.FINELY
DIVIDED DUST MAY IGNITE,BURN RAPIDLY WHEN MIXED WITH AIR IN PROPER
PROPORTIONS.TOXIC METAL FUMES MAY BE RELEASED IN FIRE SITUATION

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN.SCOOP UP/VACUUM.NOTIFICATION
OFFICIALS

RESPIRATORY PROTECTION 800-424-8802 MAY BE REQUIRED.REFER EPA/DOT/APPLICABLE
STATE/LOCAL REGULATIONS FOR CURRENT RESPONSE INFORMATION.RECOMMEND EACH USER ESTABLISH
SPILL CONTROL PLAN-INCLUDE PROPER STORAGE/CONTAINER/CLEANUP,REUSE/DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL DRY LOCATION AWAY FROM
INCOMPATIBLE MATERIALS.AVOID CONTACT WITH DUST/MIST/FUMES RESULTING FROM
USE OF PRODUCT.USE ONLY WITH ADEQUATE

E VENTILATION.

Other Precautions:DONT EAT/DRINK/SMOKE IN WORKAREA.PESONNEL SMPL
PROCEDURE:CU:NIOSH MANUAL ANALYTICAL METHODS,4TH ED,METHOD
7029;PHOSPHORUS:SAME MANUAL ABOVE,METHOD 7905;SILVER:SAME MANUAL
ABOVE,METHOD 7300. DISPO:CHEM ADDN/PROCES/ALTER MATL MAKE INFO
INACCU

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:DUST/FUME GENERATED,NIOSH/MSHA APPROV RESP MAY
BE NECESSARY.FOLLOW ALL REQMTS FOR RESP PROGRAMS/SELECTION SET

FORTH IN OSHA REG(29CFR1910.134) & ANSI Z99.2(PRACTICES FOR RESP
PROTECTION).

Ventilation:GEN/LOC EXHAU VENTI AS NECESSARY TO CONTROL ANY AIR
CONTAMINANTS TO W/IN PELS/TLVS DURING USE OF PRODUCT.

Protective Gloves:REFER TO ANSI/ASC Z49.1-94

Eye Protection:SAFETY GLASSES(W/SIDE SHIELDS).

Other Protective Equipment:BODY PROTECTION AS NECESSARY TO PREVENT SKIN
CONTACT.

Work Hygienic Practices:WASH THOROUGHLY AFT HNDLG. SARA SEC 313
CHEMS:YES.

Supplemental Safety and Health

HEALTH:

HEMOLYTIC ANEMIA,KID/LIV/SPLEEN DMG.POT HEALTH EFFECTS DESCRIBED
ABOVE ONLY APPLY IF DUST/FUME FORMED.CHRONIC:PROL OVEREXPO TO
PHOSPORUS CAUSE GI DISTRESS,GARLIC BREATH,NECROSIS,DEFORMITY IN JA
W.SYSTEMIC EFFECTS(CARDIAC,LIV,KID,DYSFUNCTION)RESULT DUE TO PROL
FUME INHAL.ARGYRIA(PERM LOC BLUE-FREY DISCOLOR EYE/SK)

=====
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:NE

Melt/Freeze Pt:M.P/F.P Text:1178F,637C

Decomp Temp:Decomp Text:NP

V

apor Pres:NA

Vapor Density:NA

Spec Gravity:7.40-8.54

pH:NA

Viscosity:NP

Solubility in Water:INSOLUBLE

Appearance and Odor:METALLIC WIRE,ROD,STRIP; ODOLRESS

Percent Volatiles by Volume:NP

Corrosion Rate:NP

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS/BASES,OXIDIZING AGENTS,ACETYLENE,AMMONIA,H2O2,MG
METAL,AMMONIUM NITRATE,HYDROGEN SULFIDE,CHLORINATED RUBB.

Stability Condition to Avoid:NONE EXPECTED.

Hazardous Deco

Composition Products: TOXIC METAL OXIDES ARE EMITTED WHEN HEATED ABOVE MELTING POINT. AMT OF FUME EVOLVED INCREASES AS TEMPERATURES RISES.

===== Disposal Considerations =====

Waste Disposal Methods: CONTAINS AG/AG CMPDS-DISPO MAY BE REG UNDER HAZ WASTE D011. BEF DISPO PROD/MIX W/PROD SHOULD BE TESTED FOR TC UNDER EPA HAZ WASTE REGS TCLP TEST PROCEDURES(40CFR261 ET SEQ). DISPO/RECYCL/RECLAMA REQMS VARY BY LOC/TYP OF DISPO SELECTED. CONSULT AUTHORIT

=====
===== Other Information =====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.