

FISKE BROTHERS REFINING CO -- LUBRIPLATE 930/AA/AAA; 930-2 -- 9150-00-953-1694

=====
Product Identification
=====

Product ID:LUBRIPLATE 930/AA/AAA; 930-2

MSDS Date:01/01/1997

FSC:9150

NIIN:00-953-1694

MSDS Number: CHKXS

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:8038

City:TOLEDO

State:OH

ZIP:43605-3843

Country:US

Info Phone Num:419-691-2491 / FA

X 419-693-3806

Emergency Phone Num:800-255-3924 CHEM-TEL

Preparer's Name:JAMES R. KONTAK

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

Company Name:HERMAN YENCIES INC

Address:577 MAIN STREET

Box:688

City:PASSAIC

State:NJ

ZIP:07055

Country:US

Phone:973-777-7200 /FAX: 973-777-0954

Contract Num:SP0450-99-M-B303

CAGE:0B260

=====
Composition/Information
=====

on Ingredients =====

Ingred Name:NON-HAZARDOUS INGREDIENT

= Wt:100.

Code:F

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:TLV: 5 MG/M3 FOR OIL MIST IN AIR.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE IR

RITATION. THIS PRODUCT HAS A LOW ORDER OF ACUTE ORAL TOXICITY, BUT MINUTE AMOUNTS ASPIRATED IN TO THE LUNGS DURING INGESTION MAY CAUSE MILD TO SEVERE PULMONARY INJURY. HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. AS A PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS, AND FUMES SHOULD BE MINIMIZ ED.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:H

UMAN HEALTH RISKS VARY FROM PERSON TO PERSON.

AS A PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS AND FUMES SHOULD BE MINIMIZED. SKIN: IRRITATION. EYES: IRRITATION.

===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH CLEAR WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN. SKIN CONTACT: REMOVE CONTAMINATED CLOTHES AND WASH WITH SOAP AND WARM WATER. IF INJECTED UNDER SKIN, RE GARDLESS OF THE APPEARANCE OR ITS

SIZE, CONTACT A

PHYSICIAN IMMEDIATELY. DELAY MAY CAUSE LOSS OF OF AFFECTED PART OF BODY. INHALATION: VAPOR PRESSURE IS VERY LOW AND INHALATION AT ROOM TEMPERATURE IS NOT A PROBLEM. IF OVERCOME BY VAPOR FROM HOT PRODUCT, IMMEDIATELY REMOVE FROM EXPOSURE AND CALL A PHYSICIAN. INGESTION: IF INGESTED, CALL A PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:=204.4C, 400.F

Autoignition Temp:Autoignition Temp Text:UNKNON

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, OR WATER SPRAY (FOG).

Fire Fighting Procedures:COOL EXPOSED CONTAINERS WITH WATER. USE AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED OR CONFINED SPACES.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND OR WELD, AS THEY MAY EXPLODE.

===== Accidental
Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE, WASH REMAINDER WITH SUITABLE PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED SEWERS AND WATER COURSES.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME OR STRONG OXIDANTS.

Other Precautions:REMOVE OIL-SOAKED CLOTHING AND LAUNDER BEFORE REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED.
Ventilation:LOCAL EXHAUST VENTILATION TO CAPTURE FUMES AND VAPORS.
Protective Gloves:USE OIL-RESISTANT GLOVES, IF NEEDED.
Eye Protection:IF CHANCE OF EYE CONTACT, WEAR GOGGLES.
Other Protective Equipment:USE OIL-RESISTANT APRON, IF NEEDED.
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING.
Supplemental Safety and Health
MANUFACTURER'S PART NUMERS COVERED BY THIS MSDS INCLUDES P/N 930-A, NO. 930-2, NO. 930-AA, NO. 930-AAA.

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:>287.8C, 550.F
Melt/Freeze Pt:M.P/F.P Text:SEMI-SOLID
Vapor Pres:5
Spec Gravity:0.94-0.97
Evaporation Rate & Reference: