

CANON USA INC -- S-20 SILICONE OIL, FG2-5962 -- 6850-01-434-7708

===== Product Identification =====

Product ID:S-20 SILICONE OIL, FG2-5962

MSDS Date:03/01/1993

FSC:6850

NIIN:01-434-7708

MSDS Number: CHPJY

=== Responsible Party ===

Company Name:CANON USA INC

Address:ONE CANON PLAZA

City:LAKE SUCCESS

State:NY

ZIP:11042

Country:US

Info Phone Num:516-328-5600

Emergency Phone Num:800-424-9300 (CHEMTREC

)

Preparer's Name:JOSEPH PALMERI

CAGE:1BA63

=== Contractor Identification ===

Company Name:CANON USA INC

Address:ONE CANON PLZ

Box:City:NEW HYDE PARK

State:NY

ZIP:11042

Country:US

Phone:516-328-5000; 5600

CAGE:08YZ7

Company Name:CANON USA INC

Address:ONE CANON PLAZA

Box:City:LAKE SUCCESS

State:NY

ZIP:11042

Country:US

Phone:516-328-5600

CAGE:1BA63

===== Composition/Information on Ingredients =====

Ingred Name:POLY (DIMETHYLSILOXANE); (SILICONE)

CAS:63148-62-9

RTECS #:JJ6484500

Fraction by Wt: 100%  
OSHA PEL:N/K  
ACGIH TLV:N/K

Ingred Name:SUP DAT: (INCL CARPETING) CLEANED COMMERCIALY. PETRO  
DISTILS MAY BE USED, EXCEPT ON PLASTIC/VINYL SURFACES. (ING 3)  
RTECS #:9999999ZZ

Ingred Name:ING 2: DISPOSE OF ABSORBENT MATERIAL IN ACCORDANCE WITH  
APPLICABLE FEDERAL, STATE, AND LOCAL REQUIREMENTS.  
RTECS #:9999999ZZ

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT): > 5 G/KG.  
Routes of Entry: Inhalation:YES Skin:Y  
ES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: SKIN: MAY CAUSE SLIGHT  
IRRITATION, BUT NO SIGNIFICANT EFFECT. EYES: MAY CAUSE SLIGHT  
IRRITATION. CHRONIC: NO KNOWN CHRONIC HEALTH EFFECTS, BUT  
UNNECESSARY EXPOSURE TO ANY CHEMICAL SHOULD BE AVO IDED.  
Explanation of Carcinogenicity:NOT RELEVANT.  
Effects of Overexposure:SEE HEALTH HAZARDS.  
Medical Cond Aggravated by Exposure:THIS PRODUCT, AS WITH ANY CHEMICAL,  
MAY ENHANCE  
ALLERGIC CONDITIONS ON CERTAIN PEOPLE.

=====  
===== First Aid Measures =====

First Aid:INHALATION: NO FIRST AID SHOULD BE REQUIRED. REMOVE TO FRESH  
AIR. SUPPORT BREATHING (GIVE OXYGEN OR ARTIFICIAL RESPIRATION) .  
EYES: OPEN EYE AND FLUSH WITH FOR AT LEAST 15 MINUTES. IF  
IRRITATION PERSISTS, GET MEDICAL ATTENTION. SKIN:SINGLE PROLONGED  
EXPOSURE CAUSES NO KNOWN ADVERSE EFFECT; WIPE AND FLUSH WITH WATER.  
INGESTION: NO FIRST AID SHOULD BE REQUIRED  
. CALL MD IMMEDIATELY .

=====  
===== Fire Fighting Measures =====

Flash Point:610F,321C  
Extinguishing Media:WATER FOG, DRY CHEMICAL, FOAM, CARBON DIOXIDE.  
Fire Fighting Procedures:WEAR NIOSH APPROVED SCBA AND FULL PROTECTIVE  
EQUIPMENT .  
Unusual Fire/Explosion Hazard:NONE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN  
FOR SALVAGE OR DISPOSAL.  
Neutralizing Agent:NONE

SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:USE REASONABLE CARE AND CAUTION. STORE IN A COOL AREA. KEEP AWAY FROM HEAT AND FLAME. DO NOT LAY CONTAINER ON ITS SIDE.

Other Precautions:AT ELEVATED TEMPERATURES THIS PRODUCT IS SENSITIVE TO CONTAMINATION. IF THIS PRODUCT BECOMES CONTAMINATED W/STRONG ACIDS, BASES/SOME METALLIC COMPOUNDS & OXIDIZING AGENTS, FLASH POINT VISCOSITY MAY CHANGE & SHOULD BE REDETERMINED. (SUP DAT)

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO RESPIRATORY PROTECTION REQUIRED. USE NIOSH APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:NONE SPECIFIED BY MANUFACTURER.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGLES .

Other Protective Equipment:EMERGENCY EYEWASH AND DELUGE SHOWER MEETING ANSI DESIGN CRITERIA .

Work Hygienic Practices:WASHING AT MEAL TIME AND END OF SHIFT IS ADEQUATE.

Supplemental Safety and Health

OTHER PREC: NOTE: THIS OIL IS VERY SLIPPERY & MAY PRESENT SKIDDING/SLIPPING HAZARD. FOLLOWING SPILL/LEAK, USE ABSORB MATL TO CONTAIN & COLLECT EXCESSIVE OIL FOR SALVAGE/DISP. THOROUGHLY CLEAN FLOOR/OTHER CONTAM SURFACE (SUCH AS LADDER) & DO NOT LEAVE ANY TRACES OF OIL. USE ALL-PURPOSE ALKALINE CLEANER/HAVE SURFACE (ING 2)

=====  
===== Physical/Chemical Properties =====

Vapor Pres: