

MOBIL OIL CORP -- MOBIL EAL ARCTIC 46 -- 9150-01-443-9396

===== Product Identification =====

Product ID:MOBIL EAL ARCTIC 46

MSDS Date:12/16/1996

FSC:9150

NIIN:01-443-9396

Status Code:A

MSDS Number: CHXDX

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:3225 GALLONS ROAD

City:FAIRFAX

State:VA

ZIP:22037-0001

Country:US

Info Phone Num:800-662-4525/800-227-0707 X3265

Emergency Phone Num:

609-737-4411/CHEMTREC 800-424-9300

CAGE:3U728

=== Contractor Identification ===

Company Name:MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWS ROAD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525/ 856-224-4644

CAGE:3U728

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA

ZIP:70058

Country:US

Phone:504-366-4542

CAGE:0T5C6

===== Composition/Information on Ingredients =====

Ingred Name:SYNTHETIC COMPRESSOR O

IL, NJT 003066009-5139.

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL (RATS) LD5):>2000MG/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:BASED ON TESTING OF SIMILAR PRODUCTS

&/OR COMPONENTS.ORAL/DERM:PRACTICALLY NON-TOXIC.EYE

IRRIT:PRACTICALLY NON-IRRIT.INHAL:PRACTICALLY NON-TOXIC.

Effects

of Overexposure:NONE

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE:FLUSH WELL W/WATER.IRIT OCCURS CALL DR.SKIN:WASH

W/SOAP/WATER.HI PRESSURE ACCIDENTAL INJECTION THRU SKIN REQUIRES

IMMED MED ATTN FORPOSSIBLE INCISION &/OR

DEDRIDEMENT.INHAL/INGEST:NOT EXPECTED TO BE PROBLEM.HOWEVER

>1/2LITER(PT)INGESTED IMMED GIVE 1-2GLASSES OF WATER.CALL DR/HOSP

EMERG RM/POIS CNTRL CNT

R FOR ASSIST.DONT INDUCE VOMIT OR GIVE

ANYTHING BY MOUTH IF UNCONSC.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:446F,230C

Autoignition Temp:Autoignition Temp Text:NE

Lower Limits:NA

Upper Limits:NA

Extinguishing Media:CARBON DIOXIDE,FOAM,DRY CHEM,WATER FOG.

Fire Fighting Procedures:H2O/FOAM MAY CAUSE FROTH.USE H2 TO KEEP FIRE

EXPO CNTNR COOL.H2OSPRAY MAY BE USED TO FLUSH SPILL AWAY FRM

EXPO.PREVENT RUNOFF FRM FIRE CNTRL/D

IL ENTER (SUPPLE)

Unusual Fire/Explosion Hazard:NONE.

===== Accidental Release Measures =====

Spill Release Procedures:REPORT AS REQUIRE TO APPROP AUTHORITIES.REGS

REQUIRE IMMED REPOTOFALL OILS SPILLS THAT COULD REACH H2OWAY

INCLUDE WETLANDS/INTERMIT DRY CREEKS TO NAT RESP CNTR

800-424-802.ACCIDENT/RD SPILL 800-424-93 00(CHEMTREC).SM-ABSORB

W/FIRE RETARDANTTREAT(SUP)

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling

and Storage =====

Handling and Storage Precautions:MATL NOT INTENDED FOR USE IN AIR
COMPRESSORS FOR BREATH APPLICATION.DONT STORE IN OPN/UNLABEL
CNTNR.STORE AWAY FRM STORNG OXID AGENTS/COMBUST MATLS.

Other Precautions:UNUSED PROD IN MOBIL OPINION NOT SPEC LISTED BY EPA
AS HAZ WASTE NOR FORM TO CONTAIN MATLS WHICH ARE LISTED HAZ
WASTE.DOESNT EXHIBIT HAZ CHARACT OF IGN,ETC DETERMINED BY TCLP.USED
PROD MAY BE REGULATE D.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQMTS UNDER ORDINARY CONDITIONS OF
USE & WITH ADEQUATE VENTILATION.

Ventilation:NO SPECIAL REQMT UNDER ORDINARY CONDITIONS OF USE ADN WITH
ADEQUATE VENTILATION.

Protective Gloves:NO SPECIAL EQPMT REQUIRED

Eye Protection:NORM INDUST PROT PRACTICES

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:GOOD PERSONAL HYGIENE PRACTICES SHOULD ALWAYS
BE FOLLOWED.

Supplemental Safety and Health

FI

REFIGHT:STREAM/SEWER/DRINK H2O SUPP.FIRE IN ENCLSD AREA-MUST USE
SCBA. SPILL:SAWDUST,DIATOMA EARTH,ETC.CONTAIN/REMOVE LG SPILL FOR
SALVG/DISPO.PREVENT FRM ENTER STORM SEWER/DRAIN/SOIL CONTACT. DISP:
CNTRL BURNER FOR FUEL VALUE,RECYC @APPROV FAC,DISP @WSATE DISP
FAC.LAND FARM/PROCESS THRU SEWAGE TREAT FAC-MUST APPROV

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>601F,>316C

Melt/Freeze Pt:M.P/F.P Text:NA

Decomp Temp:Decomp Text:

NP

Vapor Pres: