

FARWEST PAINT MFG CO -- (X-5899) LEAD FREE LATEX TRAFFIC PAINT -- 8010-01-019-1776
===== Product Identification =====

Product ID:(X-5899) LEAD FREE LATEX TRAFFIC PAINT

MSDS Date:06/01/1997

FSC:8010

NIIN:01-019-1776

MSDS Number: CHXSG

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

Box:68726

City:SEATTLE

State:WA

ZIP:98168-3251

Country:US

Info Phone Num:206-244-88

44

Emergency Phone Num:206-244-8844

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

===== Composition/Information on Ingredients =====

Ingred Name:ETHYLENE GLYCOL (SARA 313) (CERCLA)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: .01%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:50 PPM

ACGIH TLV:50 PPM

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 L

B

Ingred Name:TEXANOL (ESTER ALCOHOL)

CAS:25265-77-4

Fraction by Wt: .01%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA 313) (CERCLA)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: .02%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:200PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports

of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALE: MUCCUS MEMBRANE IRRITATION,
DIZZINESS, HEADACHE; SKIN: IRRITATION; EYES: IRRITATION; INGEST:
COULD CAUSE SERIOUS INJURY

=====
===== First Aid Measures =====

First Aid:INHALE: REMOVE TO FRESH AIR; GET MED AID IMMEDIATELY. SKIN:
WASH OFF QUICKLY WITH MUCH WATER; THEN SOAP AND WATER; REMOVE AND
WASH CONTAM CLOTHING BEFORE REUSE. EYES: FLUSH IMMED WITH MUCH
WATE

R, ESP UNDER LIDS, AT LEAST 15 MIN; GET EMERGENCY MED
TREATMENT. INGEST: OBTAIN MED TREATMENT IMMED.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Extinguishing Media:FOAM, DRY CHEMICAL, WATER, WATER FOG

Fire Fighting Procedures:WEAR SCUBA; EVACUATE AREA; WEAR PROTECTIVE
CLOTHING

Unusual Fire/Explosion Hazard:WILL NOT BURN; CLOSED CONTAINERS MAY
BURST IF EXPOSED TO HEAT. WATER MAY BE USED TO COOL AND PROTECT
EXPOSED CONTAINERS.

==

===== Accidental Release Measures =====

Spill Release Procedures:COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGS; VENT AREA; SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID TEMPS BELOW 40F; KEEP FROM FREEZING; STORE CONTAINERS WITH LIDS TIGHTLY CLOSED AND PROPERLY LABELED.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR PROPERLY FITTED, ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/OSHA

Ventilation:LOCAL EXHAUST PREFERABLE; GENERAL EXHAUST ACCEPTABLE; USE ONLY WITH ADEQUATE VENTILATION

Protective Gloves:IMPERVIOUS, AS RECCOMENDED BY SUPPLIER

Eye Protection:SAFETY SPECS W/UNPERFORATED SIDE-SHIELD*

Other Protective Equipment:EYEWASH, SAFETY SHOWERS

Work Hygienic Practices:KEEP WORK AREA CLEAN AND FREE FROM SPILLS AND LEAKS; ALWAYS WASH

HANDS WITH SOAP BEFORE HANDLING FOOD OR SMOKING

Supplemental Safety and Health

*GOGGLES AND SAFETY GLASSES

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C

Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C

Vapor Pres:23.8

Vapor Density:>AIR

Spec Gravity:1.3800

VOC Pounds/Gallon:92

pH:9

Viscosity:70-90KU

Evaporation Rate & Reference: