

MARKEL CORPORATION -- FLEXLITE HT-105 PVC TUBING -- 5970-00-802-5030

=====
Product Identification
=====

Product ID:FLEXLITE HT-105 PVC TUBING

MSDS Date:10/05/1998

FSC:5970

NIIN:00-802-5030

Status Code:A

MSDS Number: CJCLW

=== Responsible Party ===

Company Name:MARKEL CORPORATION

Address:1959 SCHOOL LANE

Box:752

City:NORRISTOWN

State:PA

ZIP:19404

Country:US

Info Phone Num:215-272-8960

Emergency Ph

one Num:215-272-8960

CAGE:03890

=== Contractor Identification ===

Company Name:MARKEL CORPORATION

Address:1959 SCHOOL LANE

Box:752

City:NORRISTOWN

State:PA

ZIP:19404

Country:US

Phone:215-272-8960

CAGE:03890

=====
Composition/Information on Ingredients
=====

Ingred Name:NON-HAZARDOUS INGREDIENTS

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes o

f Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NONE KNOWN.
Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.
Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:NONE NORMALLY NEEDED.

=====
===== Fire Fighting Measures =====
==

Extinguishing Media:WATER; MATERIAL IS NORMALLY SELF-EXTINGUISHING IN
NORMAL ATMOSPHERE.
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS FOR
FIRES IN CONFINED AREAS SUCH AS WAREHOUSES.
Unusual Fire/Explosion Hazard:WHEN FORCED TO BURN, THESE TUBES WILL
CONTRIBUTE MOSTLY CARBON MONOXIDE, CARBON DIOXIDE AND HYDROGEN
CHLORIDE AS BASES AND SMOKE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SWEEP UP.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:NORMAL HOPUSEKEEPING. RECOMMEND
STORAGE AWAY FROM LARGE AMOUNTS OF EASILY COMBUSTIBLES, HEAT AND
IGNITION SOURCES.
Other Precautions:NONE KNOWN.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN THE EVENT OF FIRE, WEAR SELF-CONTAINED
BREATHING APPARATUS.
Ventilation:LOCAL EXHAUST RECOMMENDED AS GENERA

L GOOD SAFETY PRACTICE

AND MANUFACTURING POLICY.

Protective Gloves:NONE NORMALLY REQUIRED.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:NONE NORMALLY REQUIRED.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

ITEM IS AN ARTICLE UNDER 29 CFR 1910.1200 AND NO MSDS IS REQUIRED.

===== Physical/Chemical Properties =====

HCC:N1

Spec Gravity:1.31

Evaporation Rate & Reference:NON-VOLATILE

Solubility in Water:INSOLUB

LE

Appearance and Odor:FLEXIBLE, THIN-WALLED PLASTIC TUBING. MILD,
NON-OFFENSIVE ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:NO

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:TEMPERATURES IN EXCESS OF 400F.

Hazardous Decomposition Products:MAINLY CARBON MONOXIDE, CARBON DIOXIDE
AND HYDROGEN CHLORIDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

=====

Waste Disposal Methods:SANITARY LANDFILL OR INCINERATOR. IF
INCINERATION IS USED; RECOGNIZE THAT CARBON MONOXIDE, CARBON
DIOXIDE AND HYDROGEN CHLORIDE ARE GENERATED AND APPLY APPROPRIATE
LOCAL, STATE AND FEDERAL REGULATIONS .

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this infor

mation to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.