

NORTECH ADHESIVE CORP. -- MORTECH 2109 -- 8040-00-264-3848

=====
Product Identification
=====

Product ID:MORTECH 2109

MSDS Date:01/01/1985

FSC:8040

NIIN:00-264-3848

Status Code:A

MSDS Number: CJDFG

=== Responsible Party ===

Company Name:NORTECH ADHESIVE CORP.

Emergency Phone Num:201-653-8647

CAGE:0GD30

=== Contractor Identification ===

Company Name:MILITARY SPECIFICATIONS PROMULGATED BY MILITARY

Address:DEPTS/AGENCIES UNDER AUTH OF DEF STD

Box:MANUAL

City:4120 3-M

Phone:804-279-4371 DSN 695-4371

CAGE:81349

Company Name:NORTECH ADHESIVE CORP

Address:136 HALLADAY STREET

Box:5256

City:JERSEY CITY

State:NJ

ZIP:07305

Country:US

Phone:201-433-3766

CAGE:0GD30

Company Name:TRANS WORLD ADHESIVE & CHEMICALS

Box:City:U/N

Phone:U/N

CAGE:TO023

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENTS

Fraction by Wt: 70%

ACGIH TLV:100PPM

Ingred Name:POLYMERS

Fractio

n by Wt: 30%

=====
Hazards Identification
=====

Effects of Overexposure: CAN CAUSE IRRITATION TO EYES, SKIN AND RESPIRATORY TRACT.

=====
First Aid Measures
=====

First Aid: FOR SKIN CONTACT WASH WITH WATER AND SOAP. FOR EYE CONTACT WASH WITH WATER AND CALL PHYSICIAN. FOR EXCESSIVE INHALATION, REMOVE TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

=====
Fire Fighting Measures
=====

==

Flash Point: 20F TCC -7C

Lower Limits: 1.8

Upper Limits: 1.5

Extinguishing Media: FOG, FOAM, DRY CHEMICAL OR CO*2

Fire Fighting Procedures: HANDLE AS VERY FLAMMABLE LIQUID

=====
Accidental Release Measures
=====

Spill Release Procedures: ABSORBENT CLEANING SOLVENT

=====
Handling and Storage
=====

Handling and Storage Precautions: AVOID OPEN FLAMES AND SPARK SOURCES. PROVIDE ADEQUATE VENTILATION. AVOID EXCESSIVE HEAT.

=====

Exposure Controls/Personal Protection
=====

Respiratory Protection: RESPIRATOR APPROVED FOR ORGANIC SOLVENT

Ventilation: AS REQUIRED

Protective Gloves: RUBBER OR POLYE

Eye Protection: GOGGLES TO PREVENT EYE CO

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC: F2

Boiling Pt: B.P. Text: 132F 56C

Vapor Pres: 186

Spec Gravity: .70

Evaporation Rate & Reference: 5.0

Solubility in Water: INSOLUBLE

Appearance and Odor: AMBER COLORED LIQUID

==

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: HEAT, SPARKS AND OPEN FLAMES

===== Disposal Considerations =====

Waste Disposal Methods: FOLLOW FEDERAL AND LOCAL APPROVED ENVIRONMENT REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of

America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.