

DUPONT KAPTON/TEFLON CUSTOMER SERVICE -- KAPOO1 -- 9330-01-387-0413

=====  
Product Identification  
=====

Product ID:KAPOO1

MSDS Date:10/08/1996

FSC:9330

NIIN:01-387-0413

Status Code:A

MSDS Number: CJDQB

=== Responsible Party ===

Company Name:DUPONT KAPTON/TEFLON CUSTOMER SERVICE

Box:89

City:CIRCLEVILLE

State:OH

ZIP:43113

Country:US

Emergency Phone Num:800-237-4357

CAGE:DUPP0

=== Contractor Identific

ation ===

Company Name:DUPONT KAPTON/TEFLON CUSTOMER SERVICE

Box:89

City:CIRCLEVILLE

State:OH

ZIP:43113

Country:US

Phone:800-237-4357/800-441-3637

CAGE:DUPP0

=====  
Composition/Information on Ingredients  
=====

Ingred Name:INERT POLYIMIDE FILM

&lt; Wt:100.

Ingred Name:.ALPHA.-ALUMINA

CAS:1344-28-1

RTECS #:BD1200000

Minimum % Wt:0.

Maxumum % Wt:35.

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

Minimum % Wt:0.

Maxumum % Wt:20.

OSH

A PEL:3.5 MG/M3  
ACGIH TLV:3.5 MG/M3

Ingred Name:DIMETHYL ACETAMIDE  
CAS:127-19-5  
RTECS #:AB7700000  
&lt; Wt:1.  
OSHA PEL:35 MG/M3;10 PPM  
ACGIH TLV:36 MG/M3;10 PPM

Ingred Name:POLYIMIDE POLYMER  
CAS:25038-81-7

=====  
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:UNKNOWN IARC:YES  
Health Hazards Acute and Chronic:INHALATION: EXPOSURE TO ALUMINA/CARBON  
BLACK ENCAPSULATED IN THE POLYMER IS NOT LIKELY. SKIN: DUPONT  
RECOMMENDS TREATING POLYMER D  
UST AS A NUISANCE PARTICULATE.  
SKIN/EYES: NOT A PROBABLE ROUTE OF EXPO SURE FOR FILM.  
Explanation of Carcinogenicity:THE FOLLOWING COMPONENTS ARE LISTED BY  
IARC, NTP, OSHA/ACGIH AS CARCINOGENS: CARBON BLACK.

=====  
===== First Aid Measures =====

First Aid:SKIN: WASH W/SOAP & WATER AFTER HANDLING. EYES: FLUSH  
W/WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====  
===== Fire Fighting Measures =====

Extinguishing Media:WATER  
, FOAM, DRY CHEMICAL, CO2  
Fire Fighting Procedures:NONE REQUIRED.  
Unusual Fire/Explosion Hazard:THE FLAMMABILITY CHARACTERISTIC OF  
POLYIMIDE FILM IS REPORTED AS SELF EXTINGUISHING.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:REVIEW FIRE FIGHTING MEASURES & HANDLING  
SECTIONS BEFORE PROCEEDING W/CLEAN-UP. USE APPROPRIATE PERSONAL  
PROTECTIVE EQUIPMENT DURING CLEAN-UP. PICK UP TO PREVENT SLIPPING  
HAZARD.

=====  
===== Handl

ing and Storage =====

Handling and Storage Precautions:STORE AWAY FROM FLAMMABLE MATERIALS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED FOR NORMAL USE.

Ventilation:FOR SMALL QUANTITIES: USE NORMAL AIR CIRCULATION IN CASE OF OVERHEATING. VENTILATION AT HIGHER TEMPS WILL DEPEND ON FILM QUANTITY/TEMPERATURE & EXPOSURE TIME.

Protective Gloves:RECOMMENDED

Eye Protection:SAFETY GLASSES RECOMMENDED

Other Protective E

quipment:NOT NEEDED FOR NORMAL USE.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

KAPTON WILL BURN IN AN ATMOSPHERE OF 100% OXYGEN. THE PROCESSING OF POLYIMIDE FILMS CAN CAUSE THE GENERATION OF STATIC CHARGE. PRECAUTIONS FOR STATIC CHARGES SHOULD BE TAKEN WHEN REMOVING PLASTIC FILM S USED AS PROTECTIVE PACKAGING FOR KAPTON.

===== Physical/Chemical Properties =====

Melt/Freeze Pt:M.P/F.P Text:NONE

Spec Gravity:>1.4

Solubility in Water:INSOLUBLE

Appearance and Odor:LIGHT AMBER TRANSPARENT FILM W/NO ODOR

Percent Volatiles by Volume:1%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:STATIC CHARGES, TEMPERATURES ABOVE 752F.

Hazardous Decomposition Products:CO, CO2

===== Ecological Information =====

Ecological:AQUATIC TOXICITY. INSOLUBLE.

===== Disposal Conside

rations =====

Waste Disposal Methods:LANDFILL/INCINERATE/DISPOSE OF IN ACCORDANCE  
W/LOCAL, STATE & FEDERAL REGULATIONS.

===== Regulatory Information =====

State Regulatory Information:SUBSTANCES ON THE PENNSYLVANIA HAZARDOUS  
SUBSTANCES LIST PRESENT AT A CONCENTRATION OF 1%/MORE (0.01 FOR  
SPECIAL HAZARDOUS SUBSTANCES) DIMETHYL ACETAMIDE (1% MAXMUM); SOME  
TYPES CONTAIN CARBON BLACK ( 2-30%); SOME TYPES CONTAIN ALUMIN (35%  
MAX  
IMUM). SUBSTANCES ON THE NEW JERSEY WORKPLACE HAZARDOUS  
SUBSTANCE LIST PRESENT AT A CONCENTRATION OF 1%/MORE (0.1% FOR  
SUBSTANCES IDENTIFIED AS CARCINOGENS, M UTAGENS/TERATOGENS)  
DIMETHYL ACETAMIDE (1% MAXIMUM); SOME TYPES CONTAIN CARBON BLACK  
(2-30%) SOME TY PES CONTAIN ALUMINA (35% MAXIMUM).

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elem  
ents of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.