

NORDSTROM VALVES INC -- SEALANT (STICK GRADE),950

=====
MSDS Safety Information
=====

FSC: 9150
NIIN: 00-261-8292
MSDS Date: 08/14/1998
MSDS Num: CJFHP
Product ID: SEALANT (STICK GRADE),950
MFN: 01
Responsible Party
Cage: 06JW1
Name: NORDSTROM VALVES INC
Address: 1511 JEFFERSON ST E.
City: SULPHUR SPRIN
GS TX, NK 75482
Info Phone Number: 903 439 3312
Emergency Phone Number: 903 885 3159

=====
Item Description Information
=====

Item Manager: S9G
Item Name: GREASE,PLUG VALVE
Specification Number: MIL-G-6032
Type/Grade/Class: TYPE II, CLASS C
Unit of Issue: BX
Quantitative Expression: 00000000024EA
UI Container Qty: G
Type of Container: UNKNOWN

=
Ingredients
=====

Name: *** PROPRIETARY ***

=====

Health Hazards Data
=====

LD50 LC50 Mixture: TLV: 5 MG/M3 (OIL MIST)
Route Of Entry Inds - Inhalation: NO
Skin: NO
Ingestion: NO
Carcinogenicity Inds - NTP: YES
IARC: YES
OSHA: NO
Effects of Exposure: TARGET ORGANS: EYES, SKIN, AND GASTROINTESTINAL TRACT.
ACUTE -

EYE CONTACT MAY CAUSE IRRITATION. PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE IRRITATION. NO INHALATION IS EXPECTED. INGESTION MAY BE MILDLY IRRITATING TO THE GASTROINTESTINAL TRACT. CHRONIC - UNKNOWN.

Explanation Of Carcinogenicity: ORGANOPHILIC CLAY CONTAINS 0 - 4 % CRYSTALLINE SILICA.

Signs And Symptoms Of Overexposure: IRRITATION, NAUSEA, VOMITING, DISCOMFORT
Medical Cond Aggravated By Exposure: INDIVIDUALS WITH PRE-EXISTING SKIN DISORDERS MAY BE MORE SUCCEPTIBLE TO THE EFFECTS FROM PROLONGED EXPOSURE TO THIS PRODUCT.

First Aid: GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED: VAPOR PRESSURE IS VERY LOW. VAPOR INHALATION IS NOT CONSIDERED A PROBLEM UNDER NORMAL CONDITIONS OF USE. EYES: FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. CONTACT PHYSICIAN. SKIN: WIPE OFF EXCESS. WASH SKIN WITH SOAP AND WATER. ORAL: IF MORE THAN SEVERAL MOUTHFULS OF THIS PRODUCT ARE SWALLOWED, RINSE MOUTH AND DRINK TWO GLASSES OF WATER. SEEK MEDICAL ATTENTION.

=====
=====

Handling and Disposal

=====
Spill Release Procedures: RECOVER FREE OIL. REMOVE SPILL WITH INERT ABORBENT SUCH AS SAND, CLAY, EARTH. TRANSFER TO PROPER CONTAINERS FOR DISPOSAL. PREVENT RUN-OFF TO ENTER SEWERS OR WATERWAYS. REPORT SPILLS AS REQUIRED TO AUTHORITIES. ASSURE CONFORMITY WITH APPLICABLE GOVERNMENTAL REGULATIONS.

Waste Disposal Methods: PRODUCT IS SUITABLE FOR BURNING IN AN ENCLOSED, CONTROLLED BURNER FOR FUEL VALUE OR DISPOSED BY SUPERVISED INCINERATION. IN ADDITION, THE PRODUCT MAY BE SUITABLE FOR RECYCLING. OBSERVE ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Handling And Storage Precautions: STORE IN SEALED CONTAINERS TO AVOID CONTAMINATION WITH FOREIGN PARTICLES. STORE AWAY FROM STRONG OXIDIZING AGENTS.

Other Precautions: AVOID INHALATION OF OIL FUMES, MIST, OR VAPOR. DO NOT GET IN EYES. AVOID PROLONGED/REPEATED SKIN CONTACT. REMOVE AND LAUNDRER OIL SOAKED CLOTHING BEFORE REUSE. PROPERLY DISPOSE OF CONTAMINATED LEATHER ARTICLES INCLUDING SHOES THAT CANNOT BE DECONTAMINATED. KEEP OUT OF REACH OF CHILDREN.

=====
Fire and Explosion Hazard Information

=====
Flash Point Method: COC
Flash Point: >160.C, 320.F
Extinguishing Media: DRY CHEMICAL POWDER,CARBON DIOXIDE, CHEMICAL FOAM
Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING

FIRE IN CONFINED AREAS, TREAT AS BURNING OIL

Unusual Fire/Explosion Hazard: NONE KNOWS

=====
Control Measures
=====

Respiratory Protection: NOT NEEDED UNDER NORMAL USAGE CONDITIONS.

Ventilation: USE ADEQUATE VENTILATION TO KEEP OIL MISTS OF THIS MATERIAL BELOW APPLICABLE STANDARD(S).

Protective Gloves: RUBBER AS NEEDED

Eye Protection: SAFETY GLASSES IS ADVISED.

Other Protective Equipment: EY

E BATH, WASHING FACILITY, LAB COAT OR UNIFORM ARE RECOMMENDED.

Work Hygienic Practices: GOOD PRACTICE REQUIRES THAT GROSS AMOUNT OF ANY CHEMICAL BE REMOVED FROM THE SKIN AS SOON AS PRACTICAL.

Supplemental Safety and Health: NONE

=====
Physical/Chemical Properties
=====

HCC: V6

Vapor Pres: NIL

Spec Gravity: 1.17@75F

Evaporation Rate & Reference: (ETHER=1) NIL

Solubility in Water: NEGLLGIBE

Appearance and Odor: TAN GREASE LIKE MATERIAL IN STICK FOAM, SLIGHT FATTY ODOR

Percent Volatiles by Volume: NIL

=====
Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: FIRE, EXTREME HEAT

Materials To Avoid: STRONG OXIDIZING AGENTS

Hazardous Decomposition Products: MAY FORM CARBON MONOXIDE, CARBON DIOXIDE, AND ASPHYXIANTS.

Hazardous Polymerization Indicator: NO

Condit

ions To Avoid Polymerization: NONE

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====

Regulatory Information

=====

Federal Regulatory Information: THIS PRODUCT HAS BEEN EVALUATED AND DOES NOT REQUIRE ANY WARNING LABEL UNDER THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200(D)).

=====

Other Information

=====

=====

Transportation Information

=====

=====

Responsible Party Cage: 06JW1

Trans ID NO: 141916

Product ID: SEALANT (STICK GRADE),950

MSDS Prepared Date: 08/14/1998

Review Date: 04/29/1999

MFN: 1

Multiple KIT Number: 0

Unit Of Issue: BX

Container QTY: G

Type Of Container: UNKNOWN

Additional Data: NOT REGULATED FOR TRANSPORTATION, PER MSDS.

=====

Detail DOT Information

=====

DOT PSN Code: ZZZ

DOT Proper Shippin

g Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====

Detail IMO Information

=====

IMO PSN Code: ZZZ

IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

=====

Detail IATA Information

=====

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPOR

TATION

=====
Detail AFI Information
=====

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====
HAZCOM Label
=====

Product ID: SEALANT (STICK GRADE),950

Cage: 06JW1

Company Name: NORDSTROM VALVES INC DBA NORDSTROM AUDCO, INC.

Street: 1511 JEFFERSON ST.

City

: SULPHUR SPRINGS TX

Zipcode: 75482

Health Emergency Phone: 903 885 3159

Date Of Label Review: 04/29/1999

Status Code: A

Year Procured: 1999

Origination Code: F

Eye Protection IND: NO

Skin Protection IND: NO

Signal Word: CAUTION

Respiratory Protection IND: NO

Health Hazard: Slight

Contact Hazard: Slight

Fire Hazard: None

Reactivity Hazard: None

Hazard And Precautions: TARGET ORGANS: EYES, SKIN, AND GASTROINTESTINAL TRACT.

ACUTE - EYE CONTACT MAY CAUSE IRRITATION. PROLONGED OR REPEATED SKIN CONTACT

MAY CAUSE IRRITATION. NO INHALATION IS EXPECTED. INGESTION MAY BE MILDLY IRRITATING TO THE GASTROINTESTINALTRACT. CHRONIC - UNKNOWN.

=====
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation rega

rdless of similarity to a corresponding Department
of Defense or other government situation.