

FARWEST PAINT MFG CO -- RED STENCIL PAINT 31136 -- 8010-00-285-4931
===== Product Identification =====

Product ID:RED STENCIL PAINT 31136
MSDS Date:03/01/1998
FSC:8010
NIIN:00-285-4931
Status Code:A
MSDS Number: CJGBW
=== Responsible Party ===
Company Name:FARWEST PAINT MFG CO
Address:4522 S 133 ST
Box:68726
City:TUKWILA
State:WA
ZIP:98168-3251
Country:US
Info Phone Num:206-244-8844
Emergency Phon
e Num:206-941-1619
CAGE:6F266
=== Contractor Identification ===
Company Name:FARWEST PAINT MANUFACTURING CO
Address:4522 SOUTH 133RD ST
Box:City:TUKWILA
State:WA
ZIP:98168
Country:US
Phone:206-244-8844
CAGE:6F266

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC HYDROCARBON
CAS:64742-89-8
Fraction by Wt: 13.46%
OSHA PEL:500 PPM
ACGIH TLV:300 PPM

Ingred Name:AROMATIC HYDROCARBONS
CAS:64742-95-6
Fraction by Wt: 17.64%
OSHA PEL:300 PPM
ACGIH TLV:300 PPM

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN: PROLONGED/REPEATED CONTACT MAY CAUSE IRRITATION, SENSITIZATION, OR DEFATTING OF SKIN. INHAL: EXCESSIVE EXPOSURE TO VAPORS/SPRAY MISTS CAN PRODUCE HEADACHE, DIZZINESS, NAUSEA, & LOSS OF CONSCIOUS NESS. SOME REPORTS HAVE ASSOCIATED REPEATED/PROLONGED OCCUPATIONAL OVE
REXPOSURE TO SOLVENTS
W/ PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. EYES: IRRITANT.
Medical Cond Aggravated by Exposure:NONE WHEN USED IN ACCORDANCE WITH HANDLING INSTRUCTIONS.

=====
First Aid Measures
=====

First Aid:SKIN: PROMPTLY WASH W/ SOAP & WATER. REMOVE AND WASH ANY CONTAMINATED CLOTHING BEFORE REUSE. EYES: WASH W/ LARGE AMOUNTS OF WATER FOR 15 MINUTES AND SEEK MED ATTN. INGEST: DO NOT INDUCE VOMITING. KEEP WARM & QUIET, AND GET
MED ATTN. ASPIRATION OF
MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. SEEK MED ATTN. INHALATION: REMOVE TO FRESH AIR. IF RESPIRATORY SYMPTOMS DEVELOP, SEEK MED ATTN AT ONCE.

=====
Fire Fighting Measures
=====

Flash Point:=10.C, 50.F
Lower Limits:1.0
Upper Limits:7.0
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG. ANY CLASS B EXTINGUISHING AGENT. WATER MAY BE UNSUITABLE AS EXTINGUISHING MEDIUM, BUT HELPFUL
IN KEEPING ADJACENT CONTAINERS COOL.
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA OF UNPROTECTED PERSONEL. WEAR PROTECTIVE CLOTHING.
Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURE IN AIR & MAY BE IGNITED BY SPARKS, PILOT LIGHTS, ETC. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE SOURCES OF IGNITION AND VENTILATE AREA.

ADSORB ON INERT MATERIAL SUCH AS SAWDUST, VERMICULITE, OR SAND, AND PLACE MATERIAL IN CLOSED CONTAINER. LARGE SPILL: DIKE AREA TO PREVENT FROM ENTERING SEWER OR WATERWAY. WEAR PROTECTIVE EQUIPMENT DURING CLEAN UP.

Neutralizing Agent:NONE

==== Handling and Storage =====

Handling and Storage Precautions:AVOID PROLONGED/REPEATED INHALATION OF HEATED VAPORS/SPRAY MISTS. KEEP AWAY FROM HEAT/OPEN FLAME. MATERIAL MAY CAUSE SENSITIZATION. D

O NOT GET IN EYES, ON SKIN OR CLOTHING.

DO NOT ALLOW CONTAM CLOTHIN G TO CONTACT SKIN. DO NOT WELD ON FULL/EMPTY CONTAINERS.

Other Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE & PROPERLY LABELED.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:CANNISTER TYPE RESPIRATOR MUST BE WORN TO PREVENT INHALATION OF VAPORS/SPRAY MISTS WHEN TLV/PEL EXCEEDED.

Ventilation:GENERAL VENTILATION DURING NORMAL USE. LOCAL VENTILATION MAY BE REQ

UIRED DURING CERTAIN OPERATIONS TO KEEP EXPOSURE LEVEL

1

VOC Pounds/Gallon:411

Viscosity:75 - 90KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:RED MEDIUM VISCOUS LIQUID W / MILD, SWEET AROMATIC ODOR

Percent Volatiles by Volume: