View NSN Online: https://aerobasegroup.de/nsn/6850-01-185-1187

Product ID: CLOSED CIRCUIT TREATMENT 8696-A MSDS Date:04/10/1995 FSC:6850 NIIN:01-185-1187 Status Code:A MSDS Number: CJGVH === Responsible Party === Company Name: WESTERN WATER MANAGEMENT/WESTERN CHEMICAL CO Address:1345 TANEY City:NORTH KANSAS CITY State:MO ZIP:641 16-4414 Country:US Info Phone Num:816-842-0560 Emergency Phone Num:816-842-0560 Preparer's Name: FRED HOPKINS Chemtrec Ind/Phone:(800)424-9300 CAGE:08824 === Contractor Identification === Company Name: WESTERN WATER MANAGEMENT/WESTERN CHEMICAL CO Address:1345 TANEY Box:City:NORTH KANSAS CITY State:MO ZIP:64116-4414 Country:US Phone:816-842-0560 Contract Num:DLA400-90-M-A422 CAGE:08824

Ingred Name:SODIUM NITRITE CAS:7632-00-0 RT ECS #:RA1225000 Minumum % Wt:65. Code:F Maxumum % Wt:70. Code:F Other REC Limits:NONE RECOMMENDED EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name:SODIUM TETRABORATE PENTAHYDRATE CAS:1303-96-4 RTECS #:VZ2275000 Minumum % Wt:8. Code:F Maxumum % Wt:12. Code:F Other REC Limits:NONE RECOMMENDED OSHA PEL:10 MG/M3 TWA ACGIH TLV:1 MG/M3 8 HR TWA

Ingred Name:BENZISOTRIAZOLE CAS:95-14-7 RTECS #:DM1225000 Minumum % Wt:4. Code:F Maxumum % Wt:5. Code:F Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:LD50 (ORAL, RAT) = 121 MG/KG (TECH SUPP) Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:TARGET ORGANS: EYES, SKIN, RESPIRATORY AND GI TRACTS (HMIS). ACUTE - INHALATION: DUST OR MIST MAY IRRITATE RESPIRATORY TRACT. EYES: MAY CAUSE IRRITATION. SKIN: MAY CAUSE IRRITATION WITH DISCOMFORT OR RASH. SODIUM NITRITE CAN BE ABS ORBED INTO BODY THROUGH SKIN AND LEAD TO NONSPECIFIC DISCOMFORT, SUCH AS NAUSEA. HEADACHE. OR WEAKNESS: REDUCTION OF BI OOD'S OXYGEN CARRYI

NAUSEA, HEADACHE, OR WEAKNESS; REDUCTION OF BLOOD'S OXYGEN CARRYING CAPACITY WITH CYANOSIS, WEAK NESS, OR SHORTNESS OF BREATH BY FORMATION OF METHEMOGLOBINE; ANEMIA OR LOW BLOOD PRESSURE WITH DIZZINESS. SODIUM TETRABORATE MAY AFFECT CNS. INGESTION: MAY CAUSE IRRITATION. LARGE DOSES ARE TOXIC AND MAY CAUSE DEATH. CHRONIC -UNKNOWN.

Explanation of Carcinogenicity:NONE Effects of Overexposure:IRRIT ATION, HEADACHE, DIZZINESS, NAUSEA,

VOMITING, DROWSINESS, TEARNING, BLURRED VISION, UNCONSCIOUSNESS, WEAKNESS, FATIGUE, DIARRHEA, BLUISH DISCOLORATION OF SKIN, RASH, SHORTNESS OF BREATH, ANEMIA, LOW BLOOD PRESSURE, COLLAPSE, COMA, DEATH

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PREEXISTING DISEASES OF THE CARDIOVASCULAR SYSTM AND BONE MARROW MAY HAVE SUSCEPTIBILITY TO THE TOXICITY OF EXCESSIVE EXPOSURES.

First Aid:EYES: IMMEDIATELY FLUSH WITH LARGE AMOUNT OF WATER FOR AT LEAST 15 MINUTES. HOLD LIDS OPEN TO ENSURE FLUSHING ENTIRE EYE SURFACE. GET EMERGENCY MEDICAL ATTENTION. SKN: REMOVE CONTAMINATED CLOTHING. WA SH CONTAMINATED SKIN WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, GIVE OXYGEN. IF BREATHING HAS STOPPED, GIVE ARTIFICIAL RESPIRATION. GET EMERGENCY MEDICAL ATTENTIO N. INGESTION: HAVE CONSCIOUS PATIENT DRINK SEVERA

L

GLASSES OF WATER, THEN INDUCE VOMITING BY HAVING PATIENT TICKLE BACK OF THROAT WITH FINGER. GET IMMEDIATE MEDICAL ATTENTION. NEVER GIVE FLUID OR IND UCE VOMITING IF PATIENT IS UNCONSCIOUS.

Flash Point:NONE

Lower Limits:NONFLAMMABLE

Upper Limits:NONFLAMMABLE

Extinguishing Media: FLOODING AMOUNTS OF WATER IN EARLY STAGES. HEAVY WATER JET IS ADVANTAGEOUS.

Fire Fighting Procedures:ATTEMPT TO KEEP OUT OF SEWER. F IREFIGHTERS

SHOULD ALWAYS WEAR PROTECTIVE CLOTHING AND POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES NEAR CHEMICALS.

Unusual Fire/Explosion Hazard:SODIUM NITRITE IS AN OXIDIZING AGENT-IT CAN SUPPLY OXYGEN TO STIMULATE OR ACCELERATE THE COMBUSTION OF ORGANIC OR OTHER COMBUSTIBLE MATERIALS. THERMAL DECOMPOSITION (AS MAY BE EXPERIENCED IN A FIRE) M AY PRODUCE TOXIC AND HAZARDOUS NITROGEN OXIDES, AND LEAVE A CAUSTIC RESIDUE.

Spill Release Procedures:KEEP UNAUTHORIZED PERSONS OUT OF AREA. IF FLAMMABLE MATERIALS ARE PRESENT, MONITOR OPERATION WITH A CARBON DIOXIDE FIRE EXTINGUISHER. CLEAN UP SPILLS IMMEDIATELY BY SWEEPING OR SHOVELING UP MATERIAL A ND PLACING INTO CLEAN FIBER/STEEL DRUM, CLOSE, AND LABEL "OXIDIZER". FLUSH SPILL AREA TO SEWER. ANY RELEASE OF PRODUCT TO ENVIRONMENT MAY BE SUBJECT TO FEDERAL, STATE, OR LOCAL REPORTING REQUIREMENTS Neutralizing Agent:REDUCING AGENT

Handling and Storage Precautions:STORE IN A COOL AREA AWAY FROM INCOMPATIBLE MATERIALS. KEEP DRUM TIGHTLY CLOSED WHEN NOT IN USE. PROTECT CONTAINER FROM PHYSICAL DAMAGE. DO NOT MIX WITH ANY OTHER CONCENTRATED CHEMICALS.

Other Precautions:DO NOT GET IN EYE, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. A

WATER SOURCE AND SHOWER SHOULD BE INSTALLED IN STORAGE AND WO RK AREAS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NIOSH APPROVED PARTICULATE RESPIRATOR IF DUSTY CONDITIONS EXIST IN EXCESS OF TLV.

Ventilation:LOCAL MECHANICAL EXHAUST VENTILATION IS PREFERRED TO CONTROL DUSTY CONDITIONS.

Protective Gloves:SYNTHETIC RUBBER

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: EMERGENCY EYE WASH STATION, SAFETY SHOWER, L

ONG-SLEEVED SHIRT, AND LONG PANTS WORKER SHOULD WEAR ADEQUATE PERSONAL PROTECTIVE EQUIPMENT AND CLOTHING.

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH BEFORE EATING, DRINKING OR SMOKING. Supplemental Safety and Health

HCC:D2 Spec Gravity:1.282 (80LBS/CU FT) pH:~9 (1% SOLN) Solubility in Water:~1 LB/GAL H20 Appearance and Odor:OFF WHITE POWDER WITH NO APPRECIABLE O DOR.

Stability Indicator/Materials to Avoid:NO

COMBUSTIBLE MATERIALS, ACIDS, AMMONIUM COMPOUNDS (POSSIBLY INCLUDING SOME DRY CHEMICAL FIRE EXTINGUISHING MATERIALS), AMINES, ACTIVATED CARBON, REDUCING AGENTS-PARTICULARLY CYANIDES, THIOCYANATES, THIOSULFATES, ORGANICS, AN

Stability Condition to Avoid:NONE KNOWN (UNSTABLE WITH HEAT, TEMPERATURES OVER 550 F)

Hazardous Decomposition Products: THERMAL DECOMPOSITION (A S MAY BE

EXPERIENCED IN A FIRE) MAY PRODUCE TOXIC AND HAZARDOUS NITROGEN OXIDES. NITRITE COMPOUNDS MAY REACT WITH SECONDARY AMINES TO FORM SUSPECTED CANCER-CAUSING NITROSAMINES.

Waste Disposal Methods:DISPOSE OF WASTE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAWS AND REGULATIONS REGARDING HEALTH AND POLLUTION.

SARA Title III Informat

ion:NONE

Federal Regulatory Information:ALL OF THE INGREDIENTS PRESENT IN THIS PRODUCT ARE LISTED IN THE TOXIC SUBSTANCE CONTROL ACT (TSCA) INVENTORY. OSHA HAZARD CLASSIFICATION: IRRITANT; TOXIC; OXIDIZER. REPORTABLE QUANTITY: 140 LBS.

State Regulatory Information:

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly

or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.