

ALOX CORP -- ALOX 2028D (USED FOR MIL-C-81309 TYPEIII,CLASSI) -- 8030-01-347-0978

=====  
Product Identification  
=====

Product ID:ALOX 2028D (USED FOR MIL-C-81309 TYPEIII,CLASSI)

MSDS Date:01/25/1993

FSC:8030

NIIN:01-347-0978

Status Code:A

MSDS Number: CJHJW

==== Responsible Party ====

Company Name:ALOX CORP

Address:3943 BUFFALO AVE

Box:517

City:NIAGARA FALLS

State:NY

ZIP:14302-5000

Country:US

Info P

hone Num:716-282-1295

Emergency Phone Num:716-282-1295

CAGE:60773

==== Contractor Identification ====

Company Name:ALOX CORP

Address:3943 BUFFALO AVE

Box:517

City:NIAGARA FALLS

State:NY

ZIP:14302

Country:US

Phone:716-282-1295

CAGE:60773

Company Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ALIPHATIC MINERAL SPIRITS

CAS:64742-88-7

Fracti

on by Wt: 80%  
Other REC Limits:6 MG/M3  
ACGIH TLV:100 PPM

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50(RATS): 6 G/KG  
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES: MAY CAUSE IRRITATION.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:IRRITATION, HEADACHE, DIZZINESS, NAUSEA,  
DRYING.

===== First Aid Measures =====

First Aid:EYES: FLUSH W/WATER FOR 15 MINS. CONSULT PHYSICIAN. SKIN:  
WASH W/SOAP & WATER. TREAT BURNS FROM HOT MATERIAL AS THERMAL  
BURNS. INGESTION: DON'T INDUCE VOMITING. CONSULT PHYSICIAN.  
INHALATION: REMOVE TO FRESH AIR. TREAT SYMPTOMS. GIVE OXYGEN IF  
NEEDED. OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:140 TO 142 F MIN  
Lower Limits:NOT AVAILABL  
Upper Limits  
:NOT AVAILABL  
Extinguishing Media:CO2, DRY CHEMICAL, WATER FOG  
Fire Fighting Procedures:HANDLE AS PETROLEUM PRODUCT, I.E. DO NOT USE  
WATER EXCEPT AS FOG OR TO COOL CONTAINERS OR TO FLUSH AWAY SPILLS.  
Unusual Fire/Explosion Hazard:SAME AS PETROLEUM PRODUCTS (I.E. WATER  
STREAMS ON BURNING MATERIAL MAY SPREAD FIRE).

===== Accidental Release Measures =====

Spill Release Procedures:ATTEMPT TO RECOVER. KEEP PETROLEUM PRODUCTS  
OUT OF STREAMS AND WATERWAYS.

===

=====  
Handling and Storage  
=====

Handling and Storage Precautions:AVOID PROLONGED OR REPEATED CONTACT.  
KEEP CONTAINERS CLOSED WHEN NOT IN USE.  
Other Precautions:IF INGESTION AND VOMITING OCCURS, MONITOR PATIENT FOR  
48 HOURS FOR BREATHING DIFFICULTIES.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:IF VAPORS/MIST ARE GENERATED, USE APPROPRIATE  
MASK FOR VAPORS OR MISTS.  
Ventilation:LOCAL EXHAUST IS PREFERRED  
IF VAPORS OR MISTS ARE  
GENERATED.  
Protective Gloves:OIL IMPERVIOUS IF CONTACT ANTICIPATED.  
Eye Protection:SAFETY GLASSES MINIMUM  
Other Protective Equipment:AS NEEDED TO PROTECT AGAINST HOT PRODUCT OR  
PROTECT FROM REPEATED OR PROLONGED CONTACT.  
Work Hygienic Practices:AVOID REPEATED OR PROLONGED CONTACT. WASH  
BEFORE EATING, SMOKING, OR USING TOILET. LAUNDER SATURATED CLOTHING  
BEFORE REUSE.  
Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

Boiling Pt:=180.C, 356.F  
Vapor Pres:1 AIR=1  
Spec Gravity:0.8 @ 60 F  
Evaporation Rate & Reference: