

PRODUCTS/TECHNIQUES INC -- TT-P-645A ALKYLOID PRIMER AIR DRY #84 YELLOW --
8010-01-285-1329

===== Product Identification =====

Product ID:TT-P-645A ALKYLOID PRIMER AIR DRY #84 YELLOW

MSDS Date:08/19/1996

FSC:8010

NIIN:01-285-1329

Status Code:A

MSDS Number: CJHKD

=== Responsible Party ===

Company Name:PRODUCTS/TECHNIQUES INC

Address:3271 S RIVERSIDE AVE

City:RIALTO

State:CA

ZIP:92376

Country:US

In

fo Phone Num:909-877-3951

Emergency Phone Num:(800) 424-9300

Preparer's Name:BARRY BODEN

Chemtrec Ind/Phone:(800)424-9300

CAGE:06341

=== Contractor Identification ===

Company Name:PRODUCTS/TECHNIQUES INC

Address:3271 S RIVERSIDE AVE

Box:City:RIALTO

State:CA

ZIP:92376

Country:US

Phone:909-877-3951

CAGE:06341

===== Composition/Information on Ingredients =====

Ingred Name:VM&P NAPHTHA VAPOR PRESSURE=5.4 @ 20 C

CAS:8032-32-4

RTECS #:OI6180000

Fraction by Wt: 6.16%

Other REC Limi

ts:NONE RECOMMENDED
OSHA PEL:300 TWA PPM
OSHA STEL:400 PPM
ACGIH TLV:300 TWA

Ingred Name:ISOBUTANOL (SARA III) VAPOR PRESSURE=8.8 @ 20 C
CAS:78-83-1
RTECS #:NP9625000
Fraction by Wt: 4.20%
OSHA PEL:50 TWA
ACGIH TLV:50 TWA
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ADDITIVE-GRINDING AGENT
Fraction by Wt: 0.32%

Ingred Name:ALKYLOID RESIN
Fraction by Wt: 16.81%
Other REC Limits:NONE RECOMMENDED

Ingred Name:XYLENE VAPOR PRESSURE=6.6 @ 20 C
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by
Wt: 0.84%
OSHA PEL:100 TWA
OSHA STEL:150 TWA
ACGIH TLV:100 TWA
ACGIH STEL:150 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:MIXTURE: NONHAZARDOUS ADDITIVE VAPOR PRESSURE=18
Fraction by Wt: 032%

Ingred Name:ZINC CHROMATE (24% AS CHROMIUM)
CAS:13530-65-9
RTECS #:GB3290000
Fraction by Wt: 20.30%
ACGIH TLV:0.01 MG/M3

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 6.09%
ACGIH TLV:10 MG/M3 TOTDUST

Ingred Name:BARIUM SULFATE
CAS:7727-43-7
RTECS #:CR06000

00

Fraction by Wt: 8.12%
ACGIH TLV:10 MG/M3

Ingred Name:ZINC OXIDE
CAS:1314-13-2
RTECS #:ZH4810000
Fraction by Wt: 6.49%
ACGIH TLV:10 MG/M3

Ingred Name:YELLOW IRON OXIDE
CAS:51274-00-1
Fraction by Wt: 0.81%
ACGIH TLV:5 MG/M3

Ingred Name:NAPHTHA, SOLVENT
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 20.87%
OSHA PEL:2900 MG/M3;500 PPM
ACGIH TLV:525 MG/M3;100 PPM

Ingred Name:MAGNESIUM SILICATE HYDRATE
CAS:1343-90-4
RTECS #:OM4360000
Fraction by Wt: 7.30%
ACGIH TLV:2 MG/M3

Ingred Name:ADDITIV
E-DRIER VAPOR PRESSURE=