

STIC-ADHESIVE PRODUCTS CO INC -- ENAMEL, NONFLAMING(DRY)CHLORINATED ALKYLOID RESIN, SEMIGLOSS -- 8010-01-344-5092

=====  
===== Product Identification =====

Product ID:ENAMEL, NONFLAMING(DRY)CHLORINATED ALKYLOID RESIN, SEMIGLOSS

MSDS Date:02/01/1998

FSC:8010

NIIN:01-344-5092

Status Code:A

MSDS Number: CJJCV

=== Responsible Party ===

Company Name:STIC-ADHESIVE PRODUCTS CO INC

Address:3950 MEDFORD ST

City:L

OS ANGELES

State:CA

ZIP:90063-1675

Country:US

Info Phone Num:213-268-2956

Emergency Phone Num:(800)424-9300

Chemtrec Ind/Phone:(800)424-9300

CAGE:1BH90

=== Contractor Identification ===

Company Name:STIC-ADHESIVE PRODUCTS CO INC

Address:3950 MEDFORD ST

Box:City:LOS ANGELES

State:CA

ZIP:90063-1675

Country:US

CAGE:1BH90

=====  
===== Composition/Information on Ingredients =====

Ingred Name:BARIUM METABORATE MONOHYDRATE

Fraction by Wt: 15.0%

Other REC Limits:5 MG/CU.M

OSHA PEL:TOTAL DUS

T

ACGIH TLV:TOTAL DUST

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 21.0%

Other REC Limits:10 MG/M3

OSHA PEL:TOTAL DUST

ACGIH TLV:TOTAL DUST

Ingred Name:ZINC PHOSPHATE

RTECS #:TD0590000

Fraction by Wt: 16.0%

Other REC Limits:NONE RECOMMENDED

Ingred Name:2-ETHYLHEXANOIC ACID COBALT(2+) SALT

CAS:136-52-7

Fraction by Wt: 3.0%

Other REC Limits:NONE RECOMMENDED

RY

#41-0177680-5000381P(NJAPA)

Ingred Name:NAPHTHA, SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 9.0%

OSHA PEL:2900 MG/M3;500 PPM

ACGIH TLV:525 MG/M3;100 PPM

Ingred Name:LEVELING AGENT

Ingred Name:ANTI-SKINNING AGENT

Fraction by Wt: 1.0%

Ingred Name:THIXATROPIC AGENT

===== Hazards Identification =====

Health Hazards Acute and Chronic:EYES: SEVERE IRRITATION. SKIN: PRIMARY SKIN IRRITATION. HARMFUL IF ABSORBED THRU SKIN. PROLONGED/REPEATED

CONTACT: ALLERGIC SKIN REACTION. INHAL:VAPOR/SPRAY MIST HARMFUL IF INHALED. VAPOR IRRITATES EY ES/NOSE/THROAT/LUNGS. REPEATED EXPOSURE TO HIGH VAPOR CONCENTRATIONS MAY IRRITATE RESPIRATORY SYSTEM & PERMANENT BRAIN/NERVOUS SYSTEM DAMAGE. DELIBERATE MISUSE CAN BE HARMFUL OR FATAL.

Explanation of Carcinogenicity:THIS PRODUCT CONTAINS A LOW LEVEL OF FORMALDEHYDE. NTP, IARC, & OSHA ASSOCIATE FORMALDEHYDE W/ AN INCREASED RISK OF CANCER.

Effects of Overexposure:EYE WATERING, HEADACHES, NAUSEA, DIZZINESS, & LOSS OF COORDINATION INDICATE THAT SOLVENT LEVELS ARE TOO HIGH. REDNESS, ITCHING, BURNING SENSATION, VISUAL DISTURBANCES MAY INDICATE EXCESSIVE EYE CONTACT. DRYNESS, ITCHING, CRACKING, BURNING, REDNESS, SWELLING ARE CONDITIONS ASSOCIATED W/ EXCESSIVE SKIN CONTACT.

===== First Aid Measures =====

First Aid:INGESTION: DO NOT INDUCE VOMITING. IF CONSCIOUS, GIVE 1 OR 2 GLASSES OF WATER TO DRINK. KEEP PE

PERSON WARM & QUIET. GET IMMEDIATE MEDICAL

ATTENTION. EYES: FLUSH WITH WATER FOR 30 MINUTES, LIFTING LIDS TO RINSE ENTIRE EYE. CALL DR IMMEDIATELY. SKIN: FLUSH WITH COPIOUS AMOUNTS OF WATER, THEN FOLLOW WITH SOAP & WATER. CALL DR. INHALATION: REMOVE TO FRESH AIR. APPLY CPR/OXYGEN IF NECESSARY. OTHER: IF INGESTION ANY TYPE OF OVEREXPOSURE OR SYMPTOMS OF OVEREXPOSURE OCCUR DURING/FOLLOWING PRODUCT USE, CONTACT POISON CONTROL CENTER, EMERGENCY ROOM, OR PHYSICIAN IMMEDIATELY. HAVE MSDS INFORMATION

AVAILABLE.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:=-40.6C, 105.F

Autoignition Temp:Autoignition Temp Text:NA

Extinguishing Media:USE NATIONAL FIRE PROTECTION ASSOCIATION CLASS B EXTINGUISHERS (CO2, DRY CHEMICAL, OR UNIVERSAL AQUEOUS FILM FORMING FOAM) DESIGNED TO EXTINGUISH NFPA CLASS IC FLAMMABLE LIQUID FIRES

Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. WATER SPRAY MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD UP

& POSSIBLE AUTOIGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOG NOZZLES ARE PREFERRED. FIRE FIGHTERS SHOULD WEAR SCBA.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, & OPEN FLAMES. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY ON HOT SURFACES. TOXIC GASES MAY FORM WHEN PRODUCT CONTACTS FLAME OR HOT SURFACES.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:PROVIDE MAXIMUM VENTILATION. ONLY PERSONNEL WITH PROPER RESPIRATORY & SKIN/EYE PROTECTION SHOULD BE PERMITTED IN AREA. REMOVE ALL IGNITION SOURCES. TAKE UP SPILLED MATERIAL WITH SAWDUST, VERMICULITE OR OTHER ABSORBENT MATERIAL & PLACE IN CONTAINERS FOR DISPOSAL.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120 F. STORE LARGE

QUANTITIES IN BUILDINGS DESIGNED & PROTECTED FOR STORAGE OF NFPA CLASS IC FLAMMABLE LIQUIDS.

Other Precautions:IF THIS MATERIAL IS PART OF MULTIPLE COMPONENT SYSTEM, READ MSDS(S) FOR THE OTHER COMPONENT(S) BEFORE BLENDING AS THE RESULTING MIXTURE MAY HAVE THE HAZARDS OF ALL OF ITS PARTS. GROUND CONTRS WHEN POU RING. AVOID FREE FALL OF LIQUIDS IN EXCESS OF A FEW INCHES.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:ENSURE VENTILATION CONTROLS, VAPOR EXHAUST, OR FRESH AIR ENTRY. NIOSH/MESHA-APPROVED 9TC-23C AIR PURIFYING OR AIR SUPPLIED (TC-19C) RESPIRATORS REDUCE EXPOSURES. READ RESPIRATOR MANUFACTURER'S INSTRUCTIONS & LITERATURE CAREFULLY TO DETERMINE THE TYPE OF AIRBORNE CONTAMINANTS AGAINST WHICH THE RESPIRATOR IS EFFECTIVE & HOW IT IS TO BE PROPERLY FITTED.

Ventilation:GENERAL DILUTION OR LOCAL EXHAUST IN VOLUME & PATTERN TO KEEP CONCENTRATIONS < LOWEST EXPOSURE LIMITS, LEL < STATE LIMIT,& REMOVE DECOMP PRODS WHEN WELDING

Protective Gloves:IMPERMIABLE GLOVES OF NITRILE OR NEOPRENE.

Eye Protection:CHEMICAL SPLASH GOGGLES, FACE SHIELD

Other Protective Equipment:CLEAN OR DISCARD CONTAMINATED CLOTHING & SHOES. WEAR IMPERIABLE CLOTHING SUFFICIENT TO COVER EXPOSED SKIN SURFACES (NITRILE OR NEOPRENE).

Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:310 TO 390F @ 760 MM H

Melt/Freeze Pt:M.P/F.P Text:NA

Vapor Pres:2.000 MM HG @ 68 F

Vapor Density:4.9 AIR=1

Spec Gravity:1.62 - 1.65

VOC Pounds/Gallon:340

pH:NA

VOC Grams/Liter:2.8

Corrosion Rate:NA

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ALKYLIES, STRONG MINERAL ACIDS, OR STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:MAY PRODUCE HAZ DECOMP PRODUCTS WHEN HEATED. WELDING, BRAZING, OR FLAME CUTTING MAY PRODUCE FUMES INCLUDING CO, AND/OR HYDROGEN CHLORI

DE GAS.

Conditions to Avoid Polymerization:STRONG OXIDIZING AGENTS.

===== Toxicological Information =====

Toxicological Information:AVOID LONG TERM & REPEATED CONTACT. THIS PRODUCT CONTAINS TITANIUM DIOXIDE. ANIMALS INHALING MASSIVE QUANTITIES OF TITANIUM DIOXIDE DUST DEVELOPED LUNG TUMORS. STUDIES W/ HUMANS INDICATE NO INCREASED RISK OF CANCER. POTENTIAL FOR INHALATION OF TITANIUM DIOXIDE DUSTS FROM COATINGS IS VERY LIMITED. SINCE OVEREXPOSURES ARE NOT EXPECTED, THERE IS NO SIGNIFICANT HAZARD FOR MAN. THIS PRODUCT CONTAINS LOW LEVEL OF FORMALDEHYDE. BASED ON ANIMAL STUDIES, NTP, IARC, & OSHA ASSOCIATE FORMALDEHYDE W/INCREASED RISK OF CANCER. RECENT STUDIES W/HUMANS SHOW NO CORRELATION BETWEEN FORMALDEHYDE & INCREASED CANCER RISK.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL, STATE, FEDERAL REGULATIONS. RECYCLE EMPTY CONTAINERS OR DISPOSE OF THROUGH APPROVED WASTE MANAGEMENT FACILITY.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.