

NSCG INC (NOVAGARD SILICONE COMPOUNDS & GREASES INC -- VERSILUBE G 322L, SILICONE GREASE -- 9150-01-232-7667

===== Product Identification =====

Product ID:VERSILUBE G 322L, SILICONE GREASE

MSDS Date:03/12/1998

FSC:9150

NIIN:01-232-7667

MSDS Number: CJKCC

=== Responsible Party ===

Company Name:NSCG INC (NOVAGARD SILICONE COMPOUNDS & GREASES INC

Address:5109 HAMILTON AVE

City:CLEVELAND

State:OH

ZIP

:44114

Country:US

Info Phone Num:216-881-8111

Emergency Phone Num:216-881-8111

Preparer's Name:BRIAN CHAMBERS

CAGE:0ZEE4

=== Contractor Identification ===

Company Name:FOAM SEAL INC DBA NOVAGARD

Address:5109 HAMILTON AVENUE

Box:City:CLEVELAND

State:OH

ZIP:44114-3907

Country:US

Phone:800-626-6527/216-881-8111

CAGE:00CE9

Company Name:NSCG INC

Address:5109 HAMILTON AVE

Box:City:CLEVELAND

State:OH

ZIP:44114

Country:US

Phone:216-881-8111/FAX 216-881-5318

CAGE:0ZEE4

Company Name:THE SMITH GROUP INC.

A

Address:811 E. CAYUGA STREET
Box:City:PHILADELPHIA
State:PA
ZIP:19124-3893
Country:US
Phone:215-743-8200
Contract Num:SP0450-99-M-B162
CAGE:2B613

=====
Composition/Information on Ingredients
=====

Ingred Name:ZINC CHROMATE
CAS:13530-65-9
RTECS #:GB3290000
Minimum % Wt:1.
Maximum % Wt:5.
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:0.01 MG/M3

Ingred Name:LITHIUM STEARATE
CAS:4485-12-5
RTECS #:WI4370000
Minimum % Wt:15.
Maximum % Wt:35.
Other REC Limits:NONE RECOMMENDED
OSHA PEL
:10 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:LITHIUM HYDROXIDE
CAS:1310-65-2
RTECS #:OJ6307070
< Wt:1.
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS: N/P. POTENTIAL HEALTH
EFFECTS - EYE: CONTACT WITH EYES MAY CAUSE TEMPORARY IRRITATION.
SKIN

: MAY CAUSE MILD IRRITATING. INHALATION. NOT ANTICIPATED DURING INDUSTRIAL USE.. INGESTION: NO T ANTICIPATED DURING INDUSTRIAL USE.

Explanation of Carcinogenicity:CONTAINS ZINC CHROMATE.

Effects of Overexposure:IRRITATION

=====
===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH EYES WITH COPIOUS AMOUNT OF WATER FOR A MINIMUM OF 15 MINUTES. IF CHRONIC IRRITATION DEVELOPS, CONTACT A PHYSICIAN. SKIN: WASH CONTACTED AREAS WITH SOAP AND WATER.

INGESTION: IF ING ESTED, DO NOT INDUCE VOMITING. GET PROMPT MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>204.4C, 400.F

Lower Limits:ND

Upper Limits:ND

Extinguishing Media:WATER, CO2, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP AND CONTAIN FOR SALVAGE OR DISPOSAL.

WASH ALL WALKING SURFACES WITH DETERGENT AND WATER TO REDUCE SLIPPING HAZARD. OBSERVE ALL PROTECTION EQUIPMENT RECOMMENDATIONS. LOCAL, STATE AND FEDERAL REPORTING REQUIREMENTS MAY APPLY TO SPILLS OR RELEASES OF THIS MATTER INTO ENVIRONMENT. SEE APPLICABLE REGULATORY COMPLIANCE INFORMATION.

Neutralizing Agent:REDUCING MATERIALS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Pre

cautions:AVOID CONTACT WITH SKIN AND EYES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED.

Ventilation:NONE NEEDED

Protective Gloves:CLOTH/RUBBER

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EYE BATH, WASHING FACILITY, LAB COAT OR UNIFORM.

Work Hygienic Practices:WASH AFTER ANY CONTACT.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Tex

t:NA

Vapor Pres:NA

Spec Gravity:@25C=0.93

Solubility in Water: