

INTERNATIONAL LUBRICATES INC -- RIFLE BORE CLEANER -- 6850-00-224-6658

===== Product Identification =====

Product ID:RIFLE BORE CLEANER

MSDS Date:07/01/1996

FSC:6850

NIIN:00-224-6658

Status Code:A

MSDS Number: CJLMK

=== Responsible Party ===

Company Name:INTERNATIONAL LUBRICATES INC

Address:10363 W AIRLINE HWY

City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Info Phone Num:504-469-0940

Emergency Pho

ne Num:504-469-0940

CAGE:0W1H4

=== Contractor Identification ===

Company Name:CHEMICAL SPECIALISTS AND DEVELOPMENT INC

Address:2210 HACKBERRY LN

Box:687

City:CONROE

State:TX

ZIP:77305

Country:US

Phone:409-756-1065

Contract Num:SP0450-99-M-C904

CAGE:4N760

Company Name:INTERNATIONAL LUBRICANTS INC

Address:10363 W AIRLINE HWY

Box:City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Phone:504-469-0940(504-471-0104FAX)

CAGE:0W1H4

===== Composition/Information on Ingredients =====

Ingred

Name:SOLVENT PETROLEUM HYDROCARBON

= Wt:60.

OSHA PEL:200 PPM

Ingred Name:LIGHTWEIGHT OIL

= Wt:35.

Other REC Limits:NONE RECOMMENDED

Ingred Name:CORROSION INHIBITOR

= Wt:5.

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Effects of Overexposure:PROLONGED SKIN CONTACT MAY CAUSE IRRITATION AND DERMATITIS. PROLONGED EXPOSURE TO VAPOR MAY CAUSE EYE AND RESPIRATORY TRACT IRRITATION AND HEADACHE.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. EYE CONTACT: FLUSH WITH LARGE AMOUNT OF WATER. IF IRRITATION PERSISTS, SEEK MEDICAL AID. SKIN CONTACT: WASH WITH SOAP AND WATER. INGESTION: DO NOT INDUCE VOMITING . ADMINISTER 2-4 OZ OLIVE OIL OR VEGETABLE OIL AND 1-2 OZ ACTIVATED CHARCOAL; SEEK MEDICAL AID.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:~51.1C, 124.F

Lower Limits:.7

Upper Limits:

5.0

Extinguishing Media:DRY CHEMICAL PREFERRED. FOAM AND WATER ALSO APPLICABLE.

Fire Fighting Procedures:USE FOAM AND WATER SPRAY CAREFULLY TO PREVENT EXCESSIVE FROTHING.

Unusual Fire/Explosion Hazard:KEEP AWAY FROM HEAT OR OPEN FLAME. CAN REACT WITH OXIDIZING MATERIAL, COMBUSTIBLE.

===== Accidental Release Measures =====

Spill Release Procedures:STOP FLOW. ELIMINATE IGNITION SOURCES. ABSORB OR SCRAPE UP.

===== Handling and Storage =====

ge =====

Handling and Storage Precautions:KEEP CONTAINERS TIGHTLY CLOSED. DO NOT STORE OR MIX WITH STRONG OXIDANTS. STORE IN COOL WELL-VENTILATED AREA.

Other Precautions:STORE AWAY FROM POSSIBLE SOURCES OF IGNITION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE DURING NORMAL USAGE. VAPOR REMOVING AIR PURIFYING RESPIRATOR FOR MIST AND SPRAY.

Protective Gloves:FOR PROLONGED CONTACT

Eye Protection:CHEMICAL GOGGIES

Ot

her Protective Equipment:PROTECTIVE GARMENT AS REQUIRED

Work Hygienic Practices:READ ALL LABELS CAREFULLY BEFORE USING.

Supplemental Safety and Health

FLASH POINT = 120, PER DDRV.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:=181.C, 357.8F

B.P. Text:181C-290C

Vapor Pres:NEGLIGIBLE

Vapor Density:4.5

Spec Gravity:.838-.843(H2O=1)

Evaporation Rate & Reference:N/A(BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR, PALE LUBRICATI

NG OIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS SUCH AS CHLORINE AND CONCENTRATED OXYBEN.

Hazardous Decomposition Products:CARBON MONOXIDE IN CASES OF INCOMPLETE COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE UNDER CONTROLLED CONDITIONS. OBSERVE LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by th

e compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.