

PITT PENN OIL CO -- PREMIUM DEXRON III/ MERCON AUTOMATIC TRANSMIS

=====  
MSDS Safety Information  
=====

FSC: 9150  
NIIN: 01-114-9968  
MSDS Date: 04/17/2000  
MSDS Num: CJTJF  
Product ID: PREMIUM DEXRON III/ MERCON AUTOMATIC TRANSMISSION FLUID  
MFN: 02  
Responsible Party  
Cage: 0A1G5  
Name: PITT PENN OIL CO  
Address: 426 FREEPORT R  
D  
Box: 296  
City: CREIGHTON PA 15030-0296  
Info Phone Number: 724-226-2712  
Emergency Phone Number: 800-255-3924 (CHEM TEL)  
Resp. Party Other MSDS No.: 302050,302061,302063,302070,302075

=====  
Item Description Information  
=====

Item Manager: S9G  
Item Name: HYDRAULIC FLUID,AUTOMATIC TRANSMISSION  
Specification Number: NONE  
Type/Grade/Class: NONE  
Unit of Issue: DR  
Quantitative Expression: 00000000055GL

UI Container Qty: 0  
Type of Container: DRUM

=====  
Ingredients  
=====

Name: \*\*\* PROPRIETARY \*\*\*  
-----

=====  
Health Hazards Data  
=====

LD50 LC50 Mixture: NOT PROVIDED  
Carcinogenicity Inds - NTP: NO  
IARC: NO  
OSHA: NO  
Effects of Exposure: ACUTE TOXICOLOGICAL PROPERTIES: NO DAT

A AVAILABLE. CHRONIC

EFFECTS OF OVEREXPOSURE: PROLONGED SKIN CONTACT MAY CAUSE DERMATITIS OR SKIN IRRITATION.

Explanation Of Carcinogenicity: NONE

Signs And Symptoms Of Overexposure: NOT PROVIDED

Medical Cond Aggravated By Exposure: NOT PROVIDED

First Aid: EYES: IMMEDIATELY FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES AND CALL A PHYSICIAN. SKIN: REMOVE EXCESS WITH CLOTH OR PAPER.

WASH THOROUGHLY WITH SOAP AND WATER. PROLONGED SKIN CONTACT MAY CAUSE DERMATITIS OR IRRITATION.

INHALATION: REMOVE VICTIM TO FRESH AIR. CALL A PHYSICIAN.

IF SWALLOWED: CONTACT A PHYSICIAN IMMEDIATELY.

=====  
Handling and Disposal  
=====

Spill Release Procedures: TRANSFER BULK OF MATERIAL INTO ANOTHER CONTAINER.

ABSORB WITH INERT MATERIAL SUCH AS EARTH, SAND, OR VERMICULITE, SWEEP UP AND DISPOSE REMAINING MATERIAL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS

Neutralizing Agent:

NOT RELEVANT

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE, AND LOCAL REGULATIONS.

Handling And Storage Precautions: DO NOT HANDLE OR STORE AT TEMPERATURES OVER 38 DEG C OR 100 DEG F. MAXIMUM STORAGE TEMPERATURE: 38 DEG C (100 DEG F).

Other Precautions: NOT PROVIDED

=====  
Fire and Explosion Hazard Information  
=====

Flash Point Method: COC

Flash

Point: =193.3C, 380.F

Extinguishing Media: DRY CHEMICAL OR WATER FOG OR CO2 OR FOAM. EXPOSED MATERIAL MAY BE COOLED WITH WATER.

Fire Fighting Procedures: DO NOT USE WATER, EXCEPT AS FOG.

Unusual Fire/Explosion Hazard: NONE

=====  
Control Measures  
=====

Respiratory Protection: NONE, UNLESS OIL MIST EXCEEDS 5MG/M3

Ventilation: NONE, UNLESS OIL MIST EXCEEDS 5MG/M3

Protective Gloves: NEOPRENE OR N

ITRATE RUBBER

Eye Protection: CHEMICAL SAFETY GOGGLES WITH SIDE SHIELDS OR FACE SHIELDS

Other Protective Equipment: LAUNDRER SOILED CLOTHES BEFORE REUSE.

Work Hygienic Practices: NOT PROVIDED

Supplemental Safety and Health: PRODUCT NUMBER: 302050, 302063, 302070, 302075,  
302074J

Physical/Chemical Properties

HCC: V6

NRC/State LIC No: NOT RELEVANT

Boiling Point: >357.2C, 675.F

Melt/

Freeze Pt: =-26.1C, -15.F

M.P/F.P Text: POUR POINT

Decomp Text: NOT PROVIDED

Vapor Pres: 0 (MMHG @ 20 C)

Vapor Density: NOT VOLATI

Spec Gravity: 0.870 @ 60 DEG F

Viscosity: 150 TO 155 (SUS @ 100 F)

Evaporation Rate & Reference: 0

Solubility in Water: 0% @ 20 C (BY WEIGHT %)

Appearance and Odor: RED COLORED LIQUID, PETROLEUM ODOR

Percent Volatiles by Volume: 0

Corrosion Rate: NOT PROVIDED

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: HIGH TEMPERATURES

Materials To Avoid: STRONG OXIDIZERS SUCH AS HYDROGEN PEROXIDE, BROMINE, AND  
CHROMIC ACID

Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE FROM  
BURNING. OXIDES OF PHOSPHOROUS. OXIDES OF SULFUR.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NONE

Toxicological Information

=====  
Toxicological Information: PERMISSIBLE CONCENTRATION= OIL MIST MINERAL 5 MG/M3  
(OSHA AND NIOSH). CHRONIC EFFECTS OF OVEREXPOSURE: PROLONGED SKIN CONTACT MAY  
CAUSE DERMATITIS OR SKIN IRRITATION. ACUTE TOXICOLOGICAL PROPERTIES= N O DATA  
AVAILABLE

=====  
Ecological Information

=====  
Ecological: NOT PROVIDED

=====  
=

MSDS Transport Information

=====  
Regulatory Information

=====  
Sara Title III Information: NOT PROVIDED

Federal Regulatory Information: ALL COMPONENTS ARE LISTED ON TSCA INVENTORY.

State Regulatory Information: NOT PROVIDED

=====  
Other Information

=====  
Other Information: NEW AND USED MOTOR OILS HAVE BEEN TESTED FOR POTENTIAL  
CARCINOGENICITY IN LABORATORY MICE. ONLY USED MOTOR OILS WERE SHOWN TO CAUSE  
SKIN CANCER WHEN REPEATEDLY APPLIED TO MICE WITHOUT ANY EFFORT TO RE MOVE THE  
MATERIAL BETWEEN APPLICATIONS.

=====  
Transportation Information

=====  
Responsible Party Cage: 0A1G5

Trans ID NO: 150197

Product ID: PREMIUM DEXRON III

/ MERCON AUTOMATIC TRANSMISSION FLUID

MSDS Prepared Date: 04/17/2000

Review Date: 10/12/2000

MFN: 2

Net Unit Weight: 398.6 LBS

Multiple KIT Number: 0

Unit Of Issue: DR

Container QTY: 0

Type Of Container: DRUM

Additional Data: NOT REGULATED FOR TRANSPORTATION, PER MSDS.

=====  
Detail DOT Information

=====  
DOT PSN Code: ZZZ

DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====

=====  
Detail IMO Information  
=====

IMO PSN Code: ZZZ

IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION  
=====

=====  
Detail IATA Information  
=====

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION  
=====

=====  
Detail AFI Information  
=====

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION  
=====

=====  
HAZCOM Label  
=====

Product ID: PREMIUM DEXRON III/ MERCON AUTOMATIC TRANSMISSION FLUID

Cage: 0A1G5

Company Name: PITT PENN OIL CO

Street: 426 FREEPORT RD

PO Box: 296

City: CREIGHTON PA

Zipcode: 15030-0296

Health Emergen

cy Phone: 800-255-3924 (CHEM TEL)

Label Required IND: Y

Date Of Label Review: 10/12/2000

Status Code: C

MFG Label NO: 302075

Label Date: 05/01/2000

Year Procured: 2000

Origination

Chronic Hazard IND: Y

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: CAUTION

Respiratory Protection IND: NO

Health Hazard: Slight

Contact Hazard: Slight

Fire Hazard: None

Reactivity Hazard: None

Hazard And Precautions: TARGET ORGANS: N/P. CAUTION: CONTINOUS CONTACT WITH  
USED MOTOR OIL HAS CAUSED SKIN

CANCER IN LABORATORY ANIMALS. IN CASE OF

CONTACT WASH THOROUGHLY WITH SOAP AND WATER. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: EYES: FLUSH WITH LARGE AMOUNT OF WATER FOR AT LEAST 15 MINUTES.

SKIN: WASH EXPOSED PORTION WITH SOAP AND WATER. INGESTION: DO NOT INDUCE

VOMITING. SEEK MEDICAL ATTENTION. IN CASE OF FIRE: USE WATER SPRAY, FOAM,

DRY CHEMICAL OR CARBON DIOXIDE (CO<sub>2</sub>). IN CASE OF SPILL: DO NOT USE WATER. SOAK

UP WITH SAND, EARTH, OR ABSORBENT MATERIAL. CONTAINER: DO NOT CUT, DRI

LL,

GRIND OR WELD ON OR NEAR CONTAINER.

=====  
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any persons

on or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.