

PRAXAIR SURFACE TECHNOLOGIES INC -- NI-365-2 PRODUCT CODE ZNI365-0210 --  
3439-01-426-2088

===== Product Identification =====

Product ID:NI-365-2 PRODUCT CODE ZNI365-0210

MSDS Date:09/10/1993

FSC:3439

NIIN:01-426-2088

Status Code:A

MSDS Number: CJWQK

=== Responsible Party ===

Company Name:PRAXAIR SURFACE TECHNOLOGIES INC

Address:1555 MAIN STREET

City:INDIANAPOLIS

State:IN

ZIP:46224-3283

Country:US

Info Phone Num:317-240-2650

Emergency Phone Num:(800)424-9300

Preparer's Name:MICHELLE ALEXANDER

Chemtrec Ind/Phone:(800)424-9300

CAGE:0FGH2

=== Contractor Identification ===

Company Name:PRAXAIR SURFACE TECHNOLOGIES INC

Address:1555 MAIN STREET

Box:City:INDIANAPOLIS

State:IN

ZIP:46224-3283

Country:US

Phone:317-240-2650

CAGE:0FGH2

Company Name:STARGHILL TECHNOLOGIES CORP

Address:3850 OAKMAN BLVD

Box:City:DETROIT

State:MI

ZIP:48204-1119

Country:US

Phone:313-933-4141

Contract Num:SP0450-95-D-4037

CAGE:0VYG8

=====  
=====  
Composition/Information on Ingredients  
=====  
=====

Ingred Name:CHROMIUM  
CAS:7440-47-3  
RTECS #:GB4200000  
Minumum % Wt:5.  
Maxumum % Wt:20.  
OSHA PEL:1 MG/M3  
ACGIH TLV:0.5 MG/M3  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:NICKEL  
CAS:7440-02-0  
RTECS #:QR5950000  
Minumum % Wt:50.  
Maxumum % Wt:75.  
OSHA PEL:1 MG/M3  
ACGIH TLV:1 MG/M3

Ingred Name:COBALT  
CAS:7440-48-4  
RTECS #:GF8750000  
Minumum % Wt:5.  
Maxumum % Wt:20.  
OSHA PEL:0.1 MG/M3  
ACGIH TLV:0.02 MG/M3

Ingred Name:TA  
NTALUM  
CAS:7440-25-7  
RTECS #:WW5505000  
Minumum % Wt:5.  
Maxumum % Wt:20.  
OSHA PEL:5 MG/M3  
ACGIH TLV:5 MG/M3

Ingred Name:ALUMINIUM  
CAS:7429-90-5  
RTECS #:BD0330000  
Minumum % Wt:5.  
Maxumum % Wt:20.  
OSHA PEL:15 MG/M3  
ACGIH TLV:10 MG/M3

Ingred Name:TUNGSTEN  
CAS:7440-33-7  
RTECS #:YO7175000  
Minumum % Wt:1.  
Maxumum % Wt:5.  
ACGIH TLV:5 MG/M3  
ACGIH STEL:10 MG/M3

Ingred Name:RHENIUM  
CAS:7440-15-5  
Minumum % Wt:1.  
Maxumum % Wt:5.

% Wt:5.  
OSHA PEL:0.5 MG/M3  
ACGIH TLV:0.5 MG/M3

Ingred Name:MOLYBDENUM  
CAS:7439-98-7  
RTECS #:QA4680000  
Minumum % Wt:1.  
Maxumum % Wt:5.  
ACGIH TLV:10 MG/M3

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:SKIN:MAY CAUSE ALLERGIC DERMATITIS,  
WITH REDNESS & PAPULAR FORMATION IN S

USCEPTABLE INDIVIDUALS. MAY

CAUSE ULCERS PROGRESSING TO DRY & SCALY SKIN, FEVER. EYE:MAY CAUSE  
IRRIATATION, EXPERIENCED AS REDN ESS & EXCESS REDNESS OF THE  
CONJUCTIVA. SWALLOWING: MAY CAUSE NAUSEA, ABDOMINAL PAIN, VOMITING,  
DIARRHEA, CENTRAL NERVOUS SYSTEM DEPRESSION, & BURNING SENSATION.  
INHALATION:MAY CAUSE RESPIRATORY TRACT IRRITATION, WITH CHEST  
PAIN, VOIMITING, DIARRHEA, BURNING SENSATION, & CENTRAL NERVOUS  
SYSTEM DEPRESSION. MAY ALSO CAUSE INTERSTITIAL PNEUMONI

TIS &

SENSITIZATION OF THE RESPIRATORY TRACT IN SUSCEPTIB LE PERSONS.

Explanation of Carcinogenicity:NICKEL AND CHROMIUM HAVE BEEN DETERMINED  
TO CAUSE CANCER IN EXPERMENTAL ANIMALS(IARC, NTP). NICKEL IS LISTED  
AS A PROBABLE HUMAN CARCINOGEN. CHROMIUM IS LISTED AS A HUMAN  
CARCINOGEN. CHRONIC ECZEMA/NE URODERMATITIS FROM NICKEL DOES NOT  
REQUIRE CONTINUOUS METAL CONTACT.

Effects of Overexposure:MAY CAUSE SENSITIZATION IN SUSCEPTABLE  
INDIVIDUALS. CHRONIC EXPOSURE TO THE EYE C

AN CAUSE CORNEAL DAMAGE,  
POLYCYTHEMIA, HYPERPLASIA OF THE THYROID GLAND AND DAMAGE TO THE  
ALPHA CELLS OF THE PANCREAS. REPEATED INHALATION MAY CAUSE  
EMPHYSEMA OR PULMONARY FIBROTIC DISEASE. CHRONIC SKIN CONTACT MAY  
SPREAD TO THE WHOLE BODY WITH LESIONS, ITCHING, SORENESS, BURNING  
SENSATION AND REDNESS.

Medical Cond Aggravated by Exposure:BREATHING OF DUST MAY AGGRAVATE  
ASTHMA AND INFLAMMATORY OR FIBROTIC PULMONARY DISEASE. MAY ALSO  
AGGRAVATE AN EXISTING DERMATITIS.

=====  
First Aid Measures  
=====

First Aid:SWALLOWING:GIVE AT LEAST 2 GLASSES OF MILK OR WATER. INDUCE VOMITING, UNLESS PATIENT IS UNCONSCIOUS. CALL A PHYSICIAN.  
SKIN:WASH THOROUGHLY WITH SOAP & WATER. INHALATIO: REMOVE TO FRESH AIR. GIVE ARTI FICIAL RESPIRATION IF NOT BREATHING. OXYGEN MAY BE GIVEN IF NECESSARY. CALL A PHYSICIAN. EYES: FLUSH THOROUGHLY WITH PLENTY OF WATER. IF DISCOMFORT PERSISTS, SEEK MEDICAL ATTENTION.PREFERABLYAN O PTHAL MOLOGIST. NOTES TO PHYSCIAN:THE HAZARDS OF THIS MATERIAL ARE MAINLY DUE TO ITS SENSITIZING AND MILD IRRITATING PROPERTIES. THERE IS NO SPECIFIC ANTIDOTE.

=====  
Fire Fighting Measures  
=====

Flash Point:NONE  
Upper Limits:0.00%  
Extinguishing Media:USE SPECIAL DRY POWDER METAL EXTINGUISHING MATERIAL TO EXTINGUISH METAL FIRES. USE APPROPRIATE EXTINGUISHER FOR COMBUSTABLE MATERIALS THAT MAY BE IGNITED BY THE THERMAL SPRAY FLAME.  
Fire Fighti  
ng Procedures:NONE SPECIFIED BY MANUFACTURER.  
Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT TO PROTECT AGAINST HAZARDS AND DISPOSE OF PER WASTE DISPOSAL METHOD.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.  
Other Precau  
tions:CAUTION: WHEN THERMAL SPRAYING - ELECTRICITY CAN CAUSE FATAL SHOCK! DO NOT TOUCH LIVE ELECTRICAL PARTS! ARC RAYS CAN BURN EYES AND SKIN! WEAR RECOMMENDED EYE AND BODY PROTECTION. FUMES, GAS, AND DUST CAN HARM YOUR HEALTH.PROVIDE ENOUGH VENTILATION AND WEAR RESPIRATOR IF REQUIRED.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:DEPENDS UPON SPECIFIC USE, CONDITION, AND LOCATION. IF THERE IS DUSTINESS, WEAR RESPRI-RATOR SELECT

ED PER

OSHA 1910.134, AND OSHA 29 CFR 1910.252 AND ANSI Z49.1.

Ventilation:LOCAL DUST PICK UP AND VENTILATION RECOMMENDED.

Protective Gloves:NOT REQUIRED.

Eye Protection:WHEN DUSTY USE GOGGLES PER OSHA 1910.13

Other Protective Equipment:SEE ANSI Z49.1, ANSI Z87.1, ANSI Z88.2 FOR HELMETS, FACE SHIELDS AND GOGGLES.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health  
NONE SPECIFIED BY MANUFACTURER.

=====  
===== Physical/Chemical Properties =====  
=====

HCC:N1

Boiling Pt:B.P. Text:NONE

Vapor Density:N/VOLATILE

Evaporation Rate & Reference:UNAVAILABLE

Appearance and Odor:DUSTY DARK GRAY POWDER

Percent Volatiles by Volume:0

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE KNOWN.

Stability Condition to Avoid:NONE KNOWN.

Hazardous Decomposition Products:WHEN THERMAL SPRAYING, WILL VARY WITH OPERATING CONDITIONS. REASONABLY EXPECTED DECOMPOSITION PRODUCTS OF

NORMAL OPERATION FROM THIS THERMAL SPRAY POWDER INCLUDE OXIDES OF THE LISTED INGREDIENTS.

=====  
===== Toxicological Information =====

Toxicological Information:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Ecological Information =====

Ecological:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF WASTE PER LOCAL, STATE, AND FEDERAL REGULATIONS.

=====

=====  
MSDS Transport Information  
=====

Transport Information:NONE SPECIFIED BY MANUFACTURER.

=====  
Regulatory Information  
=====

SARA Title III Information:PRODUCT CONTAINS THE FOLLOWING TOXIC  
CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF  
THE EMERGENCY PLANNING AND COMMUNITY RIGHT TO KNOW ACT OF 1986 AND  
OF 40 CFR 372: CHROMIUM, CAS# 7440-47-3,