

QUANTUM SILICONES -- QSIL-60 -- 5970-00-689-8832

=====
===== Product Identification =====

Product ID:QSIL-60
MSDS Date:10/09/1998
FSC:5970
NIIN:00-689-8832
MSDS Number: CKCYQ
=== Responsible Party ===
Company Name:QUANTUM SILICONES
Address:7518 WHITEPINE RD
City:RICHMOND
State:VA
ZIP:23237
Country:US
Info Phone Num:804-271-9010
Emergency Phone Num:804-271-9010
Preparer's Name:PHIL MCDERMOTT
Chemtrec Ind
/Phone:(800)424-9300
CAGE:1HTG4
==== Contractor Identification ====
Company Name:QUANTUM SILICONES
Address:7518 WHITEPINE RD
Box:City:RICHMOND
State:VA
ZIP:23237
Country:US
Phone:804-271-9010
CAGE:1HTG4
Company Name:THE SMITH GROUP INC.
Address:811 E. CAYUGA STREET
Box:City:PHILADELPHIA
State:PA
ZIP:19124-3893
Country:US
Phone:215-743-8200
Contract Num:SP0430-99-M-G341
CAGE:2B613

=====
===== Composition/Information on Ingredients =====

Ingred Name:IRON OXIDE
CAS:1309-37-1
RTECS #:NO7

400000
Minumum % Wt:25.
Maxumum % Wt:40.
OSHA PEL:10 MG/M3
ACGIH TLV:5 MG/M3;2 PPM

Ingred Name:FULLERS EARTH
CAS:61790-53-2
RTECS #:VV7311000
Minumum % Wt:5.
Maxumum % Wt:13.
OSHA PEL:SEE TABLE Z-3
ACGIH TLV:10 MG/M3

Ingred Name:ETHYL SILICATE
CAS:78-10-4
RTECS #:VV9450000
Minumum % Wt:.5
Maxumum % Wt:2.5
OSHA PEL:850 MG/M3;100 PPM
ACGIH TLV:85 MG/M3;10 PPM

Ingred Name:POLYDIMETHYLSILOXANES, SILANOL TERMINATED
CAS:70131-67-8
Minumum % Wt:25.
Maxumum % Wt:45.

=====
entification =====

LD50 LC50 Mixture:NO DATA PROVIDED BY MANUFACTURER
Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Health Hazards Acute and Chronic:PRIMARY ROUTE OF EXPOSURE IS EYE
CONTACT. EYE CONTACT CAN CAUSE MILD, TEMPORARY IRRITATION.
Explanation of Carcinogenicity:NO DATA PROVIDED BY MANUFACTURER
Effects of Overexposure:EYE CONTACT CAN CAUSE MILD, TEMPORARY
IRRITATION.
Medical Cond Aggravated by Exposure:NO DATA PROVIDED BY MANUFACTURER.

=====

===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH WATER FOR A MINIMUM OF 15 MINUTES.
SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. SKIN CONTACT: WASH
THOROUGHLY WITH SOAP AND WATER. INGESTION: SEEK MEDICAL ATTENTION.
INHALATION: N/A MATERIAL IS NON-VOLATILE.

===== Fire Fighting Measures =====

Flash Point:>148.9C, 300.F
Extinguishing Media:USE WATER FOG, DRY CHEMICAL, FOAM OR CO2.
Fire Fighting Procedures:FIRE
-FIGHTERS SHOULD WEAR SELF-CONTAINED
BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING. USE WATER SPRAY
TO COOL NEARBY CONTAINERS.
Unusual Fire/Explosion Hazard:MATERIAL IS NON-COMBUSTIBLE,
NON-FLAMMABLE.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE THE AREA OF UNPROTECTED PERSONNEL.
USE PERSONAL PROTECTION TO MINIMIZE EXPOSURE. MINIMIZE SPREAD OF
MATERIAL BY USING A DIKE, ABSORBENT MATERIAL OR OTHER METHOD TO
CONTAIN MATERIAL. SCRAPE, SUCK OR WIPE UP MATERIAL & PLACE IN
APPROPRIATE CONTAINERS FOR DISPOSAL. ALL FEDERAL, STATE AND LOCAL
LAWS CONCERNING REPORTING OF LEAKS & SPILLS & DISPOSAL OF
RECOVERED MATERIAL SHOULD BE FOLLOWED.
Neutralizing Agent:NO DATA PROVIDED BY MANUFACTURER

===== Handling and Storage =====

Handling and Storage Precautions:NO DATA PROVIDED BY MANUFACTURER
Other Precautions:NO DATA PROVIDED BY MANUFACTURER

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO DATA PROVIDED BY MANUFACTURER
Ventilation:NO DATA PROVIDED BY MANUFACTURER
Protective Gloves:WEAR PROTECTIVE GLOVES WHEN HANDLING.
Eye Protection:WEAR PROTECTIVE GOGGLES TO PREVENT EYE CONTACT.
Other Protective Equipment:USE APPROVED DUST MASK OR BREATHING
APPARATUS AND FULL PROTECTIVE CLOTHING.
Work Hygienic Practices:NO DATA PROVIDED BY MANUFACTURER
Supplemental Safety and Health
KEY1: N1. ITEM IS A TWO PART KIT. CONT

AINS QSIL-60 AND QSIL-60 CAT

(SERIAL NUMBER=CKCYR). QSIL-60 IS NONHAZARDOUS. QSIL-60 CAT IS TOXIC. CAS# FOR ETHYL SILICATE ON MSDS IS 75-10-4 (INVALID CAS#), ONE GIVEN IN HMRIS RECORD IS CORRECT ONE PER CAS.

===== Physical/Chemical Properties =====

HCC:T4

Boiling Pt:>148.9C, 300.F

Vapor Pres:@20C, 1MM HG NEGLIGIBLE

Vapor Density:NEGLIGIBLE

Spec Gravity:1.40G/CM3 (WATER=1)

Evaporation Rate & Reference:NEGLIGIBLE

Solubility in Water:NEGLIGIBLE / TOLU

ENE

Appearance and Odor:COLOR: RED ODOR: NEGLIGIBLE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE.

Stability Condition to Avoid:THIS MATERIAL IS CHEMICALLY STABLE.

Hazardous Decomposition Products:EXTREME HEAT OR FLAME MAY LIBERATE CARBON MONOXIDE, CARBON DIOXIDE, SILICONE, OXIDES AND FORMALDEHYDE.

===== Toxicological Information =====

Toxicological Information:OCCUPATIONAL EXPOSURE LIMITS.

DUE TO THE LOW

TOXICITY OF THIS MATERIAL NO LIMIT HAS BEEN ESTABLISHED. TOXICITY: DUE TO THE LOW TOXICITY OF THIS MATERIAL, SPECIFIC TOXICITY DATA IS UNAVAILABLE.

===== Ecological Information =====

Ecological:NO DATA PROVIDED BY MANUFACTURER

===== Disposal Considerations =====

Waste Disposal Methods:ALL FEDERAL, STATE AND LOCAL LAWS CONCERNING THE REPORTING OF LEAKS AND SPILLS AND THE DISPOSAL OF RECOVERED

MATERIAL SHOULD BE FOLLOWED.

===== MSDS Transport Information =====

Transport Information:NO DATA PROVIDED BY MANUFACTURER

===== Regulatory Information =====

SARA Title III Information:NO DATA PROVIDED BY MANUFACTURER
Federal Regulatory Information:NO DATA PROVIDED BY MANUFACTURER
State Regulatory Information:NO DATA PROVIDED BY MANUFACTURER.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.