

BOW SOLDER PRODUCTS CO INC -- #851, NVOC FLUX -- 3439-01-007-5494

=====
Product Identification
=====

Product ID:#851, NVOC FLUX
MSDS Date:06/30/1997
FSC:3439
NIIN:01-007-5494
Status Code:A
MSDS Number: CKDDD
=== Responsible Party ===
Company Name:BOW SOLDER PRODUCTS CO INC
Address:1 CROSSMAN ROAD
City:SAYREVILLE
State:NJ
ZIP:08772
Country:US
Info Phone Num:732-316-2100
Emergency Phone Num:800-535
-5053
CAGE:52329
=== Contractor Identification ===
Company Name:BOW ELECTRONIC SOLDERS
Address:1 CROSSMAN ROAD
Box:City:SAYREVILLE
State:NJ
ZIP:08872
Country:US
Phone:732-316-2100/ FAX: 732-316-2177
CAGE:52329
Company Name:JO-JON INC
Address:360 FREEPORT BLVD SUITE 1 & 2
Box:UNKNOW
City:SPARKS
State:NV
ZIP:89431
Country:US
Phone:702-356-6988
Contract Num:SP0490-00-M-Q893
CAGE:009J0

=====
Composition/Information on Ingredients
=====

Ingred Name:DISTILLED WATER
CAS:7732-18-5
RT

ECS #:ZC0110000

< Wt:95.

Ingred Name:ORGANIC ACIDS

< Wt:5.

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NO DATA PROVIDED BY RESPONSIBLE PARTY.

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE (SEVERE SHORT TERM): INHALATION OF FUMES OR INGESTION MAY CAUSE HEADCHE, NAUSEA, MUSCULAR PAIN. IRRITATION OF EYE AND NOSE MAY RESULT FROM CONTACT WITH SOLDERING FUMES. CHRONIC (PROLONGED): ANE MIA, IN

SOMNIA, WEAKNESS, CONSTIPATION, NAUSEA AND ABDOMINAL PAIN DUE TO INGESTION. SKIN RASH, DAMAGE OF MUCOUS MEMBRANE DUE TO SKIN EXPOSURE AND INHALATION.

Explanation of Carcinogenicity:NONE ACCORDING TO NTP, IARC, AND OSHA.

Effects of Overexposure:IRRITATION OF PULMONARY SYSTEM, SKIN RASH.

Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS OF THE LUNDS, DISEASES OF THE BLOOKD AND BLOOD FORMING ORGANS: KIDNEYS, NERVES AND POSSIBLY REPRODUCTIVE SYSTEMS.

=====
===== First Aid Measures =====

First Aid:CONSULT A PHYSICIAN AND GET PROPER MEDICAL ATTENTION WHEN NECESSARY, IN CASE OF CONTACT WITH SMOKE FROM SOLDERING OR REPEATED SKIN CONTACT. EYE CONTACT: FLUSH EYES WITH PLENTY OF WATER FOR 15 MINUTE S. SKIN CONTACT: WASH THOROUGHLY WITH SOAP AND WATER, USE LOTION TO PREVENT DRYNESS. INHALATION: REMOVE PERSON TO FRESH AIR. INGESTION: DRINK A LOT OF WATER, DO NOT INDUCE VOMITING AND GET PROPE R MEDICAL ATT ENTION.

=====
===== Fire Fighting Measures =====

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR ALCOHOL FOAM.

Fire Fighting Procedures:SCBA WITH FULL FACE PIECE AND PROTECTIVE CLOTHING IS RECOMMENDED.

Unusual Fire/Explosion Hazard:CLOSED CONTAINER MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILLS SHOULD BE CLEANED UP WITH ABSORBENT; LARGE SPILLS SHOUL

