

PILKINGTON AEROSPACE INC (FORMERLY- SWEDLOW INC) -- SS-6832 PT B -- 1560-01-308-8459  
===== Product Identification =====

Product ID:SS-6832 PT B  
MSDS Date:02/04/1998  
FSC:1560  
NIIN:01-308-8459  
Status Code:A  
MSDS Number: CKDLC  
=== Responsible Party ===  
Company Name:PILKINGTON AEROSPACE INC (FORMERLY- SWEDLOW INC)  
Address:12122 WESTERN AVE  
City:GARDEN GROVE  
State:CA  
ZIP:92641  
Country:US  
Info Phone Number:714-893-7531  
Emergency Phone Num:800-424-9300  
CAGE:86175  
=== Contractor Identification ===  
Company Name:PILKINGTON AEROSPACE INC (FORMERLY- SWEDLOW INC)  
Address:12122 WESTERN AVE  
Box:City:GARDEN GROVE  
State:CA  
ZIP:92641  
Country:US  
Phone:714-893-7531  
Contract Num:SP0460-97-M-DD28  
CAGE:86175

===== Composition/Information on Ingredients =====

Ingred Name:DIMETHYLMETHYLHYDROGEN POLYSILOXANES  
CAS:68037-59-2  
= Wt:2.

===== Hazards Identification =====

=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Health Hazards Acute and Chronic:EYE CONTACT: DIRECT CONTACT MAY CAUSE TEMPORARY DISCOMFORT WITH MILD REDNESS AND DRYNESS SIMILAR TO WIND BURN. SKIN: A SINGLE RELATIVELY SHORT EXPOSURE CAUSES NO KNOWN ADVERSE EFFECT. SEVERAL REPEATED PROLONGED EXPOSURES (24 TO 48 HOURS) CAUSES NO KNOWN ADVERSE EFFECT. INHALATION: NO IRRITATION TO EYES AND RESPIRATORY PASSAGES. NO INJURY IS LIKELY FROM RELATIVELY SHORT EXPOSURE OF LESS THAN 8 HOURS.

INGESTION: SMALL AMOUNTS TRANSFERRED TO THE MOUTH BY FINGERS DURING USE, ETC., SHOULD NOT INJURE. SWALLOWING LARGE AMOUNTS MAY CAUSE DIGESTIVE DISCOMFORT.

Explanation of Carcinogenicity:PER MSDS:CARCINOGENICITY: MANUFACTURERS MSDS IDENTIFIES THIS PRODUCT AS NOT A CARCINOGEN.

Effects of Overexposure:EYES: TEMPORARY DISCOMFORT WITH MILD REDNESS AND DRYNESS SIMILAR TO WINDBURN. SKIN: NO KNOWN ADVERSE EFFECTS. INHALATION: NO IRRITATION OR INJURY LIKELY.

Y. INGESTION: DIGESTIVE DISCOMFORT. CHRONIC HEALTH EFFECTS: NO KNOWN ADVERSE CHRONIC HEALTH EFFECTS, BUT UNNECESSARY EXPOSURE TO ANY CHEMICAL SHOULD BE AVOIDED.

Medical Cond Aggravated by Exposure:THIS PRODUCT, AS WITH ANY CHEMICAL, MAY ENHANCE ALLERGIC CONDITIONS ON CERTAIN PEOPLE. MANUFACTURER DOES NOT KNOW OF ANY MEDICAL CONDITIONS THAT MIGHT BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

===== First Aid Measures =====

First Aid:EY

ES: FLUSH WITH WATER. SKIN: WIPE OFF AND FLUSH WITH WATER. INHALATION: NO FIRST AID SHOULD BE NEEDED. INGESTION: NO FIRST AID SHOULD BE NEEDED.

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:~100.C, 212.F

Autoignition Temp:Autoignition Temp Text:N/D

Lower Limits:N/D

Upper Limits:N/D

Extinguishing Media:WATER FOG, CO2, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING S

HOULD BE WORN IN FIGHTING FIRES INVOLVING  
CHEMICALS.

Unusual Fire/Explosion Hazard:NONE KNOWN TO PILKINGTON AEROSPACE.

===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN FOR SALVAGE OR DISPOSAL. PRODUCT IS AN OIL IN THE CONTEXT OF THE U.S. CLEAN WATER ACT. SPILLS TO U.S. SURFACE WATER, OR TO WATERCOURSE OR SEWERS LEADING TO U.S. SURFACE WATER THAT CAUSE A VISIBLE SHEEN MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 100F/38C. USE REASONABLE CARE AND CAUTION. MAY GENERATE FLAMMABLE HYDROGEN GAS. AVOID CONTACT WITH WATER, ACIDIC, BASIC OR OXIDIZING MATERIALS. STORE IN ORIGINAL CONTAINER IN COOL, WELL- VENTILATED AREA.

Other Precautions:TRACES OF FORMALDEHYDE AND OTHER THERMAL DECOMPOSITION PRODUC

TS MAY FORM AT TEMPERATURES ABOVE 150C IN THE PRESENCE OF AIR. PROVIDE VENTILATION TO CONTROL VAPOR EXPOSURE WITHIN INHALATION GUIDELINES W HEN HANDLING AT ELEVATED TEMPERATURES. REPORT SPILLS THAT MAY ENTER SURFACE WATERS TO NATIONAL RESPO NSE CENTER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO RESPIRATORY PROTECTION SHOULD BE NEEDED WHEN HANDLING AT ROOM TEMPERATURE. WHEN HANDLING AT ELEVATED EMPERATURES, OR AEROSOL/SP RAY APPLICATIONS, ADDED PRECAUTIONS MAY BE REQUIRED.

Ventilation:LOCAL EXHAUST: NONE SHOULD BE NEEDED. MECHANICAL(GENERAL ): RECOMMENDED FOR ROOM TEMP HANDLING. MAY REQUIRE ADDED PRECAUTION AT ELEVATED TEMP OR WHEN SPRAYING

Protective Gloves:NOT APPLICABLE.

Eye Protection:USE PROPER PROTECTION-SAFETY GLASSES, AS A MINIMUM.

Work Hygienic Practices:WASHING AT MEALTIME AND END OF SHIFT IS ADEQUATE. GOOD PRACTICE REQUIRES THAT GROSS AMOUNT OF ANY CHEMICAL BE REMOVED FROM SKIN A

S SOON AS PRACTICAL, ESPECIALLY BEFORE EATING  
OR SMOKING.

Supplemental Safety and Health

KEY1:V5. THIS ENTRY, MFN 2, DESCRIBES PART TWO OF A THREE PART KIT. SEE  
THIS SAME NSN, CAGE 86175, MFN 1 AND MF 3, FOR PART 1 AND PART 3  
DATA.

===== Physical/Chemical Properties =====

HCC:F2

Vapor Pres: