View NSN Online: https://aerobasegroup.de/nsn/6810-00-236-5670

Product ID:NITRIC ACID, TECHNICAL

MSDS Date:04/08/1999

FSC:6810

NIIN:00-236-5670

Status Code:A

MSDS Number: CKFXB === Responsible Party ===

Company Name: PHOENIX INDUSTRIES INC Address: 11028 S LEADBETTER RD UNIT 10

City: ASHLAND

State:VA ZIP:23005 Country:US

Info Phone Num:804-264-5183

Emergency

Phone Num:804-264-5183

Chemtrec Ind/Phone:(800)424-9300

CAGE:0YED2

=== Contractor Identification ===

Company Name: PHOENIX INDUSTRIES INC Address: 1519 CHAMBERLAYNE PARKWAY

Box:City:RICHMOND

State:VA ZIP:23222 Country:US

Phone:804-264-5183/FAX: 264-5535 Contract Num:SPO450-00-M-D935

CAGE:0YED2

======= Composition/Information on Ingredients ========

Ingred Name:NITRIC ACID

CAS:7697-37-2

RTECS #:QU5775000 Minumum % Wt:65. Maxumum % Wt:70.

OSHA PEL:5 MG/M3;2 PPM ACGIH TLV:5.2 MG/M3;2 P PM

ACGIH STEL:10 MG/M3;4 PPM

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Minumum % Wt:30. Maxumum % Wt:35.

LD50 LC50 Mixture: INHALATION, RAT LC50: 67 PPM

Health Hazards Acute and Chronic:INHALATION: CORROSIVE! INHALATION OF VAPORS CAN CAUSE BREATHING DIFFICULTIES & LEAD TO PNEUMONIA & PULMONARY EDEMA, WHICH MAY BE FATAL. INGESTION: CORROSIVE! SWALLOWING NITRIC ACID

CAN CAUSE IMMEDIA TE PAIN & BURNS OF THE

MOUTH, THROAT, ESOPHAGUS & GASTROINTESTINAL TRACT. SKIN: CORROSIVE! CAN CAUSE REDNESS, PAIN, AND SEVERE SKIN BURNS. CONCENTRATED SOLUTIONS CAUSE DEEP ULCERS AND STAIN. EYES: C ORROSIVE! VAPORS ARE IRRITATING & MAY CAUSE SEVERE DAMAGE TO EYES. SPLASHES MAY CAUSE SEVERE BURNS & PERMANENT EYE DAMAGE. CHRONIC: LONG-TERM EXPOSURE TO CONCENTRATED VAPORS MAY CAUSE EROSION OF TEETH & LUNG DAMAGE.

Effects of Overexposure: INHALATION:

COUGHING, CHOKING, AND IRRITATION

OF THE NOSE, THROAT, AND RESPIRATORY TRACT. SYMPTOMS MAY DISAPPEAR ONLY TO RETURN IN A FEW HOURS & MORE SEVERELY. ONSET OF SYMPTOMS MAY BE DELAYED FOR 4-3 0 HOURS. SKIN: REDNESS, PAIN, SEVERE BURNS. EYES: SEVERE BURNS, PERMANENT EYE DAMAGE. INGESTION: PAIN, BURNS TO MOUTH, THROAT, ESOPHAGUS & GI TRACT.

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE DISEASE, OR CARDIOPULMONARY DISEASE MAY BE MORE SU

SCEPTIBLE TO THE EFFECTS OF THIS SUBSTANCE.

First Aid:INHALATION:REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. INGESTION: DO NOT INDUCE VOMITING! GIVE LARGE QUANTITIES OF WATER OR MILK IF AVA ILABLE. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. SKIN CONTACT: IN CASE OF CONTACT, IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 M

INUTES WHILE REMOVING

CONTAMINATED CLOTHING & SHOES. WASH CLOTHING BEFORE REUSE. THOROUGHLY CLEAN SHOES BEFORE REUSE. EYE CONTACT: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES, LIFTING LIDS OCCASIONALLY. GET MEDICAL ATTENTI ON.

========== Fire Fighting Measures ===============

Extinguishing Media:WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL. DO NOT GET WATER INSIDE CONTAINER.

Fire Fighting Procedures: IN THE EVENT OF

A FIRE, WEAR FULL PROTECTIVE

CLOTHING & NIOSH-APPROVED SELF-CONTAINED BREATHING APPRATUS WITH FULL FACEPIECE OPERATED IN THE PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:REACTS EXPLOSIVELY WITH COMBUSTIBLE ORGANIC OR READILY OXIDIZABLE MATERIALS SUCH AS: ALCOHOLS, TURPENTINE, CHARCOAL, ORGANIC REFUSE, METAL POWDER, HYDROGEN SULFIDE, ETC. REACTS WITH MOST METALS TO REL EASE HYDROGEN GAS WHICH CAN FORM EXPLOSIVE MIXTURES WITH AIR.

===		
==========	Accidental Release Measures	

Spill Release Procedures: VENTILATE AREA OF LEAK OR SPILL. WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT. KEEP UNNECESSARY & UNPROTECTED PERSONNEL FROM ENTERING. CONTAIN & RECOVER LIQUID WHEN POSSIBLE. NEUTRALIZE WITH ALKALIN E MATERIAL THEN ABSORB WITH AN INERT MATERIAL & PLACE IN A CHEMICAL WASTE CONTAINER. DO NOT USE COMBUSTIBLE MATERIALS, SUCH AS SAW DUST. DO NO NOT FLUSH TO SEWER.

Neutralizing Agent:SODA ASH, LIME.

Trainaling and Glorage	======= Ha	andling and	d Storage	
------------------------	------------	-------------	-----------	--

Handling and Storage Precautions:STORE IN A COOL, DRY, VENTILATED STORAGE AREA WITH ACID RESISTANT FLOORS & GOOD DRAINAGE. PROTECT FROM PHYSICAL DAMAGE. KEEP OUT OF DIRECT SUNLIGHT & AWAY FROM HEAT, WATER & INCOMPATIBLE MATERIALS. DO NOT WASH OUT CONTAINER & USE IT FOR OTHER PURPOSES.

Other Precautions:WHEN DILUTING, THE ACID SHOULD ALWAYS BE ADDED SLOWLY TO WATER & IN SMALL AMOUNTS. NEVER USE HO

T WATER & NEVER ADD WATER

TO THE ACID CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS W

TO THE ACID. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTY SINCE THEY RETAIN PRODUCT RESIDUES. OBSERVE ALL WARNINGS & PRECAUTIONS.

===== Exposure Controls/Personal Protection ========

Respiratory Protection:NIOSH APPROVED:WEAR A SUPPLIED AIR,
FULL-FACEPIECE RESPIRATOR, AIRLINED HOOD, OR FULL-FACEPIECE
SELF-CONTAINED BREATHING APPARATUS. NITRIC ACID IS AN OXIDIZER AND
SHOULD NOT COME IN CONTACT WITH CARTR IDGES AND CANI
STERS THAT

CONTAIN OXIDIZABLE MATERIALS, SUCH AS ACTIVATED CHARCOAL. CANISTER-TYPE RESPIRATORS USING SORBENTS ARE INEFFECTIVE.

Ventilation:LOCAL/GENERAL EXHAUST IS RECOMMENDED TO KEEP EMPLOYEE EXPOSURE BELOW THE AIRBORNE EXPOSURE LIMITS. LOCAL EXHAUST VENTILATION IS PREFERRED GENERALLY PREFERRED.

Protective Gloves:WEAR IMPERVIOUS GLOVES.

Eye Protection: CHEMICAL SAFETY GOGGLES AND/OR FULL FACE SHIELD WHERE SPLASHING IS POSSIBLE.

Other Protective Equipment:WEAR IMPERVIOUS PRO

TECTIVE CLOTHING,

INCLUDING BOOTS, LAB COAT, APRON OR COVERALLS, AS APPROPRIATE TO PREVENT SKIN CONTACT. MAINTAIN EYE WASH FOUNTAIN AND QUICK-DRENCH FACILITIES IN WORK AREA.

Supplemental Safety and Health

======== Physical/Chemical Properties ==========

HCC:C1

Boiling Pt:=122.C, 251.6F Melt/Freeze Pt:=-42.C, -43.6F

Vapor Pres:48 @20C Spec Gravity:1.41 pH:1.0 (0.1M SOLUT

Solubility in Water:INFINATELY SOLUBLE.

Appearance and Odor: COLORLESS TO YELLOWISH LIQUID. SU


FFOCATING ODOR.

======== Stability and Reactivity Data =========

Stability Indicator/Materials to Avoid:YES

A DANGEROUSLY POWERFUL OXIDIZING AGENT, FUMING NITRIC ACID IS INCOMPATIBLE WITH MOST SUBSTANCES, ESPECIALLY STRONG BASES, METALLIC POWDERS, CARBIDES, HYDROGEN SULFIDE, TURPENTINE, AND COMBUSTIBLE ORGANICS.

Stability Condition to Avoid:LIGHT AND HEAT. STABLE UNDER ORDINARY CONDITIONS OF USE AND STORAGE. CONTAINERS MAY BURST WHEN HEATED. Hazardous Decompo



ion is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.