

QUICK START PRODUCTS LTD -- QUICK START STARTING FLUID CYLINDER

MSDS Safety Information

FSC: 2910

NIIN: 01-407-9257

MSDS Date: 06/26/1996

MSDS Num: CKGMR

Product ID: QUICK START STARTING FLUID CYLINDER

MFN: 01

Responsible Party

Cage: 78280

Name: QUICK START PRODUCTS LTD

Address: HIGHWAY 251 SOUTH

City: ROC

HELLE IL 61068

Info Phone Number: 815-562-5414

Emergency Phone Number: 815-562-5414

Proprietary Ind: Y

Review Ind: Y

Published: Y

Contractor Summary

Cage: 78280

Name: QUICK START PRODUCTS LTD

Address: HIGHWAY 251 SOUTH

City: ROCHELLE IL 61068

Phone: 815-562-5414

Item Description Information

Item Manager: S9C

Item Name: PARTS KIT,ETHER,STARTING AID

Unit of Issue: EA

UI Container Qty: 0

Ingredients

Name: *** PROPRIETARY ***

Health Hazards Data

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: NO

Carcinoge

nicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: INHALATION: STRONG ANESTHESIA, INTOXICATION, UNCONSCIOUSNESS. SKIN: IRRITATION UPON PROLONGED CONTACT, DEFATTING OF SKIN. EYES: IRRITATION.

Explanation Of Carcinogenicity: NONE OF THE COMPONENTS IN THIS MATERIAL IS LISTED BY IARC, NTP, OSHA, OR ACGIH AS A CARCINOGEN.

Signs And Symptoms Of Overexposure: INHALATION: DIZZINESS.

First Aid: INHALED: REMOVE TO FRESH AIR. ARTIFICIAL RESPIRATION, CONSULT PHYSICIAN. SKIN: WASH WITH S

OAP AND WATER. REMOVE SOAKED CLOTHING TO AVOID PROLONGED SKIN CONTACT. EYE: FLUSH WELL WITH RUNNING WATER FOR 15 MINUTES. INGESTED: CALL PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. PROPER TREATMENTS DEPENDENT ON CONDITION OF PATIENT AND AMOUNT INGESTED.

=====
Handling and Disposal
=====

Spill Release Procedures: KEEP AWAY FROM HEAT, FIRE, SPARKS, FLAME. VENTILATE AREA WELL. CO2 MAY BE USED AS PRECAUTIONARY VAPOR BLANKET. SMALL AMOUNTS MAY BE FLUSHED AWAY WITH WATER.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS. DON'T PUNCTURE OR INCINERATE. AVOID ANY CONTAMINATION OF GROUNDWATER.

Handling And Storage Precautions: DO NOT STORE WHERE TEMPERATURES MAY EXCEED 120°F. STORE AWAY FROM FIRE, SPARK OR FLAME. STORE IN SUITABLE AREA FOR HAZARDOUS MATERIALS STORAGE.

Other Precautions: DO NOT USE NEAR HEAT, FLAME OR SPARKS. AVOID EXCESSIVE BREATHING OF VAPOR. DO NOT SPRAY IN DIRECTION OF BODY. USE ONLY IN ACCORDANCE WITH DIRECTIONS.

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: TCC

Flash Point: =-48.7°C, -56°F

Lower Limits: 1.8

Upper Limits: 46.0

Extinguishing Media: DRY CHEMICAL, CARBON DIOXIDE, WATER-FOG OR MIST ONLY, ALCOHOL FOAM.

Fire Fighting Procedures: AVOID POSSIBLE ACCUMULATION OF

F VAPOR AT FLOOR LEVEL,
AS VAPOR IS HEAVIER THAN AIR. SELF-CONTAINED BREATHING APPARATUS AND
PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS.
Unusual Fire/Explosion Hazard: AVOID POSSIBLE BURSTING OF PRESSURIZED CAN. DO
NOT STORE WHERE TEMPERATURE MAY EXCEED 120F. DO NOT PUNCTURE OR INCINERATE.

Control Measures

Respiratory Protection: IF TLV IS EXCEED
D WEAR NIOSH-APPROVED SELF-CONTAINED
BREATHING DEVICE OR RESPIRATOR.

Ventilation: MUST BE ADEQUATE TO MAINTAIN VAPORS AT LESS THAN 400PPM
PARTICULARLY AT FLOOR LEVEL AS VAPORS ARE HEAVIER THAN AIR.

Protective Gloves: NORMAL USE-NONE. PROLONGED EXPOSURE-NITRILE, IMPERVIOUS.

Eye Protection: SAFETY GLASSES OR GOGGLES RECOMMENDED.

Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER.

Physical/Chemical Properties

HCC: G2

Boiling Point: =34.4C, 94.F

B.P. Text: FOR DIETHYL ETHER

Vapor Pres: 150 PSIG IN CAN

Vapor Density: APPROX 2.5

Spec Gravity: 0.70

Evaporation Rate & Reference: APPROX 6, BUACE=1

Solubility in Water: APPROX 6% @70F,MODERT

Appearance and Odor: PALE YELLOW TO CLEAR LIQUID, STRONG ETHEREAL ODOR

Percent Volatiles by Volume: 86.0

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: HEAT SPARKS, FLAMES, STRONG OXIDIZERS.

Materials To Avoid: UNSTABLE EXPLOSIVE PEROXIDES MAY BE FORMED AND CONCENTRATE
BY EVAPORATION TO HAZARDOUS LEVELS. THIS PROCESS IS FAVORED BY PROLONGED
STORAGE WITH EXPOSURE TO AIR AND LIGHT.

Hazardous Decomposition Products: CARBON MONOXIDE MAY FORM ON COMBUSTION.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: WILL NOT OCCUR.

=====

Toxicological Information

=====

=====

Ecological Information

=====

=====

MSDS Transport Information

=====

Transport Information: DOT SHIPPING CLASSIFICATION: COMPRESSED GAS, FLAMMABLE
(ETHER, CARBON DIOXIDE); HAZARD CLASS 2.1; UN195
4; LABEL REQUIRED- FLAMMABLE
GAS.

=====

Regulatory Information

=====

=====

Other Information

=====

=====

Transportation Information

=====

Responsible Party Cage: 78280

Trans ID NO: 152294

Product

ID: QUICK START STARTING FLUID CYLINDER

MSDS Prepared Date: 06/26/1996

Review Date: 04/07/2000

MFN: 1

Multiple KIT Number: 0

Review IND: Y

Unit Of Issue: EA

Container QTY: 0

=====

Detail DOT Information

=====

DOT PSN Code: DQH

Symbols: G

DOT Proper Shipping Name: COMPRESSED GASES, FLAMMABLE, N.O.S.

Hazard Class: 2.1

UN ID Num: UN1954

Label: FLAMMABLE GAS

Special Provision: B13

Non Bulk Pack: 302

,305
Bulk Pack: 314,315
Max Qty Pass: FORBIDDEN
Max Qty Cargo: 150 KG
Vessel Stow Req: D
Water/Ship/Other Req: 40

=====

Detail IMO Information

=====

IMO PSN Code: EQB
IMO Proper Shipping Name: COMPRESSED GAS, FLAMMABLE, N.O.S. o
IMDG Page Number: 2124
UN Number: 1954
UN Hazard Class: 2(2.1)
IMO Packaging Group: -
Subsidiary Risk Label: -
EMS Number: 2-02
MED First Aid Guide NUM: 620

=====

Detail IATA Information

=====

IATA PSN Code: HDE
IATA UN ID Num: 1954
IATA Proper Shipping Name: COMPRESSED GAS, FLAMMABLE, N.O.S. *
IATA UN Class: 2.1
IATA Label: FLAMMABLE GAS
Packing Note Passenger: FORB
Max Quant Pass: FORB
Max Quant Cargo: 150KG
Packaging Note Cargo: 200
Exceptions: A1

=====

Detail AFI Information

=====

AFI PSN Code: HDE
AFI Symbols: *
AFI Proper Shipping Name: COMPRESSED GAS, FLAMMABLE, N.O.S.
AFI Hazard Class: 2.1
AFI UN ID NUM: UN1954
Special Provisions: P4
Back Pack Reference: A6.3, A6.5

=====

HAZCOM Label

=====

Product ID: QUICK START STARTING FLUID CYLINDER
Cage: 78280
Company Name: QUICK START PRODUCTS LTD
Street: HIGHWAY 251 SOUTH
City: ROCHELLE IL
Zipcode: 61068
He

alth Emergency Phone: 815-562-5414

Label Required IND: Y

Date Of Label Review: 04/07/2000

Status Code: A

Origination Code: F

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: DANGER

Respiratory Protection IND: YES

Health Hazard: Moderate

Contact Hazard: Slight

Fire Hazard: Severe

Reactivity Hazard: None

Hazard And Precautions: INHALATION: STRONG ANESTHESIA, INTOXICATION,
UNCONSCIOUSNESS. SKIN: IRRIATION UPON PROLONGED CONTACT, DEFATTING OF SKIN.
EYES: IRRITATION.

=====

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.