

GC THORSEN ELECTRONICS -- EPOXY RESIN COMPONENT, 10-347-1R -- 8040-00-281-2308

=====
Product Identification
=====

Product ID:EPOXY RESIN COMPONENT, 10-347-1R

MSDS Date:06/22/1994

FSC:8040

NIIN:00-281-2308

Status Code:A

MSDS Number: CKHXV

=== Responsible Party ===

Company Name:GC THORSEN ELECTRONICS

Address:1801 MORGAN STREET

City:ROCKFORD

State:IL

ZIP:61105-1209

Country:US

Info Phone Num:815-968-

9661

Emergency Phone Num:(800)424-9300

Chemtrec Ind/Phone:(800)424-9300

CAGE:72653

=== Contractor Identification ===

Company Name:GC THORSEN

Address:1801 MORGAN STREET

Box:City:ROCKFORD

State:IL

ZIP:61105

Country:US

Phone:815-968-9661

CAGE:72653

=====
Composition/Information on Ingredients
=====

Ingred Name:1-CHLORO-2,3-EPOXYPROPANE-4,4'-ISOPROPYLIDENEDIPHENOL
POLYMER

CAS:25068-38-6

RTECS #:CE6880000

Fraction by Wt: 70%

Ingred Name:INSERT FILLER (S102)

CAS:7631-86-9

Fra

ction by Wt: 30%

=====
Hazards Identification
=====

Effects of Overexposure:SKIN IRRITATION, SENSITIZATION, DERMATITIS
Medical Cond Aggravated by Exposure:MAY AGGRAVATE DERMATITIS, ALLERGY
OR ECZEMA CONDITIONS.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES - CONSULT
PHYSICIAN SKIN: WASH WITH SOAP AND WATER INHALATION: FRESH AIR,
OXYGEN INGESTION: DRINK LARGE QUAN
TITIES OF WATER - CONSULT
PRYSICIAN

=====
Fire Fighting Measures
=====

Flash Point Method:OC
Flash Point:=254.4C, 490.F
OC490F
Extinguishing Media:CO2 H2O X H2O X CHEM FOAM X DRY CHEM
Fire Fighting Procedures:USE SCBA
Unusual Fire/Explosion Hazard:DECOMOSITION AND COMBUSTION PRODUCTS MAY
BE TOXIC HMIS/NFPA RATINGS HEALTH 1 FLAMIBILITY 1 REACTIVITY 1

=====
Accidental Release Measures
=====

Spill Release Procedures:AVOI
D ALL PERSONAL CONTACT. PICK UP WITH
ABSORBENT MATERIAL. STORE IN CLOSED CONTAINERS. FLUSH AREA WITH
WATER. WASTE

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL, DRY AREA - AWAY FROM
HARDENER OTHER: KEEP CONTAINERS TIGHTLY CLOSED.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:CHEMICAL CARTRIDGE RESPIRATOR - IF NEED
Ventilation:LOCAL EXHAUST X MECHANICAL AS AEQUI

RED TO MEET TLV'S

CLOTHING/

Protective Gloves:WHEN NECESSARY

Eye Protection:CHEMICAL GOGGLES

Supplemental Safety and Health

GLOVES: AS NECESSARY TO AVOID SKIN CONTACT. (BARRIER CREAM IS HELPFUL).

===== Physical/Chemical Properties =====

Boiling Pt:>200.C, 392.F

B.P. Text:200+C

Vapor Density:NE

Evaporation Rate & Reference: