

DOW CORNING CORP. -- FLUOROSILICONE CF2-3521-2, PT B -- 8030-01-043-2295

===== Product Identification =====

Product ID:FLUOROSILICONE CF2-3521-2, PT B

MSDS Date:08/25/1993

FSC:8030

NIIN:01-043-2295

Status Code:A

Kit Part:Y

MSDS Number: CKNMG

=== Responsible Party ===

Company Name:DOW CORNING CORP.

Address:SOUTH SAGINAW ROAD

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-6000

Eme

rgency Phone Num:517-496-5900

Preparer's Name:DOW CORNING CORP.

Chemtrec Ind/Phone:(800)424-9300

CAGE:50028

=== Contractor Identification ===

Company Name:BAFCO INC

Address:717 MEARNES RD

Box:City:WARMINSTER

State:PA

ZIP:18974-2807

Country:US

Phone:215-674-1700

CAGE:50028

===== Composition/Information on Ingredients =====

Ingred Name:STYENE-DIVINYLBENZENE-ETHYLSTYRENE POLYMER.

CAS:9052-95-3

= Wt:15.

Ingred Name:TRIMETHYLATED SILICA

CAS:68909-20-6

= Wt:7.

OSHA PEL:5 MG/M3

Ing

red Name:STYRENE
CAS:100-42-5
RTECS #:WL3675000
= Wt:.7
OSHA PEL:100 PPM
ACGIH TLV:50PPM
ACGIH STEL:100 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Health Hazards Acute and Chronic:ACUTE EFFECTS: EYE: DIRECT EYE CONTACT
MAY CAUSE TEMPORARY DISCOMFORT WITH MILD REDNESS AND DRYNESS
SIMILAR TO WINDBURN. SKIN: A SINGLE PROLONGED EXPOSURE(24 TO 48
HOURS) CAUSES NO KNOWN ADVERSE EFFE CT. INHALATION: DUST MAY
IRR
ITATE NOSE AND THROAT. ORAL: SMALL AMOUNTS TRANSFERRES TO THE
MOUTH BY FINGERS DURING USE, ETC., SHOULD NOT INJURE. SWALLOWING
LARGE AMOUNTS MAY CAUSE DIGESTIVE DISCOMFO RT.
Medical Cond Aggravated by Exposure:

===== First Aid Measures =====

First Aid:EYE IMMEDIATELY FLUSH WITH WATER. SKIN: NO FIRST AID SHOULD
BE NEEDED. INHALTION: NO FIRST AID SHOULD BE NEEDED. ORAL: NO
FIRST AID SHOULD BE NEEDED.

===== Fire Fighting
Measures =====

Flash Point:=100.C, 212.F
212F
Extinguishing Media:CARBON DIOXIDE(CO2). WATER. WATER FOG (OR SPRAY).
DRY CHEMICAL, FOAM.
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AND
PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING
CHEMICALS. EVACUTAE AREA IN CASE OF OVERHEATING OR FIRE.
HAZARDOUS DECOMPOSITON PRODUCTS: SILI CON DIOXIDE, CARBON OXIDES
AND TRACES OF INCOMPLETELY BURNED COMPOUNDS. FLUORINE COMPOUNDS.
FO

RMALDEHYDE.

Unusual Fire/Explosion Hazard:INHALATION OF FUMES FROM FIRE

DECOMPOSITION OF POLYTETRAFLUOROETHYLENE (TEFLON?) IS KNOWN TO CAUSE POLYMER FEVER. THIS MATERIAL MAY FORM HIGHLY TOXIC VAPORS OF TRIFLUOROPROPIONALDEHYDE IF HEATED IN AIR ABOVE 300F (149C). PROVIDE VENTILATION TO CONTROL VAPOR EXPOSURE (INHALATION GUIDELINES HAVE NOT BEEN ESTABLISHED).

===== Accidental Release Measures =====

Spill Release Procedures:CONTAINMENT/CLEAN-UP:

DISPOSAL OF COLLECTED

PRODUCT, RESIDUES, AND CLEANUP MATERIALS MAY BE GOVERNMENTALLY REGULATED. OBSERVE ALL APPLICABLE LOCAL, STATE, AND FEDERAL WASTE MANAGEMENT REGULATIONS. SCRAPE UP AND CONTAIN FOR SALVAGE OR DISPOSAL. OBSERVE ALL PERSONAL PROTECTION EQUIPMENT RECOMMENDATIONS DESCRIBED IN SECTIONS 5 AND 8.

===== Handling and Storage =====

Handling and Storage Precautions:PERSONAL PROTECTIVE EQUIPMENT FOR

SPILLS: EYE: USE PROPER PRO

TECTION--SAFETY GLASSES AS A MINIMUM.

SKIN: WASHING AT MEALTIME AND END OF SHIFT IS ADEQUATE.

Other Precautions:PRECAUTIONARY MEASURES: AVOID EYE CONTACT. AVOID BREATHING DUST. KEEP CONTAINER CLOSED. USE REASONABLE CARE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE RESPIRATORY PROTECTION UNLESS ADEQUATE LOCAL EXHAUST VENTILATION IS PROVIDED OR AIR SAMPLING DATA SHOW EXPOSURES ARE WITHIN RECOMMENDED EXPOSURE GUIDELINES. INDU

STRIAL HYGIENE

PERSONNEL CAN ASSIST IN JUDGING THE ADEQUACY OF EXISTING ENGINEERING CONTROLS.

Ventilation:LOCAL EXHAUST: RECOMMENDED. GENERAL VENTILATION: RECOMMENDED.

Protective Gloves:WASHING AT MEALTIME AND END OF SHIFT IS ADEQUATE.

Eye Protection:USE PROPER PROTECTION--SAFETY GLASSES AS A MINIMUM.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Spec Gravity:1.36

Solubility in Water:NONE

Appearance and Odor:WHITE, SLIGHT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: OXIDIZING MATERIALS CAN CAUSE A REACTION

===== Disposal Considerations =====

Waste Disposal Methods: LOCAL, STATE, AND FEDERAL REPORTING REQUIREMENTS
MAY APPLY TO SPILLS OR RELEASE OF THIS MATERIAL INTO THE
ENVIRONMENT.

===== Other Information =====

Disclaimer (provided with

this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.