

MET-L-CHEK COMPANY -- PENETRANT & LUBE -- 6850-00-826-0981

=====  
Product Identification  
=====

Product ID: PENETRANT & LUBE

MSDS Date: 01/01/1997

FSC: 6850

NIIN: 00-826-0981

Status Code: A

MSDS Number: CKPBZ

=== Responsible Party ===

Company Name: MET-L-CHEK COMPANY

Address: 1639 EUCLID ST

City: SANTA MONICA

State: CA

ZIP: 90404-3770

Country: US

Info Phone Num: 310-450-1111

Emergency Phone Num: (800)424-9300

Ch

emtrek Ind/Phone: (800)424-9300

CAGE: 98733

=== Contractor Identification ===

Company Name: MET-L-CHEK COMPANY

Address: 1639 EUCLID ST

Box: 00000

City: SANTA MONICA

State: CA

ZIP: 90404

Country: US

Phone: 310-450-1111/FAX 310452-4046

CAGE: 98733

=====  
Composition/Information on Ingredients  
=====

Ingred Name: PETROLEUM HYDROCARBON

CAS: 64742-46-7

RTECS #: JN9379645

Minimum % Wt: 1.

Maximum % Wt: 100.

OSHA PEL: 5 MG/M3

ACGIH TLV: 5 MG/M3

=====  
Hazards Identification  
=====

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:EYE CONTACT-PRESUMED NON-IRRITATING.  
SKIN CONTACT-SLIGHTY IRRITATING. INHAHALATION-VAPORS OR OIL MIST  
MAY CAUSE MILD IRRITATION OF UPPER RESPIRATORY TRACT.  
INGESTION-MAY RESULT IN VOMITING. ASPIRATIO N MUST BE AVOIDED.  
Medical Cond Aggravated by Exposure:

===== First Aid Measures =====

First Aid:EYE CONTACT-FLUSH WITH WATER. SKIN CONTACT-FLU  
SH WATER, WASH  
SOAP AND WATER. INHALATION-REMOVE TO FRESH AIR, PROVIDE OXYGEN IF  
BREATHING IS DIFFICULT. INGESTION-DO NOT INDUCE VOMITING. GET  
MEDICAL A TTENTION.

===== Fire Fighting Measures =====

Flash Point Method:PMCC  
Flash Point:=93.3C, 200.F  
200F  
Extinguishing Media:USE WATER FOG, FOAM, DRY CHEMICAL OR CO2. DO NOT  
USE DIRECTSTREAM WATER.  
Fire Fighting Procedures:MATERIAL WILL NOT BURN UNLESS PREHEATED. DO  
NOT ENTER CONFINED FIRE-SP  
ACE WITHOUT FULL BUNKER GEAR, INCLUDING A  
POSITVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH AN ABSORBENT SUCH AS CLAY, SAND,  
OR OTHER SUITABLE MATERIAL. DISPOSE OF IN ACCORDANCE WITH FEDERAL  
AND STATE REGULATIONS FOR OIL RESIDUE.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, OPEN FL  
AMES AND  
OXIDIZING MATERIALS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURE EXCEEDS TLV, USE NIOSH APPROVED  
RESPIRATOR TO TO PREVENT OVEREXPOSURE.  
Ventilation:LOCAL EXHAUST: TO MAINTAIN TLV. MECHANICAL: TO MAINTAIN  
TLV.  
Protective Gloves:CHEMICAL RESISTANT TO MINIMIZE SKIN CONTACT.  
Eye Protection:NO SPECIAL PROTECTION REQUIRED.  
Other Protective Equipment:AS REQUIRED TO MINIMIZE SKIN CONTACT.  
Work Hygienic Practices:MINIMIZ

E SKIN CONTACT. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING TOILET.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:>204.4C, 400.F

B.P. Text:400F

Melt/Freeze Pt:=23.9C, 75.F

M.P/F.P Text:75F

Spec Gravity:ABOUT 0.88

Solubility in Water:INSOLUBLE

Appearance and Odor:DEEP RED LIQUID, HYDROCARBON ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:

YES

OXIDIZING MATERIALS.

Stability Condition to Avoid:HEAT, OPEN FLAMES, AND OXIDIZING MATERIALS.

Hazardous Decomposition Products:CAN PRODUCE CARBON MONOXIDE AND OTHER UNIDENTIFIED ORGANIC COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods:PLACE IN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.