

CLIFTON ADHESIVE INC -- CATALYST UV (SEE SUPPLEMENTAL DATA)

=====

MSDS Safety Information

=====

FSC: 2040

NIIN: 01-411-4558

MSDS Date: 12/29/1992

MSDS Num: CKVGJ

Product ID: CATALYST UV (SEE SUPPLEMENTAL DATA)

MFN: 01

Kit Part: Y

Responsible Party

Cage: 79833

Name: CLIFTON ADHESIVE INC

Address: BURGESS PL

City: WA

YNE NJ 07470

Info Phone Number: 201-694-0845; 973-694-0845

Emergency Phone Number: (800)424-9300

=====

Item Description Information

=====

Item Manager: S9C

Item Name: INFLATABLE TUBE ASSEMBLY

Specification Number: NONE

Type/Grade/Class: NONE

Unit of Issue: EA

Type of Container: UNKNOWN

=====

Ingredients

=====

=====

Name: *** PROPRIETARY ***

=====

Health Hazards Data

=====

LD50 LC50 Mixture: NOT PROVIDED

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: ACUTE: ACUTE NAUSEA AND/OR NARCOSIS. CHRONIC: NO
INFORMATION PRESENTLY AVAILABLE.

Explanation Of Carcinogenicity: NONE

Signs And S

ymptoms Of Overexposure: IRRITATION TO EYES AND MUCOUS MEMBRANES.
DRYNESS AND CRACKING OF SKIN. LIQUID INGESTION MAY CAUSE VOMITING. CENTRAL
NERVOUS SYSTEM DEPRESSION--DIZZINESS, NUMBNESS, TINGLING OF EXTRMITIES.
Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS. PRE-EXISTING EYE AND
SKIN DISORDERS.
First Aid: UTILIZE THE SUGGESTED METHODS LISTED BELOW. IN EMERGENCY SITUATIONS
NOTIFY A PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. REFER TO PHYSICIAN IF
IRRITATION PERSISTS. EYES:
FLUSH EYES ABUNDANTLY WITH CLEA N WATER AND REFER
TO A PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING. REFER TO A PHYSICIAN.
EXCESSIVE INHALATION: REMOVE PATIENT TO FRESH AIR OR GIVE OXYGEN. USE CPR IF
PATIENT IS NOT BREATHING. REFER TO PHYSICIAN.

=====
Handling and Disposal
=====

Spill Release Procedures: ABSORB SPILL IN SAND, EARTH, VERMICULITE, OIL-DRI, OR
SOL-SPEED-DRI. SHOVEL ABSORBED
MATERIAL INTO STEEL CONTAINER AND COVER.
Neutralizing Agent: NOT RELEVANT
Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL
CHEMICAL SOLVENT WASTE DISPOSAL REGULATIONS.
Handling And Storage Precautions: KEEP CONTAINERS TIGHTLY CLOSED AND STORE IN
APPROVED SOLVENT STORAGE AREA. KEEP AWAY FROM OPEN FLAME, HEAT, SPARKS, HOT
SURFACES AND OXIDIZING AGENTS.
Other Precautions: N/A.

=====
Fire and Explosion Hazard Informa
tion
=====

Flash Point Method: TCC
Flash Point: =41.1C, 106.F
Flash Point Text: AROMATIC SOLVENT
Autoignition Temp: =465.C, 869.F
Lower Limits: 0.6
Upper Limits: 7.6
Extinguishing Media: CO2, FOAM, DRY CHEMICAL.
Fire Fighting Procedures: NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING
APPARATUS SHOULD BE WORN. USE WATER SPRAY TO COOL FIRE-EXPOSED STRUCTURES
AND
DISPERSE VAPOR-CLOUD IF FIRE IS NOT PRESENT.
Unusual Fire/Explosion Hazard: VAPOR IS

HEAVIER THAN AIR AND MAY TRAVEL
CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASHBACK.

=====

Control Measures

=====

Respiratory Protection: USE NIOSH-APPROVED ATMOSPHERE SUPPLYING OR AIR
PURIFYING RESPIRATOR FOR ORGANIC VAPORS AS REQUIRED TO MAINTAIN EXPOSURE
LEVELS BELOW RECOMMENDED LIMITS.

Ventilation: LOCAL EXHAUST: REMOVE VAPORS DURING PROCESSING. MECHANICAL:
EXPLOSION-PROOF EQ

UIPMENT. SPECIAL: REDUCE VAPOR CONCENTRATIONS BELOW
SPECIFIED LIMITS.

Protective Gloves: PVA GLOVES.

Eye Protection: SAFETY GLOVES.

Other Protective Equipment: PROTECTIVE CLOTHING AS REQUIRED TO PREVENT SKIN
CONTACT.

Work Hygienic Practices: KEEP AREA CLEAN. CLEAN UP SPILLS IMMEDIATELY. PRACTICE
GOOD PERSONAL HYGIENE.

Supplemental Safety and Health: ITEM IS A KIT AND IS ASSOCIATED WITH PART
NUMBER: WMP730R-1: SUPPLIED BY CAGE:1GTCO. KIT CONSIST OF: UR-4980
(ADHESIVE), CATALYST UV AND T
ETRAHYDROFURAN (UNDER CAGE: 1GTC0).

=====

Physical/Chemical Properties

=====

HCC: F2

NRC/State LIC No: NOT RELEVANT

Boiling Point: =125.C, 257.F

M.P/F.P Text: NOT PROVIDED

Decomp Text: NOT PROVIDED

Vapor Pres: 5.2

Vapor Density: 4.1

Spec Gravity: 1.06

VOC Pounds/Gallon: 2.65

VOC Grams/Liter: 316

Viscosity: NOT PROVIDED

Evaporation Rate & Reference: NOT PROVIDED

Solubility in Water: NOT PROVID

ED
Appearance and Odor: CLEAR LIQUID. CHARACTERISTIC SOLVENT ODOR.

Percent Volatiles by Volume: NOT PROVIDED

Corrosion Rate: NOT PROVIDED

=====

Reactivity Data

=====

Stability Indicator: YES

Stability Condition To Avoid: AVOID HEAT, OPEN FLAMES, SPARKS, HOT SURFACES

Materials To Avoid: OXIDIZING AGENTS.

Hazardous Decomposition Products: OXIDES OF CARBON. NITROGEN.

Hazardous Polymerization Indicat

or: NO
Conditions To Avoid Polymerization: NONE

=====

Toxicological Information

=====

Toxicological Information: NOT PROVIDED

=====

Ecological Information

=====

Ecological: NOT PROVIDED

=====

MSDS Transport Information

=====

Transport Information: DOT NAME & NO.: FLAMMABLE LIQUID, N.O.S. (CONTAINS N-BUTYL ACETATE, AROMATIC PETROLEUM DISTILLATE), UN1993.

=====

Regulatory Information

=====

Sara Title III Information: NOT PROVIDED
Federal Regulatory Information: NOT PROVIDED
State Regulatory Information: NOT PROVIDED

=====

Other Information

=====

Other Information: CATALYST UV. MIXED WITH UR4980. FOUND IN WING INFLATABLES REPAIR KIT, P/N WMP 730R-8. ISSUED WITH EVERY WING MAIN TUBE ASSEMBLY, P/N WMP 730R-1. CAGE CODE: 1GTC0, SOL#: SP0760-00-R-6397.

=====

Transportation Information

=====

Responsible Party Cage: 79833
Trans ID NO: 155055
Product ID: CATALYST UV (SEE SUPPLEMENTAL DATA)
MSDS Prepared Date: 12/29/1992
Review Date: 10/20/2000
MFN: 1
Tech Entry NOS Shipping Nm: CONTAINS N-BUTYL ACETATE, AROMATIC PETROLEUM DISTILLATE.
Multiple KIT Number: 0
Kit Part IND: Y
Unit Of Issue: EA
Type Of Container: UNKNOWN
Additional Data: PROPER SHIPPING NAME, UN ID NUMBER, PER MSDS. MAXIMUM ALLOWED BY PASSENGER/CARGO AIR: 60L/220 L.

=====

Detail DOT Information

=====

DOT PS

N Code: GJL
Symbols: G
DOT Proper Shipping Name: FLAMMABLE LIQUIDS, N.O.S.
Hazard Class: 3
UN ID Num: UN1993
DOT Packaging Group: III
Label: FLAMMABLE LIQUID
Special Provision: B1,B52,T7,T30
Packaging Exception: 150
Non Bulk Pack: 203
Bulk Pack: 242
Max Qty Pass: 60 L
Max Qty Cargo: 220 L
Vessel Stow Req: A

=====

Detail IMO Information

=====

IMO PSN Code: HIA
IMO Proper Shipping Name: FLAMMABLE LIQUID, N.O.S.
IMDG Page Number: 3345
UN Number: 1993
UN Hazard Class: 3.3
IMO Packaging Group: III
Subsidiary Risk Label: -
EMS Number: 3-07
MED First Aid Guide NUM: T

=====

Detail IATA Information

=====

IATA PSN CA
IATA UN ID Num: 1993
IATA Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. *
IATA UN Class: 3
IATA Label: FLAMMABLE LIQUID
UN Packing Group: III
Packing Note Passenger: 309
Max Quant
Pass: 60L
Max Quant Cargo: 220L
Packaging Note Cargo: 310

=====

Detail AFI Information

=====

AFI PSN CA
AFI Symbols: *
AFI Proper Shipping Name: FLAMMABLE LIQUIDS, N.O.S.
AFI Hazard Class: 3
AFI UN ID NUM: UN1993
AFI Packing Group: III
Special Provisions: P5
Back Pack Reference: A7.3

=====

HAZCOM Label

=====

=====

Product ID: CATALYST UV (SEE SUPPLEMENTAL DATA)

Cage: 79833

Company Name: CLIFTON ADHESIVE INC

Street: BURGESS PL

City: WAYNE NJ

Zipcode: 07470

Health Emergency Phone: (800)424-9300

Label Required IND: Y

Date Of Label Review: 10/20/2000

Status Code: A

MFG Label NO: NOT PROVIDED

Year Procured: 2000

Origination Code: F

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: WARNING

Respiratory Protection IND: NO

Health Hazard: Moderate

Contact Hazard: Slight

Fire Hazard: Moderate

Reactivity Hazard: None

Hazard And Precautions: TARGET ORGANS: N-BUTYL ACETATE MAY CAUSE LIVER, KIDNEY, LUNG OR BRAIN DAMAGE, BASED ON ANIMAL DATA. FIRST AID: UTILIZE THE SUGGESTED METHODS LISTED BELOW. IN EMERGENCY SITUATIONS NOTIFY A PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. REFER TO PHYSICIAN IF IRRITATION PERSISTS. EYES: FLUSH EYES ABUNDANTLY WITH CLEAN WATER AND REFER TO A PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING. REFER TO A PHYSICIAN. EXCESSIVE INHALATION: REMOVE PATIENT

TO FRESH AIR OR GIVE OXYGEN. USE CPR IF PATIENT IS NOT BREATHING. REFER TO PHYSICIAN. SPILL: ABSORB IN SAND, EARTH, VERMICULITE, OIL-DRI, OR SOL-SPEED-DRI. SHOVEL ABSORBED MATERIAL INTO STEEL CONTAINER AND COVER

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied

warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility f

or the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.