View NSN Online: https://aerobasegroup.de/nsn/6850-01-435-5658

## 

Product ID:"VERTREL" MCA MSDS Date:09/26/2000 FSC:6850 NIIN:01-435-5658 MSDS Number: CKVJS === Responsible Party === Company Name: DU PONT FLUOROPRODUCTS Address:1007 MARKET STREET City:WILMINGTON State:DE ZIP:19898 Country:US Info Phone Num:1-800-441-7515 Emergency Phone Num:1-800-441-3637/MEDICAL EMERGE NCY Resp. Party Other MSDS Num.:6092FR Chemtrec Ind/Phone:(800)424-9300 CAGE:2S827 === Contractor Identification === Company Name: DU PONT FLUOROPRODUCTS Address:1007 MARKET STREET Box:City:WILMINGTON State:DE ZIP:19898 Country:US Phone:1-800-441-7515 Contract Num:SP0450-01-M-D210 CAGE:2S827 Company Name:SDB CONSULTANTS LTD Address:401 WHITNEY AVE SUITE 120 Box:City:GRETNA State:LA ZIP:70056 Country:US Phone:504-366-9105 Contract Num:SP0450-01-M-ZE54 CAGE:0PGK2

======= Composition/Informa

Ingred Name:1,1,1,2,2,3,4,5,5,5-DECAFLUOROPENTANE (HFC-43-10MEE) CAS:138495-42-8 Minumum % Wt:59. Maxumum % Wt:65. Other REC Limits:200 PPM (DUPONT)

Ingred Name: TRANS-1,2-DICHLOROETHYLENE (T-DCE) CAS:156-60-5 RTECS #:KV9400000 Minumum % Wt:35. Maxumum % Wt:41. Other REC Limits:200 PPM (DUPONT) **OSHA PEL:200 PPM TWA 8-HR** ACGIH TLV:200 PPM TWA 8-HR EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

LD

50 LC50 Mixture: NONE GIVEN FOR PRODUCT AS A WHOLE Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:HFC-43-10MEE MAY CAUSE SUFFOCATION, CENTRAL NERVOUS SYSTEM (CNS) STIMULATION FOLLOWED BY CNS DEPRESSION. OVEREXPOSURE MAY CAUSE IRREGULAR HEARTBEAT. INTENTIONAL MISUSE MAY CAUSE DEATH WITHOUT WARNING. SKIN CONTACT MAY CAUSE SLIGHT IRRITATION. EYE CONTACT MAY CAUSE IRRITATION. ASPIRATION OF LIQUID INTO LUNGS MAY CAUSE CHEMICAL PNEUMONIA. T-D

CE: INHALATION

MAY CAUSE CNS DEPRESSION. OTHER EFFECTS IN CLUDE IRREGULAR HEARTBEAT. SKIN CONTACT MAY CAUSE SEVERE IRRITATION. EYE CONTACT MAY CAUSE SEVERE IRRITATION. INGESTION MAY CAUSE PULMONARY EDEMA (ASPIRATION OF LIQUID INTO LUNG). INGESTION MAY CAUSE PATHOLOGICAL CHANGES IN LIVER & HEART.

Explanation of Carcinogenicity:NONE OF THE COMPONENTS PRESENT IN THIS MATERIAL AT CONCENTRATIONS EQUAL TO OR GREATER THAN 0.1% ARE LISTED BY IARC. NTP. OSHA OR ACGIH AS A CAR

CINOGEN.

Effects of Overexposure: INHALED-SLEEPLESSNESS, TREMORS, CONVULSIONS, DIZZINESS, CONFUSION, INCOORDINATION, DROWSINESS, UNCONSCIOUSNESS, STRANGE SENSATION IN CHEST, "HEART THUMPING", APPREHENSION, LIGHTHEADEDNESS, FEELING OF FAINTING, DIZZINESS, WEAKNESS, LOSS OF CONSCIOUSNESS, DEATH. SKIN: ITCHING, REDNESS, RASH. EYES: TEARING, PAIN, BLURRED VISION, ASPIRATION: COUGHING, GASPING, CHOKING, SHORTNESS OF BREATH, BLUISH DISC OLORATION OF SKIN, RAPID BREATHING AN

D HEART RATE, FEVER, PULMONARY EDEMA OR BLEEDING, DROWSINESS, CONFUSION, COMA SEIZURES.

Medical Cond Aggravated by Exposure:NOT PROVIDED BY MANUFACTURER

First Aid:INHALATION: IF INHALED, IMMEDIATELY REMOVE TO FRESH AIR. KEEP PERSON CALM. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN. SKIN: FLUSH SKIN WIT H WATER AFTER CONTACT. WASH CONTAMINATED CLOTHING BEFORE

REUSE. EYE: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICIAN. INGESTION: MATERIAL POSES AS ASPIRATION HAZA RD. IF SWALLOWED, DO NOT INDUCE VOMITING. IMMEDIATELY GIVE 2 GLASSES OF WATER. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. CALL A PHYSICIAN. IF VOMITING OCCURS NATURALLY, HAVE VICTIM LEAN F ORWARD TO REDUCE THE RISK OF ASPIRATION.

Flash P

oint Method:PMCC

Flash Point:NONE

Lower Limits:NONE

Upper Limits:NONE

Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING MATERIAL. Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS (SCBA) IS REQUIRED IF DRUMS RUPTURE AND CONTENTS ARE SPILLED UNDER FIRE CONDITIONS.

Unusual Fire/Explosion Hazard:USE WATER SPRAY OR FOG TO COOL CONTAINERS. DRUMS MAY RUPTURE UNDER FIRE CONDITIONS. DECOMPOSITION MAY OCCUR.

=====

Spill Release Procedures: INITIAL CONTAINMENT-DIKE SPILL. PREVENT MATERIAL FROM ENTERING SEWERS, WATERWAYS, OR LOW AREAS. IMMEDIATELY EVACUATE THE AREA AND PROVIDE MAXIMUM VENTILATION ESPECIALLY IN LOW PLACES WHERE HEAVY VAPOR S MIGHT COLLECT. UNPROTECTED PERSONNEL SHOULD MOVE UPWIND OF SPILL. ONLY PERSONEL EQUIPPED WITH PROPER RESPIRATORY AND SKIN/EYE PROTECTION SHOULD BE PERMITTED IN AREA. SOAK UP WITH SAWDUST, SAND, OIL Neutralizing Agent:NOT PROVIDED BY MANUFACT Handling and Storage Precautions:STORE IN A CLEAN, DRY AREA. DO NOT ALLOW STORED PRODUCT TO EXCEED 52C (125F) TO PREVENT LEAKAGE OR POTENTIAL RUPTURE OF CONTAINER FROM PRESSURE & EXPANSION. PROTECT FROM FREEZING TEMPERATURES. IF SOLV ENT IS STORED BELOW -10C(14F), MIX PRIOR TO USE.

Other Precautions: AVOID BREATHING VAPORS OR MIST. AVOID CONTACT WITH EYES, SKIN OR CLOTHING. WASH THOROUGHLY AFTER HANDLIN

G. USE OF

GLOVES IS RECOMMENDED WHEN WORKING WITH THE MATERIAL CONTAINERS. MATERIAL SHOULD NOT B E DISPENSED FROM ITS CONTAINER BY POURING, EXCEPT FOR SMALL SAMPLE CONTAINERS WHERE FUME HOODS USED TO CONTROL EXPOSURE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:WHERE THERE IS POTENTIAL FOR AIRBORNE EXPOSURES IN EXCESS OF APPLICABLE LIMITS, WEAR NIOSH APPROVED RESPIRATORY PROTECTION.

Ventilation: USE ONLY WITH ADEQUATE VENTI

LATION.

Protective Gloves:WEAR AS APPROPRIATE IMPERVIOUS GLOVES.

Eye Protection:WEAR SAFETY GLASSES OR COVERALL CHEMICAL SPLASH GOGGLES. Other Protective Equipment:WHERE THERE IS POTENTIAL FOR SKIN CONTACT

HAVE AVAILABLE & WEAR AS APPROPRIATE IMPERVIOUS GLOVES, APRON, PANTS & JACKET. PROTECTIVE GLOVES & CHEMICAL SPLASH GOGGLES SHOULD BE USED WHEN HANDLING LIQUID

Work Hygienic Practices: KEEP CONTAINER TIGHTLY CLOSED. VAPORS ARE HEAVIER THAN AIR POSING A HAZARD OF ASPHYXIA IF THEY

ARE TRAPPED IN

ENCLOSED OR LOW PLACES.

Supplemental Safety and Health

NOTE TO PHYSICIAN:THIS MATERIAL MAY MAKE THE HEART MORE SUSCEPTIBLE TO ARRHYTHMIAS. CATECHOLAMINES, SUCH AS ADRENALINE, AND OTHER COMPOUNDS HAVING SIMILAR EFFECTS, SHOULD BE RESERVED FOR EMERGENCIES A ND THEN USED ONLY WITH SPECIAL CAUTION.

HCC:T6 Boiling Pt:=39.C, 102.2F Vapor Pres:464 MMHG@25C(77F) Vapor Density:5.4 Appearance and Odor:COL Stability Indicator/Materials to Avoid:YES

INCOMPATIBLE WITH ALKALI OR ALKALINE EARTH METALS-POWDERED AL, ZN, BE, NA, MG, ETC. INCOMPATIBLE WITH STRONG BASES SUCH AS NAOH, KOH, ETC. Stability Condition to Avoid:STABLE AT NORMAL TEMPERATURES AND STORAGE CONDITIONS.

Hazardous Decomposition Products:DECOMPOSES WITH HEAT. HIGH TEMPERATURES (OPEN FLAMES, GLOWING METAL SURFACES, ETC.) CAN DECOMPOSE HFC-

43-10MEE FORMING HYDROFLUORIC ACIDS AND POSSIBLY CARBONYL HALIDES. HFC-43-10MEE IS INCOMPATIBLE Conditions to Avoid Polymerization:WILL NOT OCCUR.

Toxicological Information:ANIMAL DATA: HFC-43-10MEE: ORAL LD50: >5,000 MG/KG IN RATS. DERMAL ALD: > 5,000 MG/KG IN RABBITS. INHALATION, 4-HR LC50: 11,100 PPM IN RATS. T-DCE: ORAL LD50: 1275 MG/KG IN RATS. DERMAL LD50: >5,000 MG/KG IN RABBITS. INHALATION LC50, 4 HR: 24,100 PPM IN RATS.

Ecological:ECOTOXICOLOGICAL TOXICITY: HFC-43-10MEE: 96-HOUR LC50, FATHEAD MINNOWS: 27.2 MG/L. 96-HOUR LC50, RAINBOW TROUT: 13.9 MG/L. 48-HOUR LC50, DAPHNIA MAGNA: 11.7 MG/L. T-DCE: 96-HOUR LC50, BLUEGILL SUNFISH : 1350 MG/L. 48 HOUR LC50, DAPHNIA MAGNA: 220 MG/L.

Waste Disposal Methods:TREATMENT, STORAGE, TRANSPORTATI ON, AND DISPOSAL

MUST BE IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE/PROVINCIAL, AND LOCAL REGULATIONS.

Transport Information:DOT/IMO/IATA: NOT REGULATED IN CONTAINERS LESS THAN 2600 LBS. IF GREATER THAN 2600 LBS USE: PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (TRANS-1,2-DICHLOROETHYLENE). HAZA RD CLASS: 9. UN NUMBER: 3082. PACKING GROUP: III. REPORTABLE QUANTITY: 1000 L

## BS (TRANS-1,2-DICHLOROETHYLENE); 2600 LBS ("VERTREL" MCA).

SARA Title III Information: TITLE III HAZARD CLASSIFICATIONS SECTIONS 311, 312: ACUTE: YES, CHRONIC: NO, FIRE: NO, REACTIVITY-NO, PRESSURE-NO. SARA EXTREMELY HAZARDOUS SUBSTANCE: NO.

Federal Regulatory Information:CERCLA HAZARDOUS SUBSTANCE: 1,2-DICHLOROETHYLENE ONLY. TSCA: ALL COMPONENTS ARE LISTED ON THE TSCA PUBLIC INVENTORY. 1,1,1,2,2,3,4,5,5,5-

**DECAFLUOROPENTANE (CAS#** 

138495-42-8) IS CONTROLLED BY TSCA SECT ION 5, SIGNIFIGANT NEW USE RULE (SNUR; 40 CFR 721.5645). THE APPROVED USES ARE: PRECISION AND GENERAL CLEANING, CARRIER FLUID, DISPLACEMENT DRYING, PRINTED CIRCUIT BOARD CLEANING, PARTICULATE REMOVAL & FILM CLEANING, PROCESS MEDIUM, HEAT TRANSFER FLUID (DIELECTRIC & NON-DIELECTRIC) AND TEST FLUID.

State Regulatory Information:NOT PROVIDED BY MANUFACTURER

==================

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their pa

rticular situation.