View NSN Online: https://aerobasegroup.com/nsn/8030-01-187-8439

3M GENERAL OFFICES -- 3M MARINE ADHESIVE SEALANT 5200

\_\_\_\_\_\_

MSDS Safety Information

\_\_\_\_\_

FSC: 8030

NIIN: 01-187-8439

MSDS Date: 11/10/1997 MSDS Num: CKWXP

Product ID: 3M MARINE ADHESIVE SEALANT 5200

MFN: 02

Responsible Party Cage: 76381

Name: 3M GENERAL OFFICES

Address: 3M CENTER

City: ST PAUL MN 55144-100

0

Info Phone Number: 1-800-364-3577 Emergency Phone Number: 0000000000

Review Ind: Y Published: Y

\_\_\_\_\_\_

**Contractor Summary** 

\_\_\_\_\_

Cage: 76381

Name: MINNESOTA MINING AND MFG CO, DBA 3M

Address: 3M CENTER BLDG 224-5S-04 City: SAINT PAUL MN 55144-1000 Phone: 866-556 5712 / 612-733-1110

\_\_\_\_\_\_

Item Description Information

\_\_\_\_\_

\_\_\_\_\_

Item Manager: GSA

Item Name: SEALING COMPOUND

Specification Number: NONE Type/Grade/Class: NONE

Unit of Issue: CA

Quantitative Expression: 00000000012OZ

UI Container Qty: 0

Type of Container: CARTRIDGE

\_\_\_\_\_\_

Ingredients

\_\_\_\_\_

Cas: 9057-91-4

Name: POLYPROPYLENE PREPOLYMER

% low Wt: 50. % high Wt: 60.

-----

Cas: 14807-96-6

RTECS #: WW2710000

Name:

TALC

% low Wt: 10. % high Wt: 30.

OSHA PEL: 2 MG/M3 ACGIH TLV: 2 MG/M3

-----

Cas: 13463-67-7

RTECS #: XR2275000 Name: TITANIUM DIOXIDE

% low Wt: 3. % high Wt: 7.

OSHA PEL: 10 MG/M3 ACGIH TLV: 10 MG/M3

-----

Cas: 1314-13-2

RTECS #: ZH4810000 Name: ZINC OXIDE

% low Wt: 1. % high Wt: 5.

OSHA PEL: 10 MG/M3 ACGIH TLV: 10 MG/M3

-----

Cas: 142-82-5

RTECS #: MI7700000 Name: HEPTANE

> Wt: .4

OSHA PEL: 500 PPM ACGIH TLV: 400 PP

M

ACGIH STEL: 500 PPM

Cas: 67-64-1

RTECS #: AL3150000 Name: ACETONE

> Wt: .4

OSHA PEL: 1000 PPM ACGIH TLV: 750 PPM ACGIH STEL: 1000 PPM EPA Rpt Qty: 5000 LBS DOT Rpt Qty: 5000 LBS

-----

Cas: 108-88-3

RTECS #: XS5250000 Name: TOLUENE

> Wt: .4

OSHA PEL: 100 PPM OSHA STEL: 150 PPM EPA Rpt Qty: 1000 LBS DOT Rpt Qty: 1000 LBS

-----

Cas: 110-54-3

RTECS #: MN9275000

Name: HEXANE

> Wt: .4

OSHA PEL: 500 PPM

**ACGIH TL** 

V: 1000 PPM EPA Rpt Qty: 1 LB DOT Rpt Qty: 1 LB

\_\_\_\_\_

Health Hazards Data

\_\_\_\_\_\_

Effects of Exposure: EYE CONTACT: MODERATE EYE IRRITATION SYMPTOMS CAN INCLUDE REDNESS, SWELLING, PAIN, TEARING AND HAZY VISION. SKIN CONTACT: MILD SKIN IRRITATION SYMPTOMS INCLUDE REDNESS, SWELLING AND ITCHING. ALLERGIC REACTION SYMPTOMS CAN INCLUDE REDNESS, SWELLING, BLISTERING AND ITCHING. INHALATION: VAPO

RS OF UNCURED PRODUCT MAY CAUSE IRRITATION OF THE RESPIRATORY SYSTEM.
ALLERGIC RESPIRATORY REACTION SYMPTOMS CA N INCLUDE DIFFICULTY BREATHING,
WHEEZING, TIGHTNESS OF CHEST AND RESPIRATORY FAILURE. INGESTION MAY CAUSE
IRRITATION OF GASTROINTESTIONAL TISSUES.

First Aid: EYE CONTACT: IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER. GET IMMEDIATE MEDICAL ATTENTION. SKIN CONTACT: IMMEDIATELY WASH SKIN WITH SOAP AND LARGE AMOUNTS OF WATER. REMOVE CONTAMINATED CLOTHING. IF SYMPTOMS OCCUR

CALL A PHYSICIAN. WASH CONTAMINATED CLOTHING BEFORE REUSE AND DISPOSE OF CONTAMINATED SHOES. INHALATION: REMOVE PERSON TO FRESH AIR. IF NOT BREATHING GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GET IMMEDIATE MEDICAL ATTENTION. IF SWALLOWED: DO NOT INDUCE VOMITING. DRINK TWO GLASSES OF WATER. CALL A PHYSICIAN.

\_\_\_\_\_

Handling and Disposal

\_\_\_\_\_

Spill Release Procedures: CONTA

IN SPPILL. EVACUATE UNPROTECTED PERSONELL FROM

HAZARD AREA. NEUTRALIZE SPILL WITH AGENT ON SPILL AND ALLOW TO REACT FOR 10 MINITUES. ALTERNATELY, POUR WATER ON SPILL AND ALLOW TO REACT FOR MORE T HAN 30 MINITUES. COVER WITH ABSORBENT. PLACE IN AN APPROVED DRUM, BUT DO NOT SEAL THE DRUM FOR 48 HOURS TO AVOID POSSIABLE PRESSURE BUILDUP. NEUTRALIZE SPILL RESIDUE WITH DECONTAMINANT SOLUTION.

Neutralizing Agent: 90% WATER, 8% CONCENTRATED AMMONIA, 2% DETERGENT

Waste Disposal Methods: CURE P

RODUCT ACCORDING TO PRODUCT INSTRUCTIONS.

INCINERATE ON AN INDUSTRIAL OR COMMERCIAL FACILITY IN THE PRESENCE OF A COMBUSTABLE MATERIAL. DISPOSE OF COMPLETELY CURED MATERIAL IN A SANITARY LANDFIL L. DISPOSE OF WASTE PRODUCT IN A FACILITY PERMITTED TO ACCEPT CHEMICAL WASTE.

Handling And Storage Precautions: KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP CONTAINER IN WELL-VENTILATED AREA. KEEP OUT OF REACH OF CHILDREN.

\_\_\_\_\_\_

Fire and Explosi

on Hazard Information

\_\_\_\_\_

Flash Point: =69.4C, 157.F Flash Point Text: 157 F

Extinguishing Media: WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL, FOAM Fire Fighting Procedures: WEAR FULL PROTECTIVE CLOTHING, INCLUDING HELMET,

SCBA, BUNKER CAOT AND PANTS, BANDS AROUND ARMS, WAIST AND LEGS, FACE MASK AND

PROTECTIVE COVERING FOR EXPOSED AREAS OF THE HEAD.

\_\_\_\_\_

**Control Measures** 

===============

\_\_\_\_\_

Respiratory Protection: USE APPROVED NIOSH RESPIRATORS BASED ON CONDITIONS.

Ventilation: LOCAL EXHAUST OR ADEQUATE Protective Gloves: APPROPIATE GLOVES

Eye Protection: SAFETY GLASSES WITH SIDE SHIELDS

Other Protective Equipment: APRON, COVERALLS.

\_\_\_\_\_

Physical/Chemical Properties

\_\_\_\_\_\_

Spec Gravity: 1.170-1.220

Viscosity: CA 100000 CENTIPOISE

Solubility in Wa

ter: NIL

Appearance and Odor: THIXPTROPIC PASTE, WHITE, VERY SLIGHT ODOR

Percent Volatiles by Volume: < 1

\_\_\_\_\_

Reactivity Data

\_\_\_\_\_\_

Stability Indicator: YES

Stability Condition To Avoid: REACTION WITH WATER, ALCOHOLS AND AMINES IS NOT

HAZARDOUS IF CONTAINER CAN VENT TO THE ATMOSPHERE TO PREVENT PRESSURE BUILD

UP.

Materials To Avoid: AMINES, ALCOHOLS, WATER.

Hazardous Decomposition Produc

ts: CARBON MONOXIDE AND CARBON DIOXIDE, OXIDES OF

NITROGEN, HYDROGEN CYANIDE, ISOCYANATES, TOXIC VAPORS, GASES OR PARTICULATES.

\_\_\_\_\_\_

Regulatory Information

\_\_\_\_\_

Sara Title III Information: ZINC OXIDE, HEXANE, TOLUENE

\_\_\_\_\_

Other Information

\_\_\_\_\_

Other Information: THE INFORMATION IN THIS MSDS

IS BELIEVED TO BE CORRECT AS OF

THE DATE ISSUED. 3M MAKES NO WARRANTIES, EXPRESSES OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNE SS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. SEE HARD COPY MSDS FOR DETAILS.

-----

Transportation Information

\_\_\_\_\_\_

Responsible Party Cage: 76381

Trans ID NO: 155672

Product ID: 3M MARINE ADH

**ESIVE SEALANT 5200** 

MSDS Prepared Date: 11/10/1997

Review Date: 09/13/2000

MFN: 2

Multiple KIT Number: 0 Unit Of Issue: CA Container QTY: 0

Type Of Container: CARTRIDGE

**Detail DOT Information** 

\_\_\_\_\_\_

DOT PSN Code: ZZZ

DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

\_\_\_\_\_

**Detail IMO Information** 

\_\_\_\_\_

\_\_\_\_\_

IMO PSN Code: ZZZ

IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

\_\_\_\_\_\_

**Detail IATA Information** 

\_\_\_\_\_\_

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

\_\_\_\_\_

**Detail AFI Information** 

\_\_\_\_\_\_

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

\_\_\_\_\_

HAZCOM Label

\_\_\_\_\_

Product ID: 3M MARINE ADHESIVE SEALANT 5200

Cage: 76381

Company Name: MINNESOTA MINING AND MFG CO, DBA 3M

Street: 3M CENTER BLDG 224-5S-04

City: SAINT PAUL MN Zipcode: 55144-1000

Health Emergency Phone: 0000000000

Label Required IND: Y

Date Of Label Review: 12/22/2000

Status Code: A Origination Code:

Hazard And Precautions: EYE CONTACT: MODERATE EYE IRRITATION SYMPTOMS CAN INCLUDE REDNESS, SWELLING, PAIN, TEARING AND HAZY VISION. SKIN CONTACT: MILD SKIN IRRITATION SYMPTOMS INCLUDE REDNESS, SWELLING AND ITCHING. ALLERGIC REACTION SYMPTOMS CAN INCLUDE REDNESS, SWELLING, BLISTERING AND ITCHING. INHALATION: VAPORS OF UNCURED PRODUCT MAY CAUSE IRRITATION OF THE RESPIRATORY SYSTEM. ALLERGIC RESPIRATORY REACTION SYMPTOMS CAN INCLUDE DIFFICULTY BREATHING, WHEEZING, TIGHTNESS OF CHES

T AND RESPIRATORY FAILURE. INGESTION
MAY CAUSE IRRITATION OF GASTROINTESTIONAL TISSUES.

\_\_\_\_\_

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons o

utside the Department of Defense

nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department

of Defense or other government situation.