View NSN Online: https://aerobasegroup.de/nsn/8010-01-260-0911

Product ID: POLYURETHANE COATING, 37925 UNTINTED PART 1 MSDS Date:09/21/2000 FSC:8010 NIIN:01-260-0911 Status Code:A Kit Part:Y **MSDS Number: CKYPD** === Responsible Party === Company Name: SHERWIN-WILLIAMS CO THE Address:101 PROSPECT AVE NW City:CLEVELAND State:OH ZIP:44115-104 2 Country:US Info Phone Num:216-566-2242 Emergency Phone Num:216-566-2917 Preparer's Name: BOBBY STOKES CAGE:54636 === Contractor Identification === Company Name: SHERWIN-WILLIAMS CO THE Address:101 PROSPECT AVE NW Box:City:CLEVELAND State:OH ZIP:44115-1042 Country:US Phone:800-251-2486/216-566-2242 CAGE:54636

Ingred Name:XYLENE CAS:1330-20-7 RTECS #:ZE2100000 = Wt:1. ACGIH TLV:434 MG/M3;100 PPM ACGIH STEL:651 MG/M3;150 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:METHYL N-AMYL KETONE CAS:110-43-0 RTECS #:MJ5075000 = Wt:22. OSHA PEL:465 MG/M3;100 PPM ACGIH TLV:233 MG/M3;50 PPM

Ingred Name:1-METHOXY-2-PROPYL ACETATE CAS:108-65-6 RTECS #:AI8925000 = Wt:6.

Ingred Name:QUARTZ CAS:14808-60-7 RTECS #:VV7330000 = Wt:30. OSHA PEL:SEE TABLE Z-3 ACGIH TLV:0.1 MG/M3

Ingred Name:CRISTOBALITE CAS:14464-46-1 RTECS #:VV7325000 = Wt:4. OSHA PEL:SEE TABLE Z-3 ACGIH TLV:0.05 MG/M3

Ingred Name:11661 GREEN CAS:1308-38-9

RTECS #:GB6475000 = Wt:10. OSHA PEL:0.5 ACGIH TLV:0.5

Ingred Name:C.I. 77344 CAS:68187-49-5 = Wt:6.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic:EXPOSURE MAY BE BY INHALATION AND/OR SKIN OR EYE CONTACT, DEPENDING ON CONDITIONS OF USE. CRYSTALLINE SILICA IS LISTED BY IARC AND NTP. LONG TERM EXPOSURE TO HIGH LEVELS OF SILICA DUST WHICH OCCUR W HEN SANDING OR ABRADING THE DRY

FILM MAY CAUSE LUNG DAMAGE AND PROBABLY CANCER. COBALT IS CLASSIFIED BY IARC AS POSSIBLY CARCINOGENIC. PROLONGED OVEREXPOSURE TO SOLVENT INGREDIENTS MAY CAUSE ADVERSE AFFECTS TO LIVER, URINARY, BLOOD.

Effects of Overexposure:HEADACHE,DIZZINESS,NAUSEA,AND LOSS OF COORDINATION ARE INDICATIONS OF EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MISTS. REDNESS AND ITCHING OR BURNING SENSATION MAY INDICATE EYE OR EXCESSIVE SKIN EXPOSURE. IRRITATION OF EYES,SKIN AND RES

PIRATORY SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME OVEREXPOSURE MAY RESULT IN UNCONSCIOUSNESS AND POSSIBLY DEALTH. Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

First Aid:INHALED: IF AFFECTED ,REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET. SKIN:WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE RE-USE.EYE:F LUSH EYES WIT H LARGE AMOUNTS OF WATER FOR 15

MINUTES. GET MEDICAL ATTENTION. SWALLOWED: GET MEDICAL ATTENTION.

Flash Point Method:PMCC

Flash Point:=38.9C, 102.F

Lower Limits:1

Upper Limits:13.1

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures: FULL PROTECTIVE EQUIPMENT INCLUDING

SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PRE

FERABLE. WATER

MAY BE USED TO COOL CLOSED CO NTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTOIGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT,ELECTRICAL EQUIPMENT,SPARKS,AND OPEN FLAME.CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. APPLICATION TO HOT SURFACES REQUIRE SPECIAL PRE CAUTIONS. DURING EMERGENCY CONDITIONS OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD.

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

Handling and Storage Precautions: CONTENTS ARE COMBUSTABLE. KEEP AWAY FROM HEAT AND OPEN FLAME. KEEP CONTAINER CLOSED WHEN NOT IN USE. TRANSFER ONLY TO APPROVED CONTAINERS WITH COMPLETE AND APPROPRIATE LABELING. DO NOT TAKE IN

TERNALLY KEEP OUT OF REACH OF CHILDREN.

Other Precautions: INTENTIONAL MIUSE BE DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS CAN BE HARMFUL OR FATAL.

Respiratory Protection: IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA FOR PROTECTION AGAINST MATERIALS.

Ventilation:LOCAL EXHAUSE PREFERRABL

Ε.

Protective Gloves: AS RECOMMENDED BY GLOVE SUPPLIER Eye Protection: SAFETY SPECTACLES WITH UNPERFORATED SIDESHIELDS

Other Protective Equipment: USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR, AVOID CONTACT WITH EYES.

Supplemental Safety and Health

CONTENTS ARE COMBUSTIBLE. KEEP AWAY FROM HEAT AND OPEN FLAME. USE APPROVED BONDING AND GROUNDING PROCEDURES. KEEP CONTAINER CLOSED WHEN NOT IN USE.

Boiling P t:>138.3C, 281.F B.P. Text:281-308 F Vapor Density:> AIR Spec Gravity:1.52 VOC Pounds/Gallon:456 Evaporation Rate & amp; Reference:SLOWER THAN ETHER Percent Volatiles by Volume:54

Stability Indicator/Materials to Avoid:YES NONE KNOWN Stability Condition to Avoid:NONE KNOWN Hazardous Decomposition Products:BY FIRE:CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF METALS Conditions to Avoid Polymerization:WILL NOT OCCUR Waste Disposal Methods:WASTE FROM THIS PRODUCT MAY BE HAZARDOUS AS DEFINED UNDER THE (RCRA) 40 CFR 261. WASTE MUST BE TESTED FOR IGNITABILITY AND EXTRACTABILITY TO DETERMINE THE APPLICABLE EPA HAZARDOUS WASTE NUMBERS. INCIN ERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINER.

SARA Title III Information:CAS NUMBER 1330-20-7, XYLENE, 1% BY WEIG HT.

ALSO, CHROMIUM COMPOUND, 16% BY WT, COBALT COMPOUND, 6% BY WT, ZINC COMPOUND, 6% BY WT.

State Regulatory Information: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, ex

pressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.