

RED DEVIL, INCORPORATED -- FILLER, WOOD, PLASTIC #X-552 -- 8030-00-664-7077

===== Product Identification =====

Product ID:FILLER, WOOD, PLASTIC #X-552

MSDS Date:01/07/1996

FSC:8030

NIIN:00-664-7077

Status Code:A

MSDS Number: CKYTD

=== Responsible Party ===

Company Name:RED DEVIL, INCORPORATED

Address:ONE WEBB STREET

Box:A

City:PRYOR

State:OK

ZIP:74361

Country:US

Info Phone Num:918-825-5744

Emergen

cy Phone Num:918-825-5744

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:23577

=== Contractor Identification ===

Company Name:RED DEVIL, INCORPORATED

Address:ONE WEBB STREET

Box:A

City:PRYOR

State:OK

ZIP:74361

Country:US

Phone:918-825-5744

CAGE:23577

===== Composition/Information on Ingredients =====

Ingred Name:ISO-PROPYL ALCOHOL

CAS:67-63-0

RTECS #:NT8050000

< Wt:2.

OSHA PEL:980 MG/M3;400 PPM

ACGIH TLV:983 MG/M3;400 PPM

ACGIH STEL:1230 MG/M3;500 PPM

Ingred Name:ACETONE
CAS:67-64-1
RTECS #:AL3150000
> Wt:25.
OSHA PEL:2400 MG/M3;1000 PPM
ACGIH TLV:1780 MG/M3;750 PPM
ACGIH STEL:2380 MG/M3;1000 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:N-BUTYL ACETATE
CAS:123-86-4
RTECS #:AF7350000
< Wt:4.
OSHA PEL:710 MG/M3;150 PPM
ACGIH TLV:713 MG/M3;150 PPM
ACGIH STEL:950 MG/M3;200 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:WOOD FLOUR-(AS WOOD DUST)
< Wt:10.

===== Hazards Identification =====
=====

Effects of Overexposure:DUST GENERATED FROM DRIED PRODUCT MAY CAUSE
EYE, SKIN, AND RESPIRATORY IRRITATION
AND MAY CAUSE LUNG DAMAGE. VAPORS MAY PRODUCE HEADACHE, DIZZINESS AND
NAUSEA. EYE
CONTACT CAUSES BURNING AND IRRITATIO N. MAY CAUSE MINOR REVERSIBLE
EFFECTS ON LIVER
AND KIDNEYS.

===== First Aid Measures =====

First Aid:EYES: IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR
AT LEAST 15 MINUTES
WHILE HOLDING EYELIDS OP

EN. SKIN: WIPE MATERIAL FROM SKIN WITH CLOTH OR PAPER TOWEL, THEN WASH EXPOSED AREA WITH SOAP AND WATER. INHALATION: MOVE VICTIM TO FRESH AIR AND TREAT SYMPTOMATICALLY. INGESTION: CONTACT LOCAL POISON CONTROL CENTER OR PHYSICIAN IMMEDIATELY!

===== Fire Fighting Measures =====

Flash Point Method:CALC
Flash Point:=-4.4C, 40.F
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, OR FOAM.
Fire Fighting Procedures:USE WATER SPRAY OR FOG TO COOL FIRE-EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:VAPORS CAN FLOW TO IGNITION SOURCES AND FLASHBACK.

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP SPILLED MATERIAL, WASH AREA WITH DETERGENT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED. IF TLV IS EXCEEDED, OR FOR SYMPTOMS OF OVEREXPOSURE, WEAR A NIOSH-APPROVED RESPIRATOR FOR ORGANIC VAPORS.
Ventilation:LOCAL EXHAUST MAY BE NECESSARY UNDER SOME HANDLING/USE CONDITIONS .
Protective Gloves:WEAR CHEMICAL-RESISTANT GLOVES AND CLOTHING AS NEEDED TO PREVENT SKIN CONTACT.
Eye Protection:IF POTENTIAL FOR EYE CONTACT EXISTS, WEAR CHEMICAL GOGGLES.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Vapor Density:(AIR=1)
Spec Gravity:(H2O=1)
Evaporation Rate & Reference: