

RED DEVIL, INCORPORATED -- FILLER, WOOD, PLASTIC #X-552 -- 8030-00-664-7088

=====
Product Identification
=====

Product ID:FILLER, WOOD, PLASTIC #X-552
MSDS Date:01/07/1996
FSC:8030
NIIN:00-664-7088
Status Code:A
MSDS Number: CKYTF
=== Responsible Party ===
Company Name:RED DEVIL, INCORPORATED
Address:ONE WEBB STREET
Box:A
City:PRYOR
State:OK
ZIP:74361
Country:US
Info Phone Num:918-825-5744
Emerge
ncy Phone Num:918-825-5744
Preparer's Name:ERNEST CARTER
Chemtrec Ind/Phone:(800)424-9300
CAGE:23577
=== Contractor Identification ===
Company Name:RED DEVIL, INCORPORATED
Address:ONE WEBB STREET
Box:A
City:PRYOR
State:OK
ZIP:74361
Country:US
Phone:918-825-5744
CAGE:23577

=====
Composition/Information on Ingredients
=====

Ingred Name:ISO-PROPYL ALCOHOL
CAS:67-63-0
RTECS #:NT8050000
< Wt:2.
OSHA PEL:980 MG/M3;400 PPM
ACGIH TLV:983 MG/M3;400 PPM
ACGIH STEL:1230 MG/M3;500 PPM

Ingred Name:ACETONE
CAS:67-64-1
RTECS #:AL3150000
> Wt:25.
OSHA PEL:2400 MG/M3;1000 PPM
ACGIH TLV:1780 MG/M3;750 PPM
ACGIH STEL:2380 MG/M3;1000 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:N-BUTYL ACETATE
CAS:123-86-4
RTECS #:AF7350000
< Wt:4.
OSHA PEL:710 MG/M3;150 PPM
ACGIH TLV:713 MG/M3;150 PPM
ACGIH STEL:950 MG/M3;200 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:WOOD FLOUR-(AS WOOD DUST)
< Wt:10.

=====
Hazards Identification
=====

Effects of Overexposure:DUST GENERATED FROM DRIED PRODUCT MAY CAUSE EYE, SKIN, AND RESPIRATORY IRRITATION AND MAY CAUSE LUNG DAMAGE. VAPORS MAY PRODUCE HEADACHE, DIZZINESS AND NAUSEA. EYE CONTACT CAUSES BURNING AND IRRITATION. MAY CAUSE MINOR REVERSIBLE EFFECTS ON LIVER AND KIDNEYS.

=====
First Aid Measures
=====

First Aid:EYES: IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN

PEN. SKIN: WIPE MATERIAL FROM SKIN WITH CLOTH OR PAPER TOWEL, THEN WASH EXPOSED AREA WITH SOAP AND WATER. INHALATION: MOVE VICTIM TO FRESH AIR AND TREAT SYMPTOMATICALLY. INGESTION: CONTACT LOCAL POISON CONTROL CENTER OR PHYSICIAN IMMEDIATELY!

=====
===== Fire Fighting Measures =====

Flash Point Method:CALC
Flash Point:=4.4C, 40.F
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, OR FOAM.
Fire Fighting Procedures:USE WATER SPRAY OR FOG TO COOL FIRE-EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:VAPORS CAN FLOW TO IGNITION SOURCES AND FLASHBACK.

=====
===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP SPILLED MATERIAL, WASH AREA WITH DETERGENT.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED. IF TLV IS EXCEEDED, OR FOR SYMPTOMS OF OVEREXPOSURE, WEAR A NIOSH-APPROVED RESPIRATOR FOR ORGANIC VAPORS.
Ventilation:LOCAL EXHAUST MAY BE NECESSARY UNDER SOME HANDLING/USE CONDITIONS .
Protective Gloves:WEAR CHEMICAL-RESISTANT GLOVES AND CLOTHING AS NEEDED TO PREVENT SKIN CONTACT.
Eye Protection:IF POTENTIAL FOR EYE CONTACT EXISTS, WEAR CHEMICAL GOGGLES.
Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Vapor Density:(AIR=1)
Spec Gravity:(H2O=1)
Evaporation Rate & Reference: