

HYSAN/AMP -- MULTI-PURPOSE LUBRICANT & CORROSION INHIBITOR -- 6850-00-050-0659

=====
Product Identification
=====

Product ID: MULTI-PURPOSE LUBRICANT & CORROSION INHIBITOR

MSDS Date: 11/09/1998

FSC: 6850

NIIN: 00-050-0659

Status Code: A

MSDS Number: CKYWT

=== Responsible Party ===

Company Name: HYSAN/AMP

Address: 9055 FREEWAY DRIVE

City: MACEDONIA

State: OH

ZIP: 44056

Country: US

Info Phone Num: 330-467-4195

Emergency Phone Num: 330-467-4195

CAGE: UO035

=== Contractor Identification ===

Company Name: GOURMET INQUE LTD

Address: 191 STANLEY ST

Box: City: ELK GROVE VILLAGE

State: IL

ZIP: 60007-1555

Country: US

Phone: 847-296-6192/FAX: 800-542-1042

Contract Num: SP0450-01-M-D739

CAGE: 0TNN7

Company Name: HYSAN/AMP

Address: 9055 FREEWAY DRIVE

Box: City: MACEDONIA

State: OH

ZIP: 44056

Country: US

Phone: 330-467-4195

CAGE: UO035

=====
Composition/Information on Ingredients
=====

Ingred Name: PETROLEUM DISTI

LLATE
CAS:64742-47-8
RTECS #:OA5504000
Minumum % Wt:60.
Maxumum % Wt:70.
OSHA PEL:400 PPM

Ingred Name:INHIBITED PARAFFINIC OIL MIXTURE
Minumum % Wt:25.
Maxumum % Wt:30.
OSHA PEL:5 MG/M3
OSHA STEL:10 MG/M3
ACGIH TLV:5 MG/M3
ACGIH STEL:10 MG/M3

Ingred Name:CARBON DIOXIDE
CAS:124-38-9
RTECS #:FF6400000
Minumum % Wt:1.
Maxumum % Wt:10.
OSHA PEL:9000 MG/M3;5000 PPM
ACGIH TLV:9000 MG/M3;5000 PPM
ACGIH STEL:54000 MG/M3

===== Hazards Identification =====

LD50 LC50 M
ixture:NO DATA PROVIDED BY MANUFACTURER
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:MAY CAUSE DIZZINESS OR NARCOSIS IN
HIGH VAPOR CONCENTRATIONS. WILL CAUSE DEFATTING OF SKIN. EFFECTS
ARE REVERSIBLE. LONG TERM EXPOSURE (YEARS) TO HIGH CONCENTRATIONS
OF VAPOR MAY CAUSE LUNG, LIVER OR KIDNEY DAMAGE. THE SOLVENTS
LISTED HAVE BEEN REPORTED TO AFFECT THE CENTRAL NERVOUS SYSTEM.
ASPIRATION HAZARD IF SWALLOWED. EYE AND SKIN IRRITANT. MA
Y IRRITATE
RESPIRATORY TRACT. DELIBERATELY CONCENTR ATING AND HANDLING THE
VAPOR OF THE CONTENTS MAY BE HARMFUL OR FATAL.
Explanation of Carcinogenicity:LONG TERM TOXICOLOGICAL STUDIES HAVE NOT
BEEN CONDUCTED FOR THIS PRODUCT.
Effects of Overexposure:INHALATION-DIFFICULTY IN BREAATHING.
SKIN-REDNESS. INGESTION-VOMITING.
Medical Cond Aggravated by Exposure:HEART DISEASE, RESPIRATORY DISEASES

===== First Aid Measures =====

First Aid:GIVE OXYG

EN. DO NOT INDUCE VOMITING. WASH EYES AND SKIN WITH WATER FOR 15 MINUTES. GET MEDICAL HELP. NEVER ADMINISTER ADRENALIN FOLLOWING OVEREXPOSURE.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:=65.6C, 150.F

Lower Limits:1.1

Upper Limits:10.6

Extinguishing Media:WATER FOG, CARBON DIOXIDE, FOAM, DRY CHEMICAL

Fire Fighting Procedures:KEEP CONTAINERS COOL. USE EQUIPMENT OR SHIELDING REQUIRED TO PROTECT AGAINST BURSTING OR VENTING

CONTAINERS.

Unusual Fire/Explosion Hazard:HEATED CANS MAY BURST.

===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT SWEEPING COMPOUND TO SOAK UP MATERIAL. PUT INTO CONTAINER. DISPOSE AS HAZARDOUS WASTE.

Neutralizing Agent:NO DATA PROVIDED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, OR OPEN FLAMES. STORE AT TEMPERATURES BELOW 1 20F.

Other Precautions:WHEN SPRAYING MORE THAN ONE HALF CAN CONTINUALLY OR MORE THAN ONE CAN CONSECUTIVELY, USE NIOSH APPROVED RESPIRATOR.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR IF TLV LIMIT IS EXCEEDED.

Ventilation:LOCAL EXHAUST-YES.

Protective Gloves:NONE REQUIRED IF SPRAYING

Eye Protection:SAFETY GLASSES

Other Protective Equipment:LONG SLEEVES AND LONG PANTS.

Work Hygienic Practices:DO NOT SMOKE WHILE U

SING. WASH HANDS AFTER USE.
Supplemental Safety and Health
NO DATA PROVIDED BY MANUFACTURER

===== Physical/Chemical Properties =====

HCC:V2
Boiling Pt:B.P. Text:150->600F
Vapor Pres:95
Vapor Density:4.0
Spec Gravity:.8167
Evaporation Rate & Reference: