

GRIGGS PAINT -- A-A-00665E #14110 GREEN -- 8010-00-721-9483

=====
Product Identification
=====

Product ID:A-A-00665E #14110 GREEN

MSDS Date:08/01/1999

FSC:8010

NIIN:00-721-9483

Status Code:A

MSDS Number: CKYYG

=== Responsible Party ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

City:PHOENIX

State:AZ

ZIP:85040

Country:US

Info Phone Num:602-243-3293

Emergency Phone Num:(800)424-9300

Prepare

r's Name:HENRY SIMMONS

Chemtrec Ind/Phone:(800)424-9300

CAGE:58963

=== Contractor Identification ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

Box:City:PHOENIX

State:AZ

ZIP:85040

Country:US

Phone:602-243-3293

CAGE:58963

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC PETROLEUM DISTILLATES

CAS:64742-89-8

= Wt:10.

Ingred Name:ALIPHATIC HYDROCARBONS(STODDARD TYPE)

CAS:8052-41-3

RTECS #:WJ8925000

= Wt:8.

OSHA PEL:2900 MG/M3;500 PPM

ACGIH TLV:52

5 MG/M3;100 PPM

Ingred Name:XYLENE

CAS:1330-20-7

RTECS #:ZE2100000

= Wt:2.

ACGIH TLV:434 MG/M3;100 PPM

ACGIH STEL:651 MG/M3;150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:HEALTH HAZARDS (ACUTE AND CHRONIC)

DIRECT CONTACT TO EYES MAY CAUSE IRRITATION, PROLONG AND/OR

REPEATED MAY CAUSE SKIN IRRITATION. INHALATION OF HIGH

CONCEN

TRATIONS OF VAPORS MAY LEAD TO LUNG CHANGES, NAUSEA,

VOMITING, COUGH, PULMONARY IRRITATION, AND CENTRAL NERVOUS SYSTEM

DEPRESSION. INGESTION MAY CAUSE GASTROINTESTINAL DISTURBANCES.

ASPIRATIONS OF THIS PRODUCT INTO THE LUNGS MAY CAUSE PNEUMONITIS,

PULMONARY EDEMA AND HEMORRAGE.

Effects of Overexposure:INHALATION HEALTH RISK AND SYMPTONS OF EXPOSURE

BREATHING OF HIGH VAPOR CONCENTRATIONS MAY CAUSE DROWSINESS,

DIZZINESS, FATIGUE, FOLLOWED BY COMA. SKIN AND EYE CONTACT HEALT

H

RISKS AND SYMPTONS OF EXP OSURE.EYE: DIRECT CONTACT AND/OR CONTACT

WITH VAPORS MAY CAUSE IRRITATION.SKIN: PROLONGED OR REPEATED

CONTACT MAY CAUSE IRRITATION AND/OR DERMITITIS THROUGH THE SKIN.

SKIN ABSORPTION HEALTH RISKS AND SYMPTONS OF EXPOSURE PROLONGED

OR REPEATED EXPOSURE CAN CAUSE MODERATE IRRITATION, DEFATTING, AND

HERMITITIS.INGESTION HEALTH RISKS AND SYMPTONS OF EXPOSURE

ASPIRATION OF THIS PRODUCT MAY CAUSE INTO THE LUNGS MAY CAUSE

PNEMONTITIS.

Medic

al Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING

DISEASES IN OR HISTORY OF AILMENTS INVOLVING SKINCENTRAL NERVOUS

SYSTEM, LIVER, AND KIDNEY.

=====
===== First Aid Measures =====

First Aid:EYE CONTACT: IMMEDIATELY FLUSH WITH LARGE AMOUINTS OF WATER

FOR 15 MINUTES. SEEK MEDICAL AID SKIN: WASH THOROUGHLY WITH SOAP AND

WATER. SEEK MEDICAL AID IF IRRITAITON PERSISTS. INGESTIONS:

IMMEDIATELY SEEK MEDICAL AID. DO NOT INDUCE VOMITING. DO

NOT
ATTEMPT TO GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:=10.C, 50.F
Lower Limits:.9%
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG
Fire Fighting Procedures:APPROVED GAS MASK REQUIRED FOR FIRE FIGHTING PERSONEL. WATER MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CONTAINERS. IF WATER IS USED, FOG NOZZLES ARE PREFERRED.
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:PRECAUTIONS FOR SAFE HANDLING STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED STOP LEAK IF NO RISK INVOLVED. REMOVE ALL SOURCES OF IGNITION. STAY UPWIND. ABSORB WITH INERT MATERIAL. FLUSH AR EA WITH WATER. VENTILATE AREA FOR AT LEAST 24 HOURS OR UNTIL AREA HAS BEEN DECLARED SAFE.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED AND UPRIGHT TO PREVENT LEAKAGE. AVOID FLAMES, WELDING, OPEN LIGHTS, ETC. AVOID BREATHING OF VAPOR AND SPRAY MIST. AVOID SKIN AND EYE CONTACT.
Other Precautions:MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN CONFINED AREA WITHOUT ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURE BELOW TLV(PEL) USE MSHA/NIOSH APPROVED UNITS. USE UNITS PER CURRENT 29 CFR1910.134 AND FOLLOW MANUFACTURERS? INSTRUCTIONS AND WARNINGS. IF WITHIN O SHA PROTECTION FACTOR, AIR PURIFYING OV/FILTER UNITS OK FOR USE.

Ventilation:LOCAL AND MECHANICAL EXHAUST.

Protective Gloves:RUBBER GLOVES.

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS OR GOGGLES.

Other Protective Equipment:EYE BATH AND SAFETY SHOWER.

Wor

k Hygienic Practices: MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN
CONFINED AREAS WITHOUT ADEQUATE VENTILATION.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt: >126.7C, 260.F

B.P. Text: 260-334 DEG F

Vapor Density: >AIR

Spec Gravity: 1.0

VOC Pounds/Gallon: 400

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: ESSENTIALLY NIL

Appearance and Odor: VISCOUS LIQUID WITH TYPICAL PAINT ODOR.

===== Stabil

ity and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

OXYGEN, HYDROGEN, & PRESENCE OF ALKALIES

Stability Condition to Avoid: HIGH TEMPS, HEAT, RED HEAT & TEMPS. >125F

Hazardous Decomposition Products: OXIDES, AMMONIA CYANIDES, NITRIDES
W/CALCIUM, STRONTIUM & BARIUM

===== Disposal Considerations =====

Waste Disposal Methods: USE INERT ABSORBENT MATERIALS ON SPILLS. DISPOSE
OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL RE
GULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
partic
ular situation.