

MOBIL OIL CORP -- MOBIL DELVAC 1230 -- 9150-00-189-6729

===== Product Identification =====

Product ID:MOBIL DELVAC 1230  
MSDS Date:06/04/2000  
FSC:9150  
NIIN:00-189-6729  
Status Code:A  
MSDS Number: CKZFQ  
=== Responsible Party ===  
Company Name:MOBIL OIL CORP  
Address:3225 GALLOWS RD  
City:FAIRFAX  
State:VA  
ZIP:22037-0001  
Country:US  
Info Phone Num:800-662-4525, 703-849-3451  
Emergency Phone Num:(609) 737-4  
411  
Chemtrec Ind/Phone:(800)424-9300  
CAGE:6G112  
=== Contractor Identification ===  
Company Name:MOBIL OIL CORP  
Address:3225 GALLOWS RD  
Box:City:FAIRFAX  
State:VA  
ZIP:22037  
Country:US  
Phone:800-662-4525, 856-224-4644  
CAGE:6G112

===== Composition/Information on Ingredients =====

Ingred Name:THIS PRODUCT IS NOT FORMULATED TO CONTAIN INGREDIENTS WHICH  
HAVE EXPOSURE LIMITS ESTABLISHED BY U.S. AGENCIES.

===== Hazards Identification =====

Routes

of Entry: Inhalation:NO Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:PRODUCT ASSESSED IN ACCORDANCE WITH  
OSHA 29 CFR 1910.1200 & DETERMINED NOT TO BE HAZARDOUS.  
Effects of Overexposure:NO SIGNIFICANT EFFECTS EXPECTED.

=====  
===== First Aid Measures =====

First Aid:EYE: FLUSH THOROUGHLY WITH WATER. IF IRRITATION OCCURS, CALL  
A PHYSICIAN. SKIN: WASH CONTACT AREAS WITH SOAP AND WATER.  
INHA  
LATION: NOT EXPECTED TO BE A PROBLEM. INGESTION:NOT EXPECTED TO  
BE A PROBLEM .

=====  
===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:>216.C, 420.8F  
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL AND WATER FOG.  
Fire Fighting Procedures:WATER OR FOAM MAY CAUSE FROTHING. USE WATER TO  
KEEP FIRE EXPOSED CONTAINERS COOL. WATER SPRAY MAY BE USED TO FLUSH  
SPILLS AWAY FROM EXPOSURE. PREVENT RUNOFF FROM FIRE CONTROL OR  
DILUTION FR  
OM ENTERING STREAMS, SEWERS, OR DRINKING WATER SUPPLY.  
FOR FIRES IN ENCLOSED AREAS, FIRE FIGHTERS MUST USE SCBA.  
Unusual Fire/Explosion Hazard:NONE. HAZARDOUS DECOMPOSITION PRODUCTS:  
CARBON MONOXIDE. METAL OXIDES. ELEMENTAL OXIDES.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:ABSORB ON FIRE RETARDANT TREATED SAWDUST,  
DIATOMACEOUS EARTH, ETC. SHOVEL UP AND DISPOSE OF AT AN APPROPRIATE  
WASTE DISPOSAL FACILITY IN ACCORDANCE WITH CUR  
RENT APPLICABLE LAWS  
AND REGULATIONS, AND PR ODUCT CHARACTERISTICS AT TIME OF DISPOSAL.  
PREVENT SPILL FROM ENTERING STORM SEWERS OR DRAINS AND CONTACT WITH  
SOIL.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:AVOID BREATHING VAPORS & MIST. AVOID  
CONTACT WITH EYES. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.  
WASH THOROUGHLY AFTER HANDLING. WASH CONTAMINATED CLOTHING PRIOR TO  
REUSE.  
Other Precautions:REPORT SPILLS A

S REQUIRED TO APPROPRIATE AUTHORITIES.

U.S. COAST GUARD REGULATIONS REQUIRE IMMEDIATE REPORTING OF SPILLS THAT COULD REACH ANY WATERWAY INCLUDING INTERMITTENT DRY CREEKS. REPORT SPILLS TO COAST GUARD TOLL FREE NUMBER (800) 424-8802. IN CASE OF ACCIDENT OR ROAD SPILL NOTIFY CHEMTREC (8 00) 424-9300.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION

Ventilation:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.

Protective Gloves:NO SPECIAL EQUIPMENT REQUIRED.

Eye Protection:NORMAL INDUSTRIAL EYE PROTECTION PRACTICES SHOULD BE EMPLOYED.

Work Hygienic Practices:GOOD PERSONAL HYGIENE PRACTICES SHOULD ALWAYS BE FOLLOWED.

Supplemental Safety and Health

PRODUCT CODE: 440677-00.

=====  
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:>316.C, 600.8F

Vapor Pres: