

ABM MARKETING LTD -- ABM SPRAY INK -- 7510-00-419-9564

=====
Product Identification
=====

Product ID:ABM SPRAY INK
MSDS Date:04/01/1995
FSC:7510
NIIN:00-419-9564
Status Code:A
MSDS Number: CLBDR
=== Responsible Party ===
Company Name:ABM MARKETING LTD
Address:2799 SOUTH BELT WEST
City:BELLEVILLE
State:IL
ZIP:62223
Country:US
Info Phone Num:618-277-3773
Emergency Phone Num:000000000
CAGE:0FHG6

=====
Contractor Identification ====
Company Name:ABM MARKING CO
Address:2799 S BELT W
Box:City:BELLEVILLE
State:IL
ZIP:62223
Country:US
Phone:618-277-3773
CAGE:0FHG6

=====
Composition/Information on Ingredients
=====

Ingred Name:TERPINEOL
CAS:8000-41-7
= Wt:4.

Ingred Name:N-BUTYL ACETATE
CAS:123-86-4
RTECS #:AF7350000
= Wt:4.
OSHA PEL:150 PPM
ACGIH TLV:150 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUOL
CAS:108-88-3
RTECS #:XS5250000
= Wt:40.
OSHA PEL:100 PPM
EP

A Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLOL
CAS:1330-20-7
RTECS #:ZE2100000
= Wt:4.
OSHA PEL:100 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE
CAS:67-64-1
RTECS #:AL3150000
= Wt:34.
OSHA PEL:1000 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
= Wt:20.
OSHA PEL:1000 PPM

Ingred Name:ISOBUTANE
CAS:75-28-5
RTECS #:TI4300000
= Wt:5.
OSHA PEL:800 PPM

Ingred Name:BUTANE
CAS:106-97-8
RTECS #:EJ4200000
= Wt:7.
OSHA PEL:
L:800 PPM

=====
===== Hazards Identification =====

Health Hazards Acute and Chronic:INHALATION: EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, HEADACHE AND POSSIBLE UNCONSCIOUSNESS. INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. SKIN: PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, DRYING AND CRACKING MAY OCCUR. EYE: CAN CAUSE IRRITATION, REDNESS

, TEARING AND BLURRED VISION.

Effects of Overexposure:CONTINUED OVEREXPOSURE MAY PRODUCE UNCONSCIOUSNESS, KIDNEY DAMAGE AND DEATH. CONTACT WITH LUNGS CAN RESULT IN CHEMICAL PNEUMONATIS AND PULMONARY EDEMA/HEMORRAGE.

Medical Cond Aggravated by Exposure:PREEXISTING SENSITIVILY TO SOLVENTS CAN CAUSE A HEIGHTENED REACTION TO EXPOSURE TO THIS PRODUCT CAUSES IMPAIRMENT TO KIDNEYS AND LIVER WITH PERMENT BRAIN AND NERVOUS SYSTEM DAMAGE.

=====
=====
First Aid Measures =

First Aid:INHALATION: REMOVE INDIVIDUAL TO FRESH AIR, IF BREATHING IS DIFFICULT ADMINISTER OXYGEN. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY. SKIN: REMOVE CONTAMINATED CLOTHING THOROUGHLY WASH EXPOSED AREA WITH SOAP AND WATER. EYES: IMMEDIATELY FLUSH WITH LARGE AMOUNT OF WATER AND GET MEDICAL ATTENTION.

=====
=====
Fire Fighting Measures =====

Lower Limits:1.8

Upper Limits:9.5

Ext

inguishing Media: DRY CHEMICAL, FOAM CARBON DIOXIDE

Fire Fighting Procedures:WEAR POSITIVE PRESSURE SCBA

=====
=====
Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SORTS OF IGNITION PROVIDE ADEQUATE VENTILATION SOAK UP WITH ABSORBENT MATERIAL AND COLLECT FOR DISPOSAL. HANDLING EQUIPMENT MUST BE GROUNDED TO PREVENT SPARKING.

=====
=====
Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AB

OVE 120 F

Other Precautions:DO NOT TAKE INTERNALLY.

=====
=====
Exposure Controls/Personal Protection =====

Respiratory Protection:PROOVISE ADEQUATE VENTILATION. USE OF NIOSH/OSHA APPROVED RESPIRATORS SUITABLE FOR MATERIAL

Protective Gloves:SOLVENT RESISTANT NEOPRENE OR POLYETHLENE

Eye Protection:CHEMICAL GOGGLES WHEN NEEDED.

Supplemental Safety and Health

=====
=====
Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F/100C

Vapor Density:< AIR

p

H:8.59.5

Evaporation Rate & Reference:SLOWER THAN AIR

Solubility in Water:COMPLETE

Appearance and Odor:THICK LIQUID, WHITE & VARIOUS COLORS, SLIGHT AMMONIA ODOR

Percent Volatiles by Volume:59.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:VERY STRONG OXIDIZING AGENTS, SOURCES OF IGNITION, EXCESSIVE HEAT (OVER 110 F)

===== Disposal Considerations =====

Was

te Disposal Methods:SANITARY LANDFILL OR INCINERATE ACCORDING TO LOCAL STATE AND FEDERAL REGULATIONS. PLACE CONTAMINATED ITEM IN SUITABLE CONTAINER FOR DISPOSAL. PLACE IN DISPOSAL FACILITY APPROVED UNDER RCRA REGULATIONS FOR HAZARDOUS WASTE, USE NON LEAKING TIGHT CONTAINERS, SEAL AND LABEL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.