

ASHLAND CHEMICAL CO., ASHLAND OIL DIV. -- 7432802, TECTYL 802 A -- 9150-00-271-8427

=====
Product Identification
=====

Product ID:7432802, TECTYL 802 A

MSDS Date:06/10/1997

FSC:9150

NIIN:00-271-8427

Status Code:A

MSDS Number: CLBDX

=== Responsible Party ===

Company Name:ASHLAND CHEMICAL CO., ASHLAND OIL DIV.

Address:P.O. BOX 2219

Box:2219

City:COLUMBUS

State:OH

ZIP:43216

Info Phone Num:606-324-11

33

Emergency Phone Num:800-274-5263

Resp. Party Other MSDS Num.:506.0001461-008.009

CAGE:DO048

=== Contractor Identification ===

Company Name:ASHLAND CHEMICAL CO., ASHLAND OIL DIV.

Address:P.O. BOX 2219

Box:2219

City:COLUMBUS

State:OH

ZIP:43216

Phone:606-324-1133

CAGE:DO048

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC PETROLEUM DISTILLATES

CAS:64742-52-5

RTECS #:PY8035000

Minumum % Wt:80.

Maxumum % Wt:90.

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3

Ingred

Name:ORGANIC SALT
Minumum % Wt:2.6
Maxumum % Wt:13.
OSHA PEL:NONE ESTABLISHED
ACGIH TLV:NONE ESTABLISHED

Ingred Name:WOOL GREASE
CAS:8020-84-6
Minumum % Wt:2.1
Maxumum % Wt:12.
OSHA PEL:NONE ESTABLISHED
ACGIH TLV:NONE ESTABLISHED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NO DATA PROVIDED BY MANUFACTURER
Health Hazards Acute and Chronic:EYE: MAY CAUSE MILD EYE IRRITATION.
SKIN: CAN CAUSE SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY
DR
Y SKIN. SWALLOWING: SWALLOWING SMALL AMOUNTS OF THIS MATERIAL
DURING NORMAL HANDLING IS NOT LI KELY TO CAUSE HARMFUL EFFECTS.
SWALLOWING LARGE AMOUNTS MAY BE HARMFUL. THIS MATERIAL CAN ENTER
THE LUNGS DURING SWALLOWING OR VOMITING AND CAUSE LUNG INFLAMMATION
AND/OR DAMAGE. INHALTION: BREATHING OF VAPOR OR MIST IS POSSIBLE.
Explanation of Carcinogenicity:NO DATA.
Effects of Overexposure:EYE: STINGING, TEARING AND REDNESS. SKIN:
REDNESS, BURNING, DRYING AND CRACKING OF SKIN, B
URNS AND OTHER SKIN
DAMAGE. ALLERGIC SKIN REACTION, BLISTERING, SCALING AND OTHER SKIN
EFFECTS. SYMPTONS OF E XPOSURE: STOMACH OR INTESTINAL UPSET
(NAUSEA, VOMITING, DAIRRHEA), IRRITATION (NOSE, THROAT AND
AIRWAYS).
Medical Cond Aggravated by Exposure:NO DATA PROVIDED BY MANUFACTURER

=====
===== First Aid Measures =====

First Aid:EYES: REMOVE FROM EXPOSURE & INTO FRESH AIR. FLUSH WITH WATER
WHILE HOLDING LIDS APART. IF SYMPTOMS PERSISTS OR T
HERE IS ANY
VISUAL DIFFICULTY, SEEK MEDICAL ATTENTION. SKIN: REMOVE
CONTAMINATED CLOTHI NG. WASH WITH SOAP AND WATER. IF SYMPTOMS
PERSIST, SEEK MEDICAL ATTENTION. LAUNDER CLOTHING BEFORE REUSE.
SWALLOWING: DO NOT INDUCE VOMITING. THIS MATERIAL IS AN ASPIRATION
HAZARD. IF INDIVIDUAL IS DR OWSY OR UNCONSCIOUS, PLACE ON LEFT SIDE
WITH THE HEAD DOWN. SEEK MEDICAL ATTENTION. DO NOT LEAVE
INDIVIDUAL UNATTENDED. INHALATION: MOVE INDIVIDUAL AWAY FROM
EXPOSURE & INTO FRES

H AIR. RESTORE BREATH ING. GET IMMEDIATE
MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:=165.6C, 330.F

Autoignition Temp:Autoignition Temp Text:NO DAT

Lower Limits:NO DATA

Upper Limits:NO DATA

Extinguishing Media:REGULAR FOAM, CARBON DIOXIDE, DRY CHEMICAL

Fire Fighting Procedures:WATER OR FOAM MAY CAUSE FROTHING WHICH CAN BE
VIOLENT AND POSSIBLY ENDANGER THE LIFE OR THE FIREFIGHTER. WEAR A
SELF-CONTAINED B

REATHING APPARATUS WITH A FULL FACEPIECE OPERATED

IN POSITIVE PRESSURE D EMAND MODE WITH APPROPRIATE TURN-OUT GEAR
AND CHEMICAL RESISTANT PERSONAL PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard:NEVER USE WELDING OR CUTTING TORCH ON OR
NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN
IGNITE EXPLOSIVELY. DENSE SMOKE MAY BE GENERATED WHILE BURNING.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL: ABSORB LIQUID O

N VERMICLITE, FLOOR

ABSORBENT OR OTHE ABSORBENT MATERIAL. LARGE: PREVENT RUNOFF TO
SEWERS, STREAMS OR OTHER BODIES OF WATER. IF RUNOFF OCCURS, NOTIFY
AUTHORITIES. STOP SPILL AT S OURCE. DIKE AREA TO PREVENT SPREADING,
PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID MAY BE TAKEN UP ON
SAND, CLAY, EARTH FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND
SHOVEL INTO CONTAINERS.

Neutralizing Agent:NO DATA PROVIDED BY MANUFACTURER

===== Handling and Storage ==

=====

Handling and Storage Precautions:CONTAINERS OF THIS MATERIAL MAY BE
HAZARDOUS WHEN EMPTIED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT
RESIDUES (VAPOR, LIQUID, AND/OR SOLID), ALL HAZARD PRECAUTIONS
GIVEN IN DATA SHEET MUST BE OBSERVED.

Other Precautions:NOT APPLICABLE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURE LIMIT IS EXCEEDED, WEAR A NIOSH/MSHA
APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE

OF PROPER

ENVIRONMENTAL CONTROL. OSHA REGULATIONS ALSO PERMIT OTHER NIOSH/MSHA RESPIRATORS ((NEG ATIVE PRESSURE TYPE) UNDER SPECIFIED CONDITIONS (CONSULT INDUSTRIAL HYGIENIST). ENGINEERING OR ADMINISTRATIVE CONTROLS SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.

Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves:RESISTANT GLOVES NEOPRENE

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equi

ment:TO PREVENT REPEATED OR PROLONGED SKIN CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS.

Work Hygienic Practices:REMOVE CONTAMINATED CLOTHING. LAUNDER CONTAMINATED CLOTHING.

Supplemental Safety and Health
INO DATA PROVIDED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:>287.8C, 550.F

Vapor Pres:1.000

Evaporation Rate & Reference: