

RAABE CORPORATION -- AEROSOL PAINT -- 7510-00-469-7910

=====
Product Identification
=====

Product ID:AEROSOL PAINT

MSDS Date:05/13/1986

FSC:7510

NIIN:00-469-7910

Status Code:A

MSDS Number: CLBJT

=== Responsible Party ===

Company Name:RAABE CORPORATION

Box:1090

City:MENOMONEE FALLS

State:WI

ZIP:53052

Country:US

Info Phone Num:414-255-9500

Emergency Phone Num:0000000000

CAGE:0A3L4

=== Contractor Id

entification ===

Company Name:RAABE CORPORATION THE PRECISION COLOR COMPANY

Address:N92 W14701 ANTHONY AVE.

Box:1090

City:MENOMONEE FALLS

State:WI

ZIP:53051-1630

Country:US

Phone:414-255-9500/800-966-7580

CAGE:0A3L4

=====
Composition/Information on Ingredients
=====

Ingred Name:PROPANE

CAS:74-98-6

RTECS #:TX2275000

= Wt:16.

ACGIH TLV:1000 PPM

Ingred Name:ISOBUTANE

CAS:75-28-5

RTECS #:TI4300000

< Wt:5.

ACGIH TLV:800 PPM

Ingred Name:N-BUTANE

CAS:106-97-8

RTECS #:EJ4200000

< Wt:5.

Ingred Name:TOLUENE

CAS:108-88-3

RTECS #:XS5250000

Minumum % Wt:29.

Maxumum % Wt:35.

ACGIH TLV:375 MG/M3 100 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE

CAS:67-64-1

RTECS #:AL3150000

Minumum % Wt:9.

Maxumum % Wt:18.

ACGIH TLV:1780 MG/M3;750 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE

CAS:1330-20-7

RTECS #:ZE2100000

= Wt:3.

ACGIH TLV:434 MG/M3;100 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYLENE CHLORIDE

CAS:75-09-2

RTEC

S #:PA8050000

Minumum % Wt:10.

Maxumum % Wt:15.

ACGIH TLV:100 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Health Hazards Acute and Chronic:SEVERE INHALATION: HIGH CONCENTRATIONS OF VAPORS ARE ANESTHETIC, WILL IRRITATE THE RESPIRATORY TRACT AND CAN CAUSE NSD CHARACTERIZED BY DROWSINESS, LIGHTHEADEDNESS, HEADACHES, DIZZINESS, STAGGERING, C ONFUSION, UNCONSIIOUSNESS AOR COMA. SKIN CONTACT: PRIMARY IRRTANT. EYE C

ONTACT: PRIMARY IRRITANT.

Effects of Overexposure:REPORTS HAVE SHOWN REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMENT BRAIN AND NERVOUS SYSTEM DAMAGE.

=====
===== First Aid Measures =====

First Aid:FUMES: REMOVE FROM EXPOSURE TO FRESH AIR, APPLY ARTIFICIAL RESPIRATION IF NECESSARY, ADMINISTER OXYGEN IF NECESSARY. CALL PHYSICIAN IMMEDIATELY. SPRAY EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. CALL PHYSICIAN IMMEDIATELY.
SPLASH SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. ORAL INGESTION: DO NOT INDUCE VOMITING . CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:TOC
Flash Point:=-31.5C, -25.F
-25 DEG F
Lower Limits:.9
Upper Limits:12.8
Extinguishing Media:NFBA CLASS B EXTINGUISHERS (CARBON DIOXIDE, DRY CHEMICAL OR FOAM)
Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT INCLUDING SCBA

SHOULD BE USED. WATER SPRAY MAY BE INEFFECTIVE, BUT MAY BE USED TO KEEP DOWN VAPORS OR TO COOL CLOSED CONTAINERS TO PREVENT BUILD-UP OF PRESSURE AND POSSIBLE EXPLOSION OR AUTOIGNITION. IF WATER IS USED, FOG NOZZLES ARE PREFERRED.

Unusual Fire/Explosion Hazard:DO NOT USE OR STORE NEAR HEAT, SPARKS OR OPEN FLAME. DO NOT SMOKE. DO NOT PUNCTURE IN ANY MANNER. DO NOT INCINERATE. DO NOT CRUSH. DO NOT STORE ABOVE 120 DEGREES F. KEEP AWAY FROM ANY SOURCES OF HEAT SUCH AS SUNLIGHT, RADIATORS, STOVES, HOT WATER OR ANY OTHER SOURCE OF HEAT THAT COULD CAUSE CONTAINER TO HEAT AND BURST.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA OF SPILL AND ADJACENT LOW LYING AREAS. REMOVE WITH INERT ABSORBENT AND NON SPARKING TOOLS. WASTE DISPOSAL METHOD: DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

=====

===== **Handling and Storage**=====

Handling and Storage Precautions:DO NOT STORE AT TEMPATURES ABOVE 120 DEGREES F. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. DO NOT PUNCTURE. KEEP OUT OF THE REACH OF CHILDREN.

Other Precautions:USE ONLY AROUND EXPLOSION PROOF EQUIPMENT. AVOID PROLONGED BREATHING OF VAPORS. AVOID CONTACT WITH SKIN. DO NOT TAKE INTERNALLY. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTE NTS OF THE AERSOL CAN BE HARMFUL OR FATAL.

===== **Exposure Controls/Personal Protection**=====

Respiratory Protection:USE A BREAU OF MINES APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICULES OF OVERSPRAY DURING SPRAY APPLICATION.

Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP TLV OF MOST HAZARDOUS INGREDIENTS BELLOS TLV.

Eye Protection:CHEMICAL SAFTEY GOGGLES DESIGNED TO BE SPLASH PROOF.

Supplemental Safety and H
ealth

===== **Physical/Chemical Properties**=====

Vapor Density:+AIR

Evaporation Rate & Reference:BUTYL ACETATE SLOWER

Solubility in Water:NEGLIGABLE

Appearance and Odor:USUALLY HAS COLOR SOLVENT ODOR

===== **Stability and Reactivity Data**=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Hazardous Decomposition Products:BY OPEN FLAME CARBON MONOXIDE AND CARBON DIOXIDE.

===== **MSDS Transport Informa
tion**=====

Transport Information:D.O.T. SHIPPING INFORMATION: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (ZINC CHLORIDE, AMMONIUM CHLORIDE) SOLUTION, 8, UN3264, PG II.

===== **Regulatory Information**=====

Federal Regulatory Information:THIS PRODUCT IS LISTED IN THE TSCA INVENTORY.

State Regulatory Information:

===== **Other Information**=====

Disclaimer (provided with this information by the comp

iling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.