

PELIKAN AG -- DRAWING INK 9065, BLACK -- 7510-01-017-6069

===== Product Identification =====

Product ID: DRAWING INK 9065, BLACK

MSDS Date: 05/27/1988

FSC: 7510

NIIN: 01-017-6069

Status Code: A

MSDS Number: CLBKL

=== Responsible Party ===

Company Name: PELIKAN AG

Address: POBBIELDSKISTRASSE 141 POSTFACH 103

City: 3000 HANOVER 1

Country: GE

Info Phone Num: 0511-6969214

Emergency Phone Num: 0000000000

CAGE: D81

05

=== Contractor Identification ===

Company Name: PELIKAN AG

Address: POBBIELDSKISTRASSE 141 POSTFACH 103

Box: City: 3000 HANOVER 1

Country: GE

Phone: 0511-6969214

CAGE: D8105

===== Composition/Information on Ingredients =====

Ingred Name: PHENOL

CAS: 108-95-2

RTECS #: SJ3325000

= Wt: .7

OSHA PEL: 5 PPM

ACGIH TLV: 5 PPM

EPA Rpt Qty: 1000 LBS

DOT Rpt Qty: 1000 LBS

Ingred Name: SODIUM TETRABORATE DECAHYDRATE

CAS: 1303-96-4

RTECS #: VZ2275000

= Wt: 1.5

ACGIH TLV: 5 MG/M3

===== H

azards Identification =====

Medical Cond Aggravated by Exposure:

===== First Aid Measures =====

First Aid:EYE CONTACT: RINSE WITH WATER

===== Fire Fighting Measures =====

Extinguishing Media:NONE SPECIFIED BY MANUFACTURER.

Fire Fighting Procedures:IN CASE OF FIRE, CONTAINER SHOULD BE KEPT COOL TO AVOID EXCESSIVE PRESSURE.

Unusual Fire/Explosion Hazard:SUPPORT COMBUSTION. IF POSSIBLE, SHUT OFF SU

PPLY. DECOMPOSES AT ELEVATED TEMPERATURE. PRESSURE CAN BUILD UP DUE TO HEAT. CYLINDER MAY EXPLODE IF VALVUES FAILS.

===== Accidental Release Measures =====

Spill Release Procedures:SPILL AWAY WITH WATER

===== Handling and Storage =====

Handling and Storage Precautions:BEWARE OF FROST

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS WHERE NEEDED. Ve

ntilation:LOCAL EXHAUST RECOMMENDED.

Protective Gloves:LEATHER OR NEOPRENE.

Eye Protection:SAFETY GOGGLES OR GLASSES.

Other Protective Equipment:SAFETY SHOES WHEN HANDLING CYLINDERS.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

CYLINDERS MUST NOT BE RECHARGED UNLESS BY OR WITH THE CONSENT OF PURITAN-BENNETT CORPORATION.

===== Physical/Chemical Properties =====

Boiling Pt:=100.C, 212.F

B.P. Text:100C

Vapor Pres:CA 18

Spec

Gravity:1.05
Solubility in Water:MISCIBLE EXCEPT PIGMENT
Appearance and Odor:BLACK LIQUID TECHNICAL OSOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:ACCORDING TO LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense.
The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.