

ITW FLUID PRODUCTS GROUP -- RUSTLICK 606 LONG TERM RUST PREVENTATIVE --
6850-00-066-2333

===== Product Identification =====

Product ID:RUSTLICK 606 LONG TERM RUST PREVENTATIVE

MSDS Date:07/31/1999

FSC:6850

NIIN:00-066-2333

Status Code:A

MSDS Number: CLCZM

=== Responsible Party ===

Company Name:ITW FLUID PRODUCTS GROUP

Address:3624 WEST LAKE AVENUE

City:GLENVIEW

State:IL

ZIP:60025

Country:US

Info

Phone Num:800-452-5823

Emergency Phone Num:(800) 424-9300

Preparer's Name:DEBBIE MAKITA

Chemtrec Ind/Phone:(800)424-9300

CAGE:TO249

=== Contractor Identification ===

Company Name:GOURMET INQUE LTD

Address:191 STANLEY ST

Box:City:ELK GROVE VILLAGE

State:IL

ZIP:60007-1555

Country:US

Phone:847-296-6192/FAX: 800-542-1042

Contract Num:SP0450-01-M-ZC09

CAGE:0TNN7

Company Name:ITW FLUID PRODUCTS GROUP

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL

ZIP:60025

Country:US

Phone:800-452-5823

CAGE:

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM HYDROCARBON
CAS:64742-47-8
RTECS #:OA5504000
Minumum % Wt:71.
Maxumum % Wt:90.

Ingred Name:HEXYLENE GLYCOL
CAS:107-41-5
RTECS #:SA0810000
Minumum % Wt:1.
Maxumum % Wt:5.
ACGIH STEL:C121 MG/M3;C25 PPM

=====
Hazards Identification
=====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: SLIGHT IRRITATION. CHRONIC:
EFFE
CTS ARE NOT KNOWN.
Explanation of Carcinogenicity:ACGIH CARCINOGENICITY: NO.
Effects of Overexposure:INHALATION: HIGH CONCENTRATIONS OF VAPORS MAY
PRODUCE IRRITATION OF THE RESPIRATORY TRACT, HEADACHE, DIZZINESS,
AND NAUSEA. SKIN AND EYE: SLIGHT IRRITATION. SKIN ABSORPTION:
SLIGHT IRRITANT. INGESTION : NO DATA.
Medical Cond Aggravated by Exposure:SKIN DISORDERS.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH WELL WITH WATER. CONTACT A PHY
SICIAN IF
IRRITATION PERSISTS. SKIN: WASH WITH SOAP AND WATER. INHALATION: NO
EMERGENCY CARE ANTICIPATED UNDER NORMAL CONDITIONS. INGESTION: DO
NOT INDUCE VOM ITING. CONTACT A PHYSICIAN. IF VOMITING OCCURS, KEEP
HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO LUNGS.

=====
Fire Fighting Measures
=====

Flash Point Method:PMCC
Flash Point:=79.4C, 175.F
Lower Limits:1.2%
Upper Limits:8.8%
Extinguishing Media:CO2, DRY CHEMICAL, FOAM.
Fire Fight

ing Procedures:FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS IN CONFINED AREAS.

Unusual Fire/Explosion Hazard:NONE.

===== Accidental Release Measures =====

Spill Release Procedures:PREVENT SKIN AND EYE CONTACT. USE NON-COMBUSTIBLE MATERIAL TO CONFINE AND /OR ABSORB. ELIMINATE IGNITION SOURCES. VENTILATE AREA.

===== Handling and Storage =====

Handling and Storage Precautions:IF MISTS ARE GENERATED IN THE USE OF THIS PRODUCT; THEN THE FOLLOWING VALUES FOR PETROLEUM OILS APPLY:
--ACHIG - TLV/TWA = 5 MG/M3/8HR ---OSHA - PEL/TWA =5 MG/M3/8HR
---ACGIH - TLV/STEL = 10 MG/M3. IF MIST LEVELS EXCEED THESE VALUES, THEN A RESPIRATOR SHOULD BE WORN TO PROVIDE PROTECTION TO WORKERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED AT NORMAL HANDLING TEMPERATURES.
Ventilation:LOCAL EXHAUST VENTILATION IS RECOMMENDED FOR CONFINED

AREAS. GENERAL MECHANICAL VENTILATION IS ADEQUATE FOR NORMAL USE.

Protective Gloves:CHEMICAL RESISTANT RUBBER GLOVES, SUCH AS POLYVINYL CHLORIDE-COATED

Eye Protection:SAFETY GLASSES. SPLASH PROOF GOGGLES.

Other Protective Equipment:EYE BATH AND SAFETY SHOWER. OTHER PROTECTIVE GEAR AS REQUIRED TO MINIMIZE SKIN CONTACT.

Work Hygienic Practices:FOLLOW H.M.I.S. REGULATIONS.

Supplemental Safety and Health

FINISHED GOODS: 5 GAL = 71052, 55 GAL = 71552.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:=100.C, 212.F

Vapor Density:>1

Spec Gravity:0.83

Evaporation Rate & Reference: