

FARWEST PAINT MANUFACTURING CO -- SILICONE ALKYD COPOLYMER ENAMEL #27875 WHITE --
8010-01-344-5322

=====
Product Identification
=====

Product ID:SILICONE ALKYD COPOLYMER ENAMEL #27875 WHITE

MSDS Date:03/01/1997

FSC:8010

NIIN:01-344-5322

Status Code:A

MSDS Number: CLFGR

=== Responsible Party ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

City:TUKWILA

State:WA

ZIP:98168

Country:US

Info Phone Num:206-244-8844

Emergency Phone Num:800-277-9694

Preparer's Name:HENRY SIMMONS

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS 350

= Wt:31.75

=====
Hazards Identification
=====

Reports of Carcino

genicity:NTP:NO IARC:NO OSHA:NO

Effects of Overexposure:SKIN: THIS MATERIAL MAY CAUSE IRRITATION, SENSITIZATION, OR DEFATTING OF SKIN UPON PROLONGED OR REPEATED CONTACT. INHALATION: EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MIST CAN RESULT IN HEADACHE, DIZZINE SS, NAUSEA AND LOSS OF CONSCIOUSNESS. SOME REPORTS HAVE ASSOCIATED REPATED & PROLONGED OCCUPATIONAL OVEREXPOPSURE TO SOLVENTS WITH PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. EYES: THIS MATERIAL MAY BE A N EYE IRRITANT.

Medical Cond Aggravated by Exposure:NONE; WHEN USED IN ACCORDANCE WITH SAFE HANDLING INSTRUCTIONS.(SEE SECTION VIII)

===== First Aid Measures =====

First Aid:SKIN: PROMPTLY WAS WITH SOAP AND WATER, REMOVE AND WASH ANY CONTAINIMATED CLOTHING BEFORE REUSE EYES: FLUSH WITH LARGE QUANTITIES OF WATER FOR 15 MINUTES AND SEEK MEDICAL ATTENTION SWALLOWING: IF I NJESTED DO NOT INDUCE VOMITING: KEEP PERSON WARM AND QUIET AND GET MEDICAL ATTEN TION. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUNITIS WHICH CAN BE FATAL. INHALATION: REMOVE VICTIM TO F RESH AIR IMMEDIATELY. IF RESPIRATORY SYMPTONS DEVELOP, SEEK MEDICAL ATTENTION AT ONCE.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:=-41.7C, 107.F

Lower Limits:0.7

Upper Limits:6.0

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, OR WATER FOG. USE THE ABOVE OR ANY CLASS B EXTINGUISHING AGENT. WATER MAY BE UNSUITABLE

AS AN EXTINGUISHING MEDIUM.

Fire Fighting Procedures:FIREFIGHTERS AND OTHER EXPOSED TO VAPORS OR PRODUCTS OF COMBUSTION SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS. EVACUATE AREA OF UNPROTECTED PERSONNEL. WEAR PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN AIR MAY BE IGNITED BY SPARKS, PILOT LIGHT, ETC. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures ===

=====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION VENTILATE AREA. ABSORB SPILL WITH AN ABSORBENT MATERIAL SUCH AS SAWDUST, VERMICULITE OR SAND AND PLACE MATERIAL INTO A CLOSED CONTAINER. IF LARGE SPILL, DIKE AREA TO PREVENT THIS MATERIAL FROM ENTERING WATER SYSTEMS OR SEWERS. WEAR PROTECTIVE EQUIPMENT DURING CLEANUP.

===== Handling and Storage =====

Handling and Storage Precautions: AVOID PROLONG OR REPEATED INHALATION OF HEATED VAPORS OR SPRAY MIST. KEEP AWAY FROM HEAT OR OPEN FLAME. THIS MATERIAL MAY CAUSE SENSITIZATION. DO NOT GET INTO EYES, ON SKIN OR CLOTHING. DO NOT ALLOW CONTAMINATED CLOTHING TO CONTACT SKIN. DO NOT WELD ON FULL OR EMPTY CONTAINERS. KEEP CONTAINERS CLOSED

===== Exposure Controls/Personal Protection =====

Respiratory Protection: A CANISTER TYPE RESPIRATOR MUST BE WORN TO PREVENT THE INHALATION OF VAPORS OR SPRAY MIST WHEN THE TLV OR PEL IS EXCEEDED

D.

Ventilation: GENERAL VENTILATION IS REQUIRED DURING NORMAL USE. LOCAL VENTILATION MAY BE REQUIRED DURING CERTAIN OPERATIONS TO KEEP EXPOSURE LEVEL BELOW THE LIMITS.

Protective Gloves: CHEMICAL RESISTANT NITRILE, NEOPREN OR RUBBER GLOVES REQUIRED.

Eye Protection: WEAR FACE SHIELD OR CHEMICAL GOGGLES.

Other Protective Equipment: WEAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT. EYE WASH STATION AND SAFETY SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices: WASH HANDS BEFORE EATING OR SMOKING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt: =152.8C, 307.F

B.P. Text: 307-387F

Vapor Pres: 2.6MMHG@20C

Vapor Density: >AIR

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: NIL

Appearance and Odor: WHITE LIQUID, MILD ODOR.

Percent Volatiles by Volume: 45

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
AVOID CONTACT WITH STRONG OXIDANTS.

ACIDS. BASES AND EPOXY HARDENERS
UNDER UNCONTROLLED CONDITIONS.

Stability Condition to Avoid:HEAT, SPARKS, & OPEN FLAME. IF PRODUCT
CONTAINS ALLUMINUM. MIOSTURE IN CLOSED CONTAINERS WILL GENERATE
HYDROGEN GAS.

Hazardous Decomposition Products:INCOMPLETE COMBUSTION CAN YIELD CARBON
MONOXIDE AND TOXIC VAPORS.

=====
===== Toxicological Information =====

Toxicological Information:NA

=====
===== Ecological Information =====

Ecolog
ical:AVOID DISCHARGE TO NATURAL WATERS.

=====
===== Disposal Considerations =====

Waste Disposal Methods:WASTE DISPOSAL METHOD: IF DISCARDED, THIS
MATERIAL AND CONTAINERS SHOULD BE TREATED AS HAZARDOUS WASTE BASED
ON THE CHARACTERISTICS OF IGNITABILTY AS DEFINED UNDER FEDERAL RCRA
REGULATIONS (40 CFR 261). DISPOSAL OF THIS MATERIAL OR ITS
CONTAINERS REQUIRES COMPLIANCE WITH APPLICABLE, PACKGED AND RECO
RDKEEPING STANDARDS

=====
===== R
egulatory Information =====

SARA Title III Information:PURSUANT TO TITTLE THREE OF THE SUPERFUND
AMMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA) AND 40 CFR PART
372, THIS PRODUCT CONTAINS, OR MAY CONTAIN A TOXIC CHEMICAL IN THE
QUANTITY SUBJECT TO THE R EPORTING REQUIREMENTS UNDER SECTION 313.

Federal Regulatory Information:US POSTAL REGULATIONS: NON-HAZARDOUS,
NON-FLAMMABLE, OKAY TO SHIP BY MAIL.

=====
===== Other Information =====
=====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular

situation.