

GE SILICONES -- DBT STANNANE, DIBUTYL BIS{ (1-OXODODECYL), (SEE SUPPL.) --  
5970-00-832-8028

===== Product Identification =====

Product ID:DBT STANNANE, DIBUTYL BIS{ (1-OXODODECYL), (SEE SUPPL.)

MSDS Date:10/23/1996

FSC:5970

NIIN:00-832-8028

Status Code:A

Kit Part:Y

MSDS Number: CLFLK

=== Responsible Party ===

Company Name:GE SILICONES

Address:260 HUDSON RIVER ROAD

City:WATERFORD

State:NY

ZIP:12188

Country:US

Info Phone Num:518-237-3330

Emergency Phone Num:518-237-3330

Preparer's Name:CE HANNIGAN

CAGE:IO364

=== Contractor Identification ===

Company Name:GE SILICONES

Address:260 HUDSON RIVER ROAD

Box:City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330

CAGE:IO364

Company Name:THE SMITH GROUP INC.

Address:811 E. CAYUGA STREET

Box:City:PHILADELPHIA

State:PA

ZIP:19124-3893

Country:US

Phone:215-743-8200

Contract Num:SP0430-99-M-Y055

CAGE:2B613

===== Composition/Information

on Ingredients =====

Ingred Name:DIBUTYLTIN DILAURATE  
CAS:77-58-7  
RTECS #:WH7000000  
Minumum % Wt:80.  
Maxumum % Wt:99.  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:0.1 MG/M3  
ACGIH TLV:0.1 MG/M3

Ingred Name:NON-HAZARDOUS

===== Hazards Identification =====

LD50 LC50 Mixture:LD50: ORAL (RAT): = 1,470 (MG/KG)  
Routes of Entry: Inhalation:UNKNOWN Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:  
INGESTION: HARMFUL IF SWALLOWED. SKIN  
CONTACT: CAUSES MODERATE IRRITATION. HARMFUL IF ABSORBED THRU THE  
SKIN. INHALATION: VAPORS GIVEN OFF BY HEATED PRODUCT MAY BE  
HARMFUL. EYE CONTACT: CAUSES SEVERE EYE IRRITATION. SUBCHRONIC  
(TARGET ORGAN) EFFECTS: CENTRAL NERVOUS SYSTEM DAMAGE.  
Explanation of Carcinogenicity:THIS PRODUCT OR ONE OF ITS INGREDIANTS  
PRESENT 0.1% OR MORE IS NOT LISTED AS A CARCINOGEN OR SUSPECTED  
CARCINOGEN BY NTP, IARC, OR OSHA.  
Effects of Overexposure:S  
KIN CONTACT: IRRITATION. EYE  
CONTACT:IRRITATION. INGESTION: CENTRAL NERVOUS SYSTEM EFFECTS.  
Medical Cond Aggravated by Exposure:CENTRAL NERVOUS SYSTEM DISORDERS

===== First Aid Measures =====

First Aid:INGESTION: DO NOT INDUCE VOMITING. SLOWLY DILUTE WITH 1-2  
GLASSES OF WATER OR MILK AND SEEK MEDICAL ATTENTION. NEVER GIVE  
ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. SKIN: REMOVE  
CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. WASH WITH SOAP  
AND  
WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION:  
MOVE PERSON TO FRESH AIR. EYE: IN CASE OF CONTACT, OR SUSPECTED  
CONTACT, IMMEDIATELY FLUS H EYES WITH PLENTY OF WATER FOR AT LEAST  
15 MINUTES AND GET MEDICAL ATTENTION IMMEDIATELY AFTER FLUSHING.  
NOTE TO PHYSICIAN: NONE KNOWN

===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:=235.C, 455.F  
Autoignition Temp:Autoignition Temp Text:UNKN  
Lower Limits:NA  
Up

per Limits:NA

Extinguishing Media:ALL STANDARD FIREFIGHTING MEDIA.

Fire Fighting Procedures:NONE KNOWN. WEAR RESPIRATORY PROTECTION IF IN A CONFINED AREA.

Unusual Fire/Explosion Hazard:SENSITIVITY TO STATIC DISCHARGE IS NOT EXPECTED. SENSITIVITY TO MECHANICAL IMPACT: NO.

===== Accidental Release Measures =====

Spill Release Procedures:WIPE, SCRAPE, OR SOAK UP SPILL IN AN INERT MATERIAL AND PUT IN A CONTAINER FOR DISPOSAL. WEAR PROPER PROTECTIVE EQUIP

MENT AS SPECIFIED IN THE PROTECTIVE EQUIPMENT SECTION. WARN OTHER WORKERS OF SPILL.

Neutralizing Agent:NOT PROVIDED BY MFR

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE. AVOID CONTACT WITH SKIN AND EYES. WASH HANDS BEFORE EATING AND SMOKING.

Other Precautions:NOT PROVIDED BY MFR.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE KNOWN.

Ventila

tion:USE ONLY IN WELL VENTILATED AREA.

Protective Gloves:RUBBER GLOVES.

Eye Protection:SAFETY GLASSES. MONOGOGGLES.

Other Protective Equipment:EYE WASH STATION, SHOWERS, RUBBER APRON.

Work Hygienic Practices:NOT PROVIDED BY MFR

Supplemental Safety and Health

THIS ENTRY DESCRIBES PART 1, SERIAL NUMBER "CLFLK", DBT STANNANE, DIBUTYL BIS( (1-OXODODECYL), OF A TWO PART KIT. SEE THIS SAME NSN AND SERIAL NUMBER "CLFLS", RTV11 RTV SILICONE RUBBER, FOR KIT PART 2 DATA.

===== Physical/Chemical Properties =====

HCC:V5

Boiling Pt:=204.4C, 400.F

Melt/Freeze Pt:=18.3C, 65.F

Decomp Temp:Decomp Text:NOT PROVIDED BY MFR

Vapor Pres:NEGL.

Vapor Density:21.8(AIR=1

Spec Gravity:1.035 (WATER=1)

VOC Pounds/Gallon:27

pH:NA

Viscosity:NOT PROVIDED BY MFR

Evaporation Rate & Reference:2,000 MG/KG; ACUTE, INHALATION, LC50: NONE FOUND.

===== Ecological Information =====

Ecological:ECOTOXICOLOGICAL INFORMATION: NO DATA AT THIS

TIME. CHEMICAL

FATE INFORMATION: NO DATA AT THIS TIME.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. INCINERATION RECOMMENDED IN APPROVED INCINERATOR ACCORDING TO FEDERAL, STATE, AND LOCAL REGULATIONS.

===== MSDS Transport Information =====

Transport Information:DOT SHIPPING: NOT DOT REGULATED. IATA: NONE; IMO IMDG-CO

DE: NONE; EMS NO: N/A; EUROPEAN CLASS: RID (OCTI): NONE; ADR (ECE): NONE; RAR (IATA): NONE.

===== Regulatory Information =====

SARA Title III Information:SECTION 302: NONE FOUND. SARA 311,312) HAZARD CLASS: ACUTE HEALTH HAZARD, CHRONIC HEALTH HAZARD. SARA (313) CHEMICALS: NONE.

State Regulatory Information:CALIFORNIA PROPOSITION 65: NONE.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.