View NSN Online: https://aerobasegroup.com/nsn/9150-00-179-5144

Product ID:MIL-L-6082, GRADE 1100 (BASE OIL) MSDS Date:03/16/1994 FSC:6650 NIIN:00-179-5144 Status Code:A **MSDS Number: CLGMB** === Responsible Party === Company Name: JOINT OIL ANALYSIS PROGRAM TECHNICAL SUPPORT CENTER(JOAP-TSC Address:296 FARRA **R RD SUITE B** City:PENSACOLA State:FL ZIP:32508-5010 Country:US Info Phone Num:904-452-3191 / 904-452-8448 Emergency Phone Num:904-452-3191 Preparer's Name: DIRECTOR, JOAP-TSC CAGE:UO325 === Contractor Identification === Company Name: JOINT OIL ANALYSIS PROGRAM TECHNICAL SUPPORT CENTER(JOAP-TSC Address:296 FARRAR RD SUITE B Box:City:PENSACOLA State:FL ZIP:32508-5010 Country:US Phone:904-452-3191 / 904-452-8448 CAGE:UO325 Ing red Name: BASE METALS: AG, AL, B, CU, CR, FE, MG, NI, NA, PB, SI, SN, TI, ZN, MO. = Wt:.03 LD50 LC50 Mixture:RAT ORAL LD50: 29000 MG/KG Health Hazards Acute and Chronic: THIS PRODUCT MAY BE IRRITATING TO THE EYES AND MAY CAUSE SLIGHT SKIN IRRITATION. Effects of Overexposure: BECAUSE OF THE LOW LEVEL OF TOXICIT ASSOCIATED WITH THESE SAMPLES, OVEREXPOSURE IS UNLIKELY.

======= First Aid Measures =====

First Aid:REMOVE FROM EXPOSURE SITUATION, WASH EYES 15 MINUTES WITH CLEAR WATER, SEE PHYSICIAN. WASH SKIN WITH SOAP AND WATER. CONSULT PHYSICIAN IF INGESTED. DO NOT INDUCE VOMITING.

Flash Point Method:COC Flash Point:=215.6C, 420.F Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM. Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: TREAT AS AN OIL SPILL. CLEAN WITH TOWEL OR RAG. DISPOSE OF RAG IN TRASH. DO NOT STORE WITH OXIDIZERS. FLOOR MAY BE SLIPPERY. DETERGENT WASH MAY BE REQUIRED.

Handling and Storage Precautions:DO NOT STORE WITH OXIDIZERS. NORMAL GOOD HOUSEKEEPING PROCEDURES.

Other Precautions: EXHAUST SYSTEM SHOULD BE IN PROPER WORKING ORDER TO FURNISH NORMAL WORKPLACE VENTILATION.

==

Respiratory Protection:NOT NORMALLY NEEDED UNLESS OIL MIST OCCURS THEN USE DUST/MIST CARTRIDGE.
Ventilation:NOTHING BEYOND NORMAL VENTILATION.
Protective Gloves:RUBBER GLOVES IF SPILLS LIKELY.
Eye Protection:SAFETY GLASSES ARE RECOMMENDED.
Supplemental Safety and Health
CHEMICAL NAME & SYNONYMS: D12-300, -100, -50, -30, -10, -5, D-19-0, D3-100 OIL STANDARD. SPECIFICATION NUMBER: MIL-L-6082, GRADE 1100

(BAS EOIL). CHEM

ICAL FAMILY: METALLO-ORGANIC SULFONATES & MINERAL OIL. FORMULA: RNC6H5-NSO3M R-ALKYL GROUPS, M-METAL.

HCC:N1 Boiling Pt:B.P. Text:VERY HIGH RANGE Vapor Pres:NIL Vapor Density:UNK Spec Gravity:0.9119 Evaporation Rate & amp; Reference:NIL Solubility in Water:NIL Appearance and Odor:D19-0 IS GOLDEN BROWN, AMBER TO PEALESCENT BLACK COLOR, LUBE OIL ODOR Percent Volatiles by Volume:NIL

Stability Indicator/Materials to Avoid:YES DO NOT MIX WITH STRONG OXIDIZERS. Hazardous Decomposition Products:PARTIALLY BURNED HYDROCARBONS, METAL OXIDES. Conditions to Avoid Polymerization:WILL NOT OCCUR.

Waste Disposal Methods:SMALL SPILL RESIDUES OF THESE PRODUCTS ARE NOT CONSIDERED HAZARDOUS AND MAY E DISCARDED AS TRASH.

=======

Federal Regulatory Information:THIS PRODUCT IS NOT HAZARDOUS AS DEFINED BY THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200). MIL-L-6082, GRADE 1100 OIL REPRESENTS 99+% OF THE TOTAL VOLUME.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, exp ressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.