

J&R INDUSTRIES INC. -- WS-516 BASE COMPOUND -- 8030-00-148-7362

=====
Product Identification
=====

Product ID:WS-516 BASE COMPOUND

MSDS Date:01/31/1992

FSC:8030

NIIN:00-148-7362

Status Code:A

MSDS Number: CLGRV

=== Responsible Party ===

Company Name:J&R INDUSTRIES INC.

Address:800 E. ANAHEIM STREET

City:WILMINGTON CALIFORNIA

State:CA

ZIP:90744

Country:US

Info Phone Num:310-476-7121

Emergency Phon

e Num:310-476-7121

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:UO504

=== Contractor Identification ===

Company Name:J&R INDUSTRIES INC.

Address:800 E. ANAHEIM STREET

Box:City:WILMINGTON CALIFORNIA

State:CA

ZIP:90744

Country:US

Phone:310-476-7121

CAGE:UO504

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE

CAS:108-88-3

RTECS #:XS5250000

= Wt:4.

OSHA PEL:SEE TABLE Z-2

ACGIH TLV:188 MG/M3;50 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 L

BS

Ingred Name:INACTIVE INGREDIENTS
= Wt:96.

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE
Routes of Entry: Inhalation:UNKNOWN Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:NOT DETERMINED.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:ANEMIA, STOMACH CRAMPS, MUSCLE AND JOINT PAIN,
NEUROMUSCULAR DYSFUNCTION KIDNEY DAMAGE.ANEMIA, STOMACH CRAMPS,
MUSCLE AND JOINT PAIN, NEUROMUSCULAR DYSFUNCTION KIDNEY DAMAGE.
Medical
Cond Aggravated by Exposure:NONE

=====
===== First Aid Measures =====

First Aid:USE NIOSH APPROVED RESPIRATORS, GLOVES & GOGGLES. INGESTION
INDUCE VOMITING. WASH EYES & SKIN WITH PLENTY OF SOAP AND WATER. IN
ALL CASES, CONTACT PHYSICIAN IMMEDIATELT.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Autoignition Temp:Autoignition Temp Text:NONE
Lower Limits:NONE
Upper Limits:NONE
Extinguishing Media:STANDARD COMMERCIAL EXTINGUISHER.
Fire Fighting Procedures:USE A POSITIVE PRESSURE SELF-CONTAINED
BREATHING APPARATUS WITH FULL FACE PIECE.
Unusual Fire/Explosion Hazard:RAPID DECOMPOSITION, WHICH MAY LEAD TO
EXPLOSION.

=====
===== Accidental Release Measures =====

Spill Release Procedures:KEEP ALL SOURCES OF HEAT & SPARKS AWAY. WEAR
PROTECTIVE EQUIPMENT.CLEAN UP SPILL IMMEDIATELY.
Neutralizing Agent:NONE

=====
===== Handling and Storage =====

Ha

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE AWAY FROM SPARKS, HEAT & OPEN FLAME. WASH THOROUGHLY AFTER HANDLING.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR NIOSH APPROVED RESPIRATOR.

Ventilation:MECHANICAL VENTILATION.

Protective Gloves:PROTECTIVE GLOVES: GLOVES.

Eye Protection:GOGGLES.

Other Protective Equipment:CLEAN WATER SHOULD BE AVAILABLE IN THE WORK AREA FOR FLUSHING SKIN AND EYES.

Work Hyg

enic Practices:NONE

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

Boiling Pt:=111.1C, 232.F

Melt/Freeze Pt:M.P/F.P Text:NONE

Decomp Temp:>148.9C, 300.F

Vapor Density:3.2

Spec Gravity:(H2O=1)

Evaporation Rate & Reference:0.8

Solubility in Water: