

EASTMAN KODAK COMPANY -- 812 1188,WKG SOL,KODAK T-MAX 100 DIRECT POS FILM REV BLEACH -- 6750-01-097-0773

=====  
Product Identification  
=====

Product ID:812 1188,WKG SOL,KODAK T-MAX 100 DIRECT POS FILM REV BLEACH

MSDS Date:02/04/2001

FSC:6750

NIIN:01-097-0773

Status Code:A

MSDS Number: CLGZH

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SULFURIC ACID (SARA 302/313) (CERCLA)

CAS:7664-93-9

RTECS #:WS5600000

Minumum % Wt:1.

Maxu

Minimum % Wt:5.  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1 MG/M3  
ACGIH TLV:1 MG/M3/3 STEL; 9495  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Minimum % Wt:95.  
Maximum % Wt:100.  
Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM PERMANGANATE (SARA 313) (CERCLA)  
CAS:7722-64-7  
RTECS #:SD6475000  
&lt; Wt:1.  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:C 5 MG(MN)/M3  
ACGIH TLV:5 MG(MN)/M3; 9495  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

=====  
== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:EXPECTED TO BE A LOW HAZARD FOR  
RECOMMENDED HANDLING. EYES: NO SPECIFIC HAZARD KNOWN. MAY CAUSE  
TRANSIENT IRRITATION. SKIN: LOW HAZARD FOR RECOMMENDED HANDLING.  
INGESTION: EXPECTED TO BE A LOW INGESTION HAZARD.  
Explanation of Carcinogenicity:INTERNATIONAL AGENCY FOR RESEARCH ON  
CANCER (IARC)  
C): GROUP 1, STRONG INORGANIC MISTS OR VAPORS CONTAINING  
SULFURIC ACID - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL  
HYGIENISTS (ACGIH) (SULFURIC ACID): SUSPECTED HUMAN CARCINOGEN  
(A2) - NATIONAL TOXICOLOGY PROGRAM (NTP): NONE - OCCUPATIONAL  
SAFETY AND HEALTH ADMINISTRATION (OSHA): NONE  
Effects of Overexposure:EXPECTED TO BE A LOW HAZARD FOR RECOMMENDED  
HANDLING. EYES: NO SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIENT  
IRRITATION. SKIN: LOW HAZARD FOR RECOMMENDED HANDLING

. INGESTION:

EXPECTED LOW INGESTION HAZARD.

Medical Condition Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid: INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. TREAT SYMPTOMATICALLY. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: ANY MATERIAL THAT CONTACTS EYE SHOULD BE WASHED OUT IMMEDIATELY WITH WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKIN: WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION: DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point: NONE, NON-COMBUSTIBLE  
Extinguishing Media: USE APPROPRIATE AGENT FOR ADJACENT FIRE.  
Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING.  
Unusual Fire/Explosion Hazard: NONE.

===== Accidental Release Measures =====

Spill Release Procedures: ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATERIAL, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE THOROUGHLY TO REMOVE RESIDUAL CONTAMINATION.  
Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions: KEEP CONTAINER CLOSED. KEEP AWAY FROM INCOMPATIBLE SUBSTANCES (SEE INCOMPATIBILITY SECTION).  
Other Precautions: AVOID BREATHING MIST AT CONCENTRATIONS GREATER THAN THE EXPOSURE LIMITS. AVOID CONTACT WITH EYES AND PROLONGED OR REPEATED CONTACT WITH SKIN. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NONE SHOULD BE NEEDED. IF ENGINEERING CONTROLS DO NOT MAINTAIN AIRBORNE CONCENTRATIONS BELOW RECOMMENDED EXPOSURE LIMITS, AN APPROVED RESPIRATOR MUST BE WORN. RESPIRATOR TYPE: ACID GAS. IF RESPIRATORS

ARE USED, A PROGRAM SHOULD BE INSTITUTED TO ASSURE COMPLIANCE WITH OSHA STANDARD 29 CFR 1910.134.

Ventilation:GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES PER HOUR) SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS.

Protective Gloves:FOR PROLONGED OR REPEATED CONTACT, WEAR IMPERVIOUS GLOVES.

Eye Protection:WEAR SAFETY GLASSES WITH SIDE SHIELDS (OR GOGGLES).

Other Protective Equipment:EYE BATH, SAFETY SHOWER, WASHING FACILITIES

Work Hygienic Practices:IT IS A GOOD INDUSTRIAL HYGIENE PRACTICE TO MINIMIZE SKIN CONTACT.

Supplemental Safety and Health

THIS IS A FIVE PART KIT, SAME NSN AND CAGE. FOR OTHER APRTS, SEE MSDS #CLGZC, CLGZD, CLDZK, AND CLHBT.

===== Physical/Chemical Properties =====

HCC:C3

Boiling Pt:>100.C, 212.F

Vapor Pres:68F: 24MBAR(18 MM HG)

Vapor Density:0.6

Spec Gravity:1.01

pH:100. DAPHNID EC50

MG/L:> 100. ALGAL IC50 MG/L: >100. ORGANICS: N/A. POTENTIAL BIOACCUMULATION: LOG POW 100.

=====

===== Disposal Considerations =====

Waste Disposal Methods:CONTRACT WITH A LICENSED CHEMICAL DISPOSAL AGENCY. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE, FOLLOW LABEL WARNINGS EVEN AFTER CONTAINER IS EMPTIED.

===== MSDS Transport Information =====

Transport Information:CALL KODAK HOTLINE: 716-722-2400

===== Regulatory Information =====

SARA Title III Information:CHEMICALS SUBJECT TO THE RE

PORTING

REQUIREMENTS OF SEC 313/TITLE III (40CFR 372): POTASSIUM  
PERMANGANATE.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.