View NSN Online: https://aerobasegroup.de/nsn/6140-01-441-3512

Product ID:SEALED LEAD BATTERY (CLOSED CYLINDRICAL) MSDS Date:03/01/1990 FSC:6140 NIIN:01-441-3512 Status Code:A **MSDS Number: CLHDP** === Responsible Party === Company Name: HAWKER ENERGY PRODUCTS INC (GATES ENERGY PRODUCTS, INC) Address:617 NORT H RIDGEVIEW DR City:WARRENSBURG State:MO ZIP:64093-9301 Country:US Info Phone Num:800-730-7733 Emergency Phone Num: (816) 429-2165 CAGE:0WY95 === Contractor Identification === Company Name: CELL ENERGY INC Address:3190-B ORANGE GROVE AVE Box:City:NORTH HIGHLANDS State:CA ZIP:95660-5706 Country:US Phone:916-484-7974 Contract Num:SP0430-01-M-FL50 CAGE:1U269 Company Name: HAWKER ENERGY PRODUCTS INC Address:617 NORTH RIDGEVIEW DR Box:City:WARRENSBURG State:MO ZIP:64093 Country:US Phone:660-429-7528 / 8

00-964-2837 CAGE:0WY95

Ingred Name:LEAD - LEAD OXIDES = Wt:69. ACGIH TLV:0.05 UG/M3

Ingred Name:SULFURIC ACID ELECTROLYTE = Wt:21. ACGIH TLV:1 MG/M3

Ingred Name:NON-HAZARDOUS MATERIALS = Wt:10.

Health Hazards Acute and Chronic:NOT APPLICABLE FOR FINISHED PRODUCT USED IN NORMAL CONDITIONS. STATEMENT INCLUDED WITH MSDS FROM RESPONSIBLE PARTY: "THE

GATES SEALED LEAD ACID BTTERY IS DETERMINED TO BE AN "ARTICLE" ACCORDING TO THE OSHA HAZARD COMMUNICATION STANDARD AND IS THEREBY EXCLUDED FROM ANY REQUIREMENTS OF THE STANDARD. THE ATTACHED MATERIAL SAFETY DATA SHEET IS THEREFORE SUPPLIED FOR INFORMATION PURPOSES ONLY."

First Aid:BATTERY CONTAINS ACID ELECTROLYTE. IF BATTERY CASE IS PUNCTURED, COMPLETELY FLUSH ANY RELEASED MATERIAL FROM SKIN OR EYES

WITH WATER.

Flash Point:NON-FLAMMABLE

Lower Limits:/A

Extinguishing Media:MULTI-PURPOSE DRY CHEMICAL OR MULTI-PURPOSE CO2. Fire Fighting Procedures:COOL BATTERY EXTERIOR TO PREVENT RUPTURE. ACID MISTS AND VAPORS IN A FIRE ARE TOXIC AND CORROSIVE. Unusual Fire/Explosion Hazard:HYDROGEN GAS MAY BE PRODUCED AND MAY

EXPLODE IF IGNITED. REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA.

======= Accidental Release

Measures ===============

Spill Release Procedures: AVOID CONTACT WITH ACID MATERIALS. USE SODA ASH OR LIME TO NEUTRALIZE. FLUSH WITH LARGE AMOUNTS OF WATER. Neutralizing Agent: SODA ASH OR LIME.

Other Precautions: READ MANUFACTURERS LITERATURE, WHICH IS AVAILABLE UPON REQUEST.

======= Exposure Controls/Personal Protection ==========

Supplemental Safety and Health

======= Physical/Chemical P

roperties ==============

HCC:Z4

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:AVOID SHORTING. USE ONLY APPROVED CHARGING METHODS. DO NOT PUNCTURE BATTERY CASE.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

Waste Disposal Methods:PLACE IN ACID RESISTANT CONTAINERS. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND L OCAL REGULATIONS. DO NOT INCINERATE.

Transport Information:AS AN " ARTICLE" THIS PRODUCT IS EXCLUDED FROM ANY REQUIREMENTS OF THE STANDARD. THIS IMPLIES THAT BATTERY MEETS REQUIREMENTS OF REGULATIONS UNDER 49 CFR 173.159(D) AND REQUIRES THAT BATTERIES BE PROT ECTED AGAINST SHORT CIRCUITS AND SECURELY PACKAGED AND THE BATTERY AND OUTER PACKAGING PLAINLY AND DURABLY MARKED "NONSPILLABLE" OR "NONSPILLABLE

## BATTERY". ALSO THE BATTERIES

MUST BE CAPABLE OF WITHST ANDING , WITHOUT LEAKAGE OF BATTERY FLUID, THE VIBRATION TEST AND THE PRESSURE DIFFERENTIAL TEST SPECIFIED IN 49 CFR 173.159(D)(3)(I) AND (I I).

pressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.