

GRIGGS PAINT -- TPD-24607 #25526 NON-FLAMING 700L78 -- 8010-01-344-5059

=====
Product Identification
=====

Product ID:TPD-24607 #25526 NON-FLAMING 700L78

MSDS Date:05/01/1995

FSC:8010

NIIN:01-344-5059

Status Code:A

MSDS Number: CLHZB

=== Responsible Party ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

City:PHOENIX

State:AZ

ZIP:85040

Country:US

Info Phone Num:602-243-3293

Emergency Phone N

um:(800)424-9300

Preparer's Name:HENRY SIMMONS

Chemtre Ind/Phone:(800)424-9300

CAGE:58963

=== Contractor Identification ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

Box:City:PHOENIX

State:AZ

ZIP:85040

Country:US

Phone:602-243-3293

CAGE:58963

=====
Composition/Information on Ingredients
=====

Ingred Name:AROMATIC PETROLEUM DISTILLATES

< Wt:5.

Ingred Name:MAGNESIUM SILICATE

< Wt:5.

Ingred Name:ALIPHATIC HYDROCARBON(STODDARD TYPE)

= Wt:7.

=====

== Hazards Identification ==

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:DIRECT CONTACT TO EYES MAY CAUSE IRRITATION, PROLONGED AND/OR REPEATED CONTACT MAY CASE SKIN IRRITATION. INHALATION OF HIGH CONCENTRATION OF VAPORS MAY LEAD TO LUNG CHANGES, NAUSEA, VOMITING, COUGH, PULMONARY IRRITATION, AND CENTRAL NERVOUS SYSTEM DEPRESSION. INGESTION MAY CAUSE GASTROINTESTINAL DISTURBANCES. ASPIRATION OF THIS PRODUCT INTO THE

LUNGS MAY CAUSE PNEUMONITIS, PULMONARY EDEMA AND HEMORRHAGE.

Effects of Overexposure:INHALATION-BREATHING OF HIGH VAPOR CONCENTRATIONS MAY CAUSE DROWSINESS. DIZZINESS, FATIGUE, FOLLOWED BY COMA. EYE: DIRECT CONTACT AND/OR CONTACT WITH VAPORS MAY CAUSE IRRITATION. SKIN: PROLONGED AND /OR REPEATED CONTACT MAY CAUSE IRRITATION AND/OR DERMATITIS. MAY BE ABSORBED THROUGH THE SKIN. SKIN ABSORPTION-PROLONGED OR REPEATED EXPOSURE CAN CAUSE MODERATE IRRITATION, DEFAT

TING , AND DERMATITIS . INGESTION-ASPIRATION OF THIS PRODUCT INTO THE LUNGS MAY CAUSE PNEUMONITIS, PULMONARY EDEMA AND HEMORRHAGE. INGESTION MAY CAUSE GASTROINTESTINAL DISTURBANCES.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING DISEASE IN OR HISTORY OF AILMENTS INVOLVING SKINCENTRAL NERVOUS SYSTEM, LIVER AND KIDNEY.

==== First Aid Measures =====

First Aid:EYE CONTACT: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF 15 MINUTES. SEEK MEDICAL AID SKIN: WASH THOROUGHLY WITH SOAP AND WATER. SEEK MEDICAL AID IF IRRITATION PERSISTS. INGESTION: IMMEDIATELY SEEK MEDICAL AID. DO NOT INDUCE VOMITING. DO NOT ATTEMPT TO GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

==== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:=-37.8C, 100.F

Lower Limits:1.0

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:APPROVED GAS MASK REQUIRED FOR

R FIRE FIGHTING

PERSONNEL. WATER MAY BE USED TO COOL CONTAINERS. IF WATER IS USED, FOG NOZZLES ARE PREFERRED.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:STOP LEAK IF NO RISK INVOLVED. REMOVE ALL SOURCES OF IGNITION. STAY UPWIND. ABSORB WITH INERT MATERIAL. FLUSH AREA WITH WATER. VENTILATE AREA AT LEAST 24 HOURS OR UNTIL AREA HAS BEEN DECLARED SAFE.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED AND UPRIGHT TO PREVENT LEAKAGE. AVOID FLAMES, WELDING, OPEN LIGHTS, ETC. AVOID BREATHING OF VAPOR AND SPRAY MIST. AVOID SKIN AND EYE CONTACT.

Other Precautions:MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN CONFINED AREAS, TANK OR PIT, WITHOUT ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION BELOW TLV(PEL), USE MSHA/NIOSH APPROVED UNITS PER CURRENT 29 CFR1910.134 AND FOLLOW MANUFACTURER'S INSTRUCTIONS AND WARNINGS. IF WITHIN OSHA PROTECTION FACTOR, AIR PURIFYING OVER/FILTER UNITS OK FOR USE.

Ventilation:LOCAL AND MECHANICAL EXHAUST.

Protective Gloves:RUBBER GLOVES.

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS OR GOGGLES.

Other Protective Equipment:EYE BATH AND SAFETY SHOWER.

Work Hygienic Practices:MAINTAIN GOOD PERSONAL HYGIENE, DO NOT USE IN CONFINED AREAS.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt.=160.C, 320.F

B.P. Text:320-334F

Vapor Density:>AIR

Spec Gravity:1.6

VOC Pounds/Gallon:339

VOC Grams/Liter:2.83

Solubility in Water:ESSENTIALLY NIL.

Appearance and Odor:VISCOUS LIQUID WITH TYPICAL PAINT ODOR

===== Stability

and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: FLAMES, SPARKS, SMOKING AND HEAT.

Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods: USE INERT ABSORBENT MATERIALS OR SPILLS. DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.