

MOBIL OIL CORP, AVIATION AND GOVT SALES DIV -- AVREX S TURBO 256 -- 9150-00-782-2627

=====
Product Identification
=====

Product ID:AVREX S TURBO 256

MSDS Date:06/18/1998

FSC:9150

NIIN:00-782-2627

Status Code:A

MSDS Number: CLJHY

=== Responsible Party ===

Company Name:MOBIL OIL CORP, AVIATION AND GOVT SALES DIV

Address:3225 GALLOWS ROAD

City:FAIRFAX

State:VA

ZIP:22037

Country:US

Info Phone Num:7

03-846-4090; 609-224-4644

Emergency Phone Num:609-737-4411

Resp. Party Other MSDS Num.:494237-00

Chemtrec Ind/Phone:(800)424-9300

CAGE:3U728

=== Contractor Identification ===

Company Name:MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWS ROAD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525/ 856-224-4644

CAGE:3U728

=====
Composition/Information on Ingredients
=====

Ingred Name:HYDROCARBONS AND ADDITIIVES

Ingred Name:1-NAPHTHALENAMINE

, N-PHENYL-

CAS:90-30-2

RTECS #:QM4500000

Minumum % Wt:1.

Maxumum % Wt:5.

=====
Hazards Identification
=====

LD50 LC50 Mixture:LD50 RATS: >2000MG/KG

Health Hazards Acute and Chronic:NO SIGNIFICANT EFFECTS EXPECTED.

Effects of Overexposure:NO SIGNIFICANT EFFECTS EXPECTED.

=====
First Aid Measures
=====

First Aid:EYE: FLUSH THOROUGHLY WITH WATER. IF IRRITATION OCCURS, CALL
A PHYSICIAN. SKIN: WASH CONTACT AREAS WITH SOA

P AND WATER.

INHALTION: REMOVE FROM FURTHER EXPOSURE. IF RESPIRATORY IRRITATION, DIZZINESS, N AUSEA, OR UNCONSCIOUSNESS OCCURS, SEEK IMMEDIATE MEDICAL ASSISTANCE. IF BREATHING HAS STOPPED, ASSIST VENTILATION WITH BAG-VALVE-MASK DEVICE OR USE-MOUTH-TO-MOUTH RESUSCITATION. INGESTION: SEEK IMMEDIATE MEDICAL ATTENTION. DO NOT INDUCE VOMITING. NOTE TO PHYSICIAN: MATERIAL IF INGESTED MAY BE ASPIRATED INTO THE LUNGS AND CAN CAUSE CHEMICAL PNEUMONITIS. TREAT APPROPRIATEL

Y.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:≈210.C, 410.F

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL AND WATER FOG.

Fire Fighting Procedures:WATER/FOAM MAY CAUSE FROTHING. USE WATER TO KEEP FIRE EXPOSED CONTAINER COOL. WATER SPRAY MAY BE USED TO FLUSH SPILL AWAY FROM EXPOSURE. PREVENT RUNOFF FROM FIRE CONTROL/DILUTION FROM ENTERING STREAMS , SEWERS, OR DRINKING WATER SUPPLY. NO FIRES IN ENCLOSED AREA, FI

RE FIGHTER MUST USE SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:NEUROTOXIC FUMES MAY BE GENERATED.

CAUTION- THERMATALLY DECOMPOSED RESIDUES MAY BE NEUROTOXIC.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ABSORB ON FIRE RETARDANT TREATED SAWDUST, DIATOMACEOUS EARTH ETC. SHOVEL UP AND DISPOSE OF AT AN APPROPRIATE WASTE DISPOSAL FACILITY IN ACCORDANCE WITH CURRENT APPLICABLE LAWS AND REGULATIONS, AND PRO DUC

T CHARACTERISTICS AT TIME OF DISPOSAL.

PREVENT SPILLS FROM ENTERING STORM SEWERS OR DRAINS AND CONTACT WITH SOIL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:NO SPECIAL PRECAUTIONS ARE NECESSARY BEYOND NORMAL GOOD HYGIENE PRACTICES. DO NOT STORE IN OPEN OR UNLABELLED CONTAINERS. STORE AWAY FROM STRONG OXIDIZING AGENTS OR COMBUSTIBLE MATERIAL.

=====
===== Exposure Controls/Personal Protection =====

Respir

atory Protection:NO SPECIAL REQUIREMENTS UNDER ORDINARY
CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.

Ventilation:USE IN WELL VENTILATED AREA.

Protective Gloves:NO SPECIAL EQUIPMENT REQUIRED.

Eye Protection:NORMAL INDUSTRIAL EYE PROTECTION PRACTICES FOLLOWED

Other Protective Equipment:NO SPECIAL EQUIPMENT REQUIRED.

Work Hygienic Practices:GOOD PERSONAL HYGIENE PRACTICES SHOULD ALWAYS
BE FOLLOWED.

Supplemental Safety and Health

THIS NSN REPLACES CANCELLED NSN: 9150-00-159-4882.

=====

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:>316.C, 600.8F

Vapor Pres: