

SIKA CORPORATION -- SIKAFLEX-LA:*ALL COLORS -- 8030-00-965-2397

=====
Product Identification
=====

Product ID:SIKAFLEX-LA:*ALL COLORS

MSDS Date:03/22/1985

FSC:8030

NIIN:00-965-2397

Status Code:A

MSDS Number: CLJLT

=== Responsible Party ===

Company Name:SIKA CORPORATION

Address:875 VALLEY BROOK AVENUE

City:LYNDHURST

State:NJ

ZIP:07071

Info Phone Num:800-424-9300

Emergency Phone Num:(800)424-9300

P

reparer's Name:HENRY SIMMONS

Chemtrec Ind/Phone:(800)424-9300

CAGE:OPMN0

=== Contractor Identification ===

Company Name:SIKA CORPORATION

Address:875 VALLEY BROOK AVENUE

City:LYNDHURST

State:NJ

ZIP:07071

Phone:800-424-9300

CAGE:OPMN0

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENE

CAS:1330-20-7

RTECS #:ZE2100000

= Wt:5.

ACGIH TLV:434 MG/M3;100 PPM

ACGIH STEL:651 MG/M3;150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:CALCIUM OXIDE

CAS:1305-78

-8
RTECS #:EW3100000
= Wt:1.
OSHA PEL:5 MG/M3
ACGIH TLV:2 MG/M3

Ingred Name:TITANIUM DIOXIDE
= Wt:6.
OSHA PEL:15 MG/M3
ACGIH TLV:15 MG/M3

Ingred Name:CARBON BLACK
= Wt:2.
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Effects of Overexposure:SKIN IRRITANT

EYE IRRITANT

SIKAFLEX-LA TESTED ACCORDING TO FHSLA
16 CFR-1500 HAS SHOWN:

1. PRIMARY SKIN IRRITANT
2. EYE IRRITANT
3. NOT TOXIC ORALLY
4. NOT TOXIC BY INHALATION
5. NOT TOXIC DERMALLY

Medical Cond Aggravated by Exposure:PRESENTIZATION TO PRODUCT

=====
===== First Aid Measures =====

First Aid:SKIN: WASH THOROUGHLY WITH SOAP AND WATER. EYES: FLUSH WITH
COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. OBTAIN MEDICAL
ATTENTION. INHALATION: MOVE TO AN AREA FROM RISK OF FURTHER
EXPOSURE. INGESTION: OBTAIN MEDICAL ATTENTION IMMEDIATELY. DO NOT
INDUCE VOMITING.

=====
===== Fire Fighting Measures =====

Flash Point:61.7C, 143.F

Lower Limits:1.0

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:PERSONNEL ENGAGED IN FIGHTING FIRES MUST BE
PROTECTED AGAINST NITROGEN DIOXIDE FUMES AND SHOULD WEAR
SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:DURING A FIRE IRRITATING TOXIC GASES
AND/OR AEROSOLS FROM THE D

ECOMPOSITION/COMBUSTION PRODUCTS MAY BE
PRESENT

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN WITH CLOTH OR ABSORBENT PAPER. IF AREA
ENCLOSED, VENTILATE

===== Handling and Storage =====

Handling and Storage Precautions:32F MINIMUM ? 122F MAXIMUM. IF CLOSED
CONTAINER OF MATERIAL IS EXPOSED TO HEAT, PRESSURE CAN BUILD UP. IF
MOISTURE ENTERS, PRESSURE BUILDUP DUE TO REACTION.

Other Precaution

s:KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. STORE IN
TIGHTLY CLOSED CONTAINER AND PROTECT FROM MOISTURE AND FOREIGN
MATERIALS. AT MAXIMUM STORAGE TEMPERATURES NOTED, MATERIAL MAY
POLYMERIZE WITHOUT HAZARD. IDEAL STORAGE TEMPERATURE IS 50-80F.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE

Ventilation:LOCAL EXHAUST RECOMMENDED

Protective Gloves:CHEMICALLY RESISTANT RUBBER OR PLASTIC

Eye Protection:SAFETY GLASSES OR CHEMICAL GOGGLE

S

Work Hygienic Practices:AS REQUIRED BY YOUR COMPANY.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume: